

## FEATURES

- Pre-calibrated single-holes fiber optic wire stripper (125 micron).
- Ergonomic anti-slip bi-component handle for a safe, light and comfortable grip
- Anti-reflection phosphating surface treatment
- Closing stop lever
- Laser marking
- Made in Italy

# RS PRO Pre-calibrated single-holes fiber optic wire stripper (125 micron)

RSPRO Stock No.: 238-0716



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

- *Made in Italy with special carbon steel and undergo a controlled atmosphere heat treatment.*
- *The anti-reflection phosphating surface treatment ensures an accurate view of the work being carried out.*
- *The tools are joined with grounded holes and surfaces, thereby allowing precise movements.*
- *The anti-slip bi-material dolphin handle is created following ergonomic principles, thus guaranteeing a safe, light and comfortable grip for the operator even when used constantly for many hours*
- *Adjustable single -holes fiber optic wire stripper (125micron). Closing stop lever.*

## General Specifications

|                         |   |
|-------------------------|---|
| <b>Plier Type</b>       | Pre-calibrated single -holes fiber optic wire stripper (125 micron) |
| <b>Non-Sparking</b>     | Yes   |
| <b>Material</b>         | Carbon Steel  |
| <b>Number Of Pieces</b> | 1   |
| <b>Finish</b>           | Anti-reflection phosphating surface treatment, red grip             |

## Electrical Specifications

|                 |    |
|-----------------|----|
| <b>ESD Safe</b> | no |
|-----------------|----|

## Mechanical Specifications

|                                 |            |
|---------------------------------|------------|
| <b>Wire stripper capability</b> | 125 micron |
| <b>Overall Length</b>           | 145 mm     |
| <b>Weight</b>                   | 83 g       |
| <b>Steel Thickness</b>          | 3 mm       |

