




# **Datasheet**

# RS Pro Simplex/Duplex Patch Cord

**RS Stock No: 121-3933** 



### **Description:**

Multimode patch cords are used to connect high speed and legacy networks like 10/40/100 gigabit ethernet, fast ethernet and ethernet. Multimode patch cords are manufactured using LSZH cable and conform to Telcordia, EIA TIA or IEC standards. The OM4 patch cords are terminated with standard connectors which gives optimum optical performance.

#### **Features:**

- FC, LC, MTRJ, SC, and ST connectors
- Low smoke zero halogen (LSZH) cable in aqua or erika violet colour
- 900  $\mu$ m / 600  $\mu$ m tight buffer
- OM4 fibre conforms to ITU-T G.651.1, TIA/EIA 492AAAD, IEC60793-2-10 A1a.3a
- Simplex and duplex assembly options
- SC and LC duplex assemblies available with clips
- Higher optical performance available on request
- Armoured option also available
- REACH, RoHS & SvHC materials compliant





# **Specifications:**

Specifications.			
Connector Specification:-			
Optical Performance	Multimode		Conformance
IL Max/Master (Acceptance)	0.25dB		IEC 61300-3-4
Ave/Master	0.15dB		IEC 61300-3-4
Ave/Random	0.20dB		IEC 61300-3-34
Note: Return loss > 28dB based on sample data using method IEC 61300-3-6			
Cable Specification:-			
Characteristics	Simplex		Duplex
Cable Material	LSZH		LSZH
Strength Member	Aramid		Aramid
Crush (N)	1000		1000
Operating Temperature (°C)	-20 to 60		-20 to 60
Fire Specification	IEC 60332-1		IEC 60332-1
Fibre Specification:-			
Characteristics:-			
Attenuation (dB/km)		2.8 @ 850nm / 0.8 @ 1310nm	
Bandwidth OFL (MHz x km)		3500 @ 850nm / 500 @ 1310nm	
Bandwidth LEMB (MHz x km)		4700 @ 850nm	

## **Applications**

- For use in 10Gb/s high speed LAN networks over a 400m indicative link length at 850nm (SX) wavelength using a laser launch
- For use in 1Gb/s high speed LAN networks over a 1000m indicative link length at 850nm (SX) wavelength using a laser launch
- High speed and legacy networks including Gigabit Ethernet, Fast Ethernet and Ethernet
- Data centers
- Premises cabling in data networks including backbone, riser and horizontal
- Supports video, data and voice services