E3034H1_EBGS_G2

Neo, 250V, 4 G, 1 W, Horizantol Dolly Switch, With white LED, WP plus WS





Main Range Neo Product or component Control switch type Device application Control Surface Wiring device mounting Flush Switch function 1-way Switch Switch application Incandescent lamp Load type Fluorescent lamp Resistive Inductive

LED (white)

Grey silver

Complementary

Rated current	10 A at 250 V AC 50/60 Hz	
Number of gangs	4 gangs horizontal	
Material	Brass: metal parts Polycarbonate: plastic part Steel: metal parts	
Clamping connection capacity	3 x 2.5 mm² for solid cable(s) 3 x 2.5 mm² for stranded cable(s) 4 x 1.5 mm² for solid cable(s) 4 x 1.5 mm² for stranded cable(s)	
Connections - terminals	Pillar terminals	
Width	87 mm	
Height	87 mm	
Embedding depth	23.5 mm	
Depth	36 mm	

Bulb type Colour tint

Environment

Ambient air temperature for operation	040 °C
Relative humidity	095 %
Environmental characteristic	Indoor use
Standards	GB 16915.1 EN 60669-1 IEC 60669-1

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.6 cm	
Package 1 Width	8.7 cm	
Package 1 Length	8.7 cm	
Package 1 Weight	102 g	
Unit Type of Package 2	BB1	
Number of Units in Package 2	8	
Package 2 Height	15 cm	

Package 2 Width	19 cm
Package 2 Length	8 cm
Package 2 Weight	830 g
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	21 cm
Package 3 Width	31 cm
Package 3 Length	50 cm
Package 3 Weight	9300 g

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	