

Datasheet

## RS Pro 2 Output Toroidal Transformer, 50VA, 2 x 55V ac

RS Stock No: **671-9101**



### Product Details

RS Pro 2 output toroidal transformer is a small size and low weight with traditional stacked laminated transformers. It has both primary and twin secondary windings connected in series or parallel. This transformer has primary voltage rating of 115 V ac, 230 V ac, secondary voltage rating of 2 x 55 V ac and power rating of 50 VA. Toroidal transformer meets EN 61558, IEC 742, UL 506, UL 1411, UL 478 and CE certified.

### Features and Benefits

- Low induced noise (hum)
- Low level of radiated magnetic field
- Flexible leadouts for ease of installation
- 100% electrical and flash testing

**Specifications:**

Diameter	80 mm
Dimensions	80 (dia.) x 33 mm
Height	33 mm
Maximum Operating Frequency	60 Hz
Minimum Operating Frequency	50 Hz
Number of Outputs	2
Power Rating	50 VA
Primary Voltage Rating	115 V ac, 230 V ac
Secondary Current	0.455 A
Secondary Voltage Rating	2 x 55 V ac
Termination Type	Copper Conductor
Weight	740 g
Construction	Open
Standards Met	UL 506, IEC 61558 Class II, EN 61558 Class II, VDE0570 Class II, RoHS Compliant

