

FEATURES

- **Stainless steel shackles with screw pin**
- **Jaw Width of 31mm**
- **Pin diameter of 16mm**
- **This Chain Shackle deals well with weather conditions**

RS PRO D-Shackle, Stainless Steel, 0.75t

RS Stock No.: 312-3522



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

The usability of Shackles, also referred to as gyve reaches hundreds of years. Shackles built their reputation as the simple, but solid construction providing the most cost-effective method of attaching the anchor with chain. The primary purpose is lifting heavy objects and equipment. Basic models are available for domestic and light use, such as for luggage and tow ropes. The commercial site is using the Shackles to cope with more extreme load capacities and atmospheric conditions. Each Shackle is made of durable and high-quality material, ensuring a perfect connection to the sling and therefore providing excellent reliability. For Shackles that are suitable for lifting, we are strongly recommending checking a weight limit guidance. If using in extreme temperatures (more than + 200°C or - 40°C) always consult this with either a manufacturer or distributor.

The Shackle consists of 2 parts, which is the body and the pin (or bolt). The body can have different shapes. Therefore, you can see on the market Bow Shackles, D Shackles, Green Pin Shackles, Safety Pin Shakes, Screw Pink Shackles, Stainless-Steel and Pilling Shackles. Another way of identifying Shackles are by pin types, such as round pin and cotter (class 1), screw (class 2) and bolt, nut and cotter pin (class 3). We are proudly introducing our won branded RS PRO Stainless-Steel D Shackle recognizable as they are narrower than a Bow Shackle and, in most cases, they have a threaded pin or pin close. The purpose of their existence is to serve for an in-line load, which explains why the loop is so small. The material of this D-Shackle is stainless-steel meaning it can be subjected to climatic factors. This D-Shackle (known as Chain Shackle) with 16 mm diameter, withstands of the 0.75-ton is a perfect solution to secure your loads.

General Specifications

Shackle Type	D-Shackle
Pin Type	Screw Pin
Safe Working Load	0.75t
Material	Stainless Steel
Application	Wire Rope Slings, Moderate to heavy lifting loads, Industrial crane rigging on board large ships, Commonly used in personal safety gear including climbing and mountaineering harnesses

Mechanical Specifications

Shackle Diameter	16mm
Jaw Width	31mm
Pin Diameter	16mm

Operation Environment Specifications

Approved for use at	-40°C to 204°C
---------------------	----------------

Approvals

Standards Met	ANSI/ESD S20.20:2014 and BS EN 61340-5-1:2007
---------------	---

