multicomp PRO

Construction

ltem	Material	Diameter	
		(Inch)	(mm)
Inner Conductor	Copper Covered Steel - CCS	0.023 ±0.001	0.58 ±0.03
Dielectric	Solid PE	0.146 ±0.004	3.7 ±0.1
Shield	80% Copper Braid	0.185 ±0.004	4.7 ±0.1
Jacket	LSZH-black	0.242 ±0.004	6.15 ±0.1

Electrical Characteristics

Impedance	: 75Ω ±3Ω
Capacitance	: 67pF/m
Velocity of Propagation	: 66%
Max. Operating Frequency	: 1GHz
Max. Operating Voltage	: 1700 RMS
Corona Extinction Voltage	: 2300VRMS
Voltage Withstand	: 7000VRMS
Spark Test	: 5000VRMS
Operating Temp. Range	: -40°C to +85°C

Attenuation (@20°C)

Frequency (MHz)	Max. Attenuation (dB/100ft)	Max. Attenuation (dB/100m)
10	1.1	3.6
50	2.6	8.5
100	3.4	11.1
200	5.2	16.9
400	7.2	23.5
600	9.2	30.2
860	10.9	35.6
1000	12	39.5

Part Number Table

Description	Length	Part Number
Coaxial Cable, RG59, LSZH, Black	Per Meter or 100 Meter	RG59 LSZH

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

