

FlashCheck® Min-Max Alarm Digital Thermometer

Features

- Measuring range from -50°C to 70°C (-58°F to 158°F)
- Highly accurate up to $\pm 0.5^{\circ}\text{C}$ ($\pm 1^{\circ}\text{F}$)
- High/low alarm settings
- Minimum/Maximum memory for lowest & highest readings
- Jumbo Large LCD
- Detachable external sensor with gold plated stereo jack
- Blunt probe sensor with 3 meter (10 foot) cable
- Non-volatile memory retains settings during battery swaps



Applications

- Freezers, refrigerators, display cases, storage & packing areas, water tanks & coolers.

Model	12217
Measuring Range	-50°C to 70°C (-58°F to 158°F)
Operating Range	-10°C to 50°C (14°F to 122°F)
Accuracy	$\pm 1.0^{\circ}\text{F}$ (-22°F to 131°F) $\pm 0.5^{\circ}\text{C}$ (-30°C to 55°C); otherwise $\pm 1.8^{\circ}\text{F}$ ($\pm 1.0^{\circ}\text{C}$)
Display Resolution	0.1°F/°C
Display Reading Update	17 seconds
Sensor	Thermistor
External Probe Type / Size	Stainless Steel, 17.8mm L x 5mm Dia (0.7in L x 0.2in Dia)
Sensor Cable	3 meters x 2mm Dia (9.84ft x 0.08in Dia)
Battery	AA Battery, user replaceable
Dimension	76mm x 95mm x 19 mm