



## Datasheet

# RS PRO FULLY-COATED ZigZag STAINLESS STEEL CABLE TIES

RS Stock No. 1834158,1834159,1834160,1834161

EN



### Technical Information:

**Material:** Stainless Steel Grade 316

316 grade stainless steel, for extra corrosive environments

**Coating:** Polyester

**Working Temp.:** -80°C to +150°C

**Description:** Entirely Black

**Flammability:** Fireproof

**Other Properties:** UV-resistant, Halogen free, non toxic

**Product Feature:** The cable ties are self locking with a roller ball head, making them fast and easy to secure. The zig zag design maintains installed tension on surfaces, helping to reduce movement and slips.

Fully coated version with non-toxic, halogen free polyester coating, provide additional edge protection.

**Applications:** Ideal for petrochemical, industries, power stations, mining, ship-building, offshore, and other aggressive environments.

## Specification

RS CODE	EASE CODE	LENGTH		WIDTH		TICKNESS		MAX. BUNDLE DIAMETER	
		mm	inch	mm	inch	mm	inch	mm	inch
1834158	CT-SS-ZZ-100/4.6FC	100	3.9					25	0.99
1834159	CT-SS-ZZ-200/4.6FC	200	7.9	4.6	0.18	0.35	0.014	50	1.97
1834160	CT-SS-ZZ-360/4.6FC	360	14.2					90	3.55
1834161	CT-SS-ZZ-200/7.9FC	200	7.9	7.9	0.31	0.35	0.014	50	1.97