

FEATURES

- The lead wire is held by soldering in a large solder bucket, The product is also supplied with a large diameter insulating cover that accepts cables with a maximum outside diameter of 7,1mm. Gold spec - GOLD 0.5 MICRONS Cu/Cu/Au0.5

RS PRO Blue Male Banana Connectors-Green

RS Stock No.: 2121252



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

Looking to make your own test leads, then RS PRO has the perfect addition in the 4 mm banana plug. This silver plated plug is the ideal solution for making test leads to your specification. Upon inspection, the plug connector offers high-grade acetal plastic insulation with a centre contact made from nickel-plated brass and solder termination method. It accepts test lead cables with a 7.1 mm diameter and is suitable for any 4 mm insulated or non-insulated socket.

General Specifications

Type	Banana Plug
Colour	Green
Gender	Male
Contact Material	Brass
Contact Plating	Silver

Electrical Specifications

Voltage Rating	50V
Current Rating	16A
Termination Method	Solder
Insulation Material	Acetal C 27021 R

Mechanical Specifications

Length	48.75mm
--------	---------

Approvals

Declarations	RoHS Certificate of Compliance
--------------	--------------------------------

Similar Products

Parameters	Stock# 423-201	Stock# 423-239	Stock# 103-7637	Stock# 454-283
Brand	RS PRO	RS PRO	RS PRO	RS PRO
Colour	Black	Red	Red	Black
Gender	Female	Female	Male	Male
Contact Material	Brass	Brass	Stainless Steel	Brass
Voltage Rating	50V dc	50V dc	50V	1kV
Current Rating	16A	16A	30A	30A
Termination Method	Solder	Solder	Solder	Solder
Insulation Material	POM	POM		PP
Length	52.9mm	52.9mm		

Height Above Panel	24mm to 32mm	24mm to 32mm	24mm to 32mm
Overall Diameter	14mm	14mm	14mm
Thread Size	4BA clearance	4BA clearance	
Maximum Panel Thickness	12.7mm		

Product Dimensions Details

