



1.0 ELECTRICAL

- 1.1 FREQUENCY RANGE: DC-1.8 GHz
- 1.2 NOMINAL IMPEDANCE: 50 OHM
- 1.3 WORKING VOLTAGE: 100 VOLTS MAX
- 1.4 PROOF VOLTAGE: 200 VOLTS

2.0 MATERIALS

- 2.1 BODIES: BRASS PER JIS-C3604
PHOSPHOR BRONZE
- 2.2 CENTER CONTACT: BRASS PER JIS-C3604
PHOSPHOR BRONZE
- 2.3 INSULATION: NYLON PER ASTM D1457 AND ASTM D1710
PBI(DURANBY 3126),UL94V-0

3.0 FINISHES AND OTHERS

- 3.1 SEE BELOW TABLE FOR DETAILS.

4.0 ENVIRONMENTAL

- 4.1 OPERATING TEMPERATURE RANGE: -40° C TO +90° C

2	SMT CONNECTOR	1	Ø1.13
1	23-38 Ø1.13 (50Ω)	1	T.G.G/N
NO	DESCRIPTION	Q'TY	FINISH

APPROVED

by _____ DATE: _____



DESCRIPTION		FME BULKHEAD FRONT MOUNT PLUG + SMT PLUG WHIT Ø1.13 CABLE							
製 圖 檢 圖 總 定	DRAWN	TOLERANCE		品名	YK05-77	日 期	DATE	版 次	REV.
	Yoko	.X	±0.2	TITLE	\ROHS COMPLIANT		07.15.11'		A-0
	CHECK	.XX	±0.1	單位	mm(In)	DWG.NO.	99-0403		
	APPROVAL	.XXX	±0.05	比例	SCALE				
	Jenny	ANGLE	±5°		4:1				