



# DI200-2 EXTENSION LADDER



Traction Cap™ endcaps



Continuous braided polyester rope



Dual action feet



NOT FOR USE  
NEAR ELECTRICITY

✓ TWIST-PROOF®



- STRONG LOCKS AND FEET
- DEEP RUNGS FOR STANDING
- SAFE WIDE BASE

**225lb**  
LOAD CAPACITY



# DI200-2

## 225lb

### LOAD CAPACITY

#### Type 2 Duty Rating

Combined Weight of User and Materials

Traction Cap™ endcaps

Interlocking side rails

Rope and pulley system

Continuous braided polyester rope

Spring loaded locks

Slip-resistant Traction-Tred® D-rungs

Dual action feet

- Lightweight aluminum construction
- Twist-Proof® Alflo® rung joint
- Strong locks and feet
- Deep rungs for standing
- Safe wide base
- Traction Cap™ endcaps

## SPECIFICATIONS

Model No.	Size (ft)	Max. Safe Working Height (ft)	Max. Open Extended Length (ft)	Approx. Closed Length (ft)	Reach Height (ft)	Approx. Shipping Weight (lbs)
D1216-2*	16	13	13	8	15	22
D1220-2	20	17	17	10	19	27
D1224-2	24	21	21	12	23	33.5
D1228-2	28	25	25	14	27	43
D1232-2	32	29	29	16	31	54
D1236-2	36	32	32	18	34	62.5
D1240-2	40	35	35	20	37	73.5

\*Note: D1216-2 is not equipped with rope and pulley

## DIMENSIONS

Rails: 3 in.

Flange: 1 in.

Rung: 1-3/4 in.

Fly Width: 15-1/4 in.



Exclusive Alflo® rung joint means Twist-Proof® performance

