

Datasheet


Brass, Steel Pneumatic Quick Connect Coupling, G 3/4 Male, Threaded

RS Stock number 667-2030

027 [Quick Release Pneumatic Couplings]



SUPER FLOW LINE



Interchangeability

RECTUS 27, CEJN 410 TST 410

Temperature Range

-20 C +100 C (-4 F +212 F)

Working Pressure

0 - 35 bar (0 - 500 PSI)

Flow Capacity

NW - 10

Standard version

Brass Nickel Plated

Buna (M)

Options

F- Straight Through Flow

K - Chrome Plated

S -Stainless Steel

V - Viton Seal

Material

Coupler Body : Brass Nickel Plated

Back Part: Brass Nickel Plated

Sleeve : Steel Nickel Plated

Valve : Brass

Springs : Stainless Steel

Locking O-Ring : Stainless Steel

Balls : Stainless Steel AISI 420

Seals : Buna (M)

Plug : Steel Nickel Plated

Couplers and Plugs







Male Thread Coupler



Female Thread Coupler

| Connection | Order No | SW | Lenght | Dia |
|------------|-----------|----|--------|-----|
| R 1/4" | 027 EG 13 | 24 | 60 | 28 |
| R 3/8" | 027 EG 17 | 24 | 60 | 28 |
| R 1/2" | 027 EG 21 | 24 | 65 | 28 |
| R 3/4" | 027 EG 26 | 27 | 65 | 28 |
| G 1/4" | 027 DG 13 | 24 | 57 | 28 |
| G 3/8" | 027 DG 17 | 24 | 57 | 28 |
| G 1/2" | 027 DG 21 | 24 | 57 | 28 |
| G 3/4" | 027 DG 26 | 32 | 61 | 28 |

| | | | | | |
|--|-------------|-----------|----|----|----|
| | 6 mm 1/4" | 027 HG 06 | 24 | 75 | 28 |
| | 8 mm 5/16" | 027 HG 08 | 24 | 75 | 28 |
| | 9 mm 5/14" | 027 HG 09 | 24 | 75 | 28 |
|  Standart Hose Barb Coupler | 10 mm 3/8 " | 027 HG 10 | 24 | 75 | 28 |
| | 13 mm 1/2" | 027 HG 13 | 24 | 75 | 28 |
| | 16 mm 5/8 " | 027 HG 16 | 24 | 75 | 28 |
| | 19 mm 3/4" | 027 HG 19 | 24 | 75 | 28 |
|  Standart Hose Barb Plug | 6 mm 1/4" | 027 HU 06 | | 46 | |
| | 8 mm 5/16" | 027 HU 08 | | 46 | |
| | 9 mm 5/14" | 027 HU 09 | | 46 | |
| | 10 mm 3/8" | 027 HU 10 | | 46 | |
| | 13 mm 1/2" | 027 HU 13 | | 46 | |
| | 16 mm 5/8" | 027 HU 16 | | 46 | |
|  Male Thread Plug | R 1/4" | 027 EU 13 | 17 | 40 | |
| | R 3/8" | 027 EU 17 | 17 | 40 | |
| | R 1/2" | 027 EU 21 | 22 | 46 | |
| | R 3/4" | 027 EU 27 | 27 | 46 | |
|  Female Thread Plug | G 1/4" | 027 DU 13 | 17 | 34 | |
| | G 3/8" | 027 DU 17 | 19 | 24 | |
| | G 1/2" | 027 DU 21 | 24 | 38 | |
| | G 3/4" | 027 DU 26 | 32 | 42 | |