

HERCULES

2 / 5 KG

CO2 Fire Extinguisher



Capacity	2KG CO2	5KG CO2
Model	FT02-02F-00	FT02-03D-00
Test Standard	EN3	
Extinguishing Agent	Carbon Dioxide	
Propellant	Carbon Dioxide	
Cylinder Diameter	103 MM	135.8 MM
Total Height	565 MM	755 MM
Approx Total Weight	6.4 KG	13.5 KG
OperateTemp	-30°C to 60°C	
Working Pressure	56 BAR	
Test Pressure	250 BAR	
Fire Rating	34B	89B
Pack Dimension(mm)	125x160x600 (1per box)	145x180x775 (1per box)
PART NO	FEL-FT-C02	FEL-FT-C05

Information

Effective against **class B fires** involving flammable liquids, solvents, oils, paints, thinner and liquifieable solids.

Effective against **electric fires**. Note that before attempting to fight electric fires, the electricity must be turned off.

Carbon dioxide is a **clean agent** that leaves no residue upon discharge.

Instructions for use

1. Read instructions before using to ensure that you have selected the correct fire extinguisher for the fire you intend to fight.

2. **P**ull out safety pin.

3. **A**im.

4. **S**queeze handle.

5. **S**weep.



EN3

SETSCO SG
APPROVED

Accessories



Wire Bracket



L Bracket

Due to constant improvements, product dimensions may differ slightly.



FIRE ARMOUR

14 Fan Yoong Rd, T62666788 F 62663788
Email: firearmour@firearmour.com.sg