

# VVE3

## TeSys Vario - emergency stop switch disconnecter - 63 A - back of enclosure



### Main

Range	TeSys
Product name	TeSys VARIO
Device short name	VVE
Product or component type	Emergency stop switch disconnecter
Performance level	High performance
Poles description	3P
Contacts type and composition	3 NO
Network type	DC AC
Control type	Rotary handle
Rotary handle mounting style	Direct
Handle colour	Red
Handle front plate colour	Yellow
Suitability for isolation	Yes

### Complementary

Rotary handle padlocking	1 padlock 4...6 mm
Marking	0 - 1
Mounting support	Switch: symmetrical rail Switch: plate
Fixing mode	By clips for switch By screws for switch
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	63 A
[Ithe] conventional enclosed thermal current	50 A
[Ie] rated operational current	41.5 A AC-23 Ue: 400 V
Rated operational power in W	11 KW at 230...240 V (AC-3) 22 KW at 500 V (AC-3) 22 KW at 690 V (AC-23A) 30 KW at 500 V (AC-23A) 18.5 KW at 400...415 V (AC-3) 18.5 KW at 690 V (AC-3) 15 KW at 230...240 V (AC-23A) 22 kW at 400...415 V (AC-23A)
Intermittent duty class	30
Making capacity ( I Rms)	630 A at 400 V AC-21A 630 A at 400 V AC-22A 630 A at 400 V AC-23A
[Icm] rated short-circuit making capacity	2.1 kA at 400 V at Ipeak
[Icw] rated short-time withstand Rms current	756 A at 400 V duration: 1 s
Rated conditional short-circuit current	10 KA at 400 V - associated fuse 63 A aM 10 kA at 400 V - associated fuse 63 A gG
Breaking capacity	500 A at 400 V (AC-21A) 500 A at 400 V (AC-22A) 500 A at 400 V (AC-23A)
Device composition	Switch Handle

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Mechanical durability	30000 cycles
Electrical durability	30000 Cycles AC-21 30000 cycles DC-1...5
Connections - terminals	Power circuit: screw clamp terminals 25 mm <sup>2</sup> - solid Power circuit: screw clamp terminals 16 mm <sup>2</sup> - flexible - with cable end
Tightening torque	Power circuit: 4 N.m - on screw clamp terminals
Handle front plate dimension	45 x 45 mm
Height	83 mm
Width	60 mm
Depth	110 mm
Net weight	0.53 kg

## Environment

Standards	IEC 60947-3
Product certifications	UL GL CSA
Protective treatment	TC
IP degree of protection	IP65 IP65 conforming to IEC 60529
Mechanical robustness	Vibrations 10...150 Hz (1 gn) conforming to IEC 60068-2-6 Shocks 11 ms (30 Gn) conforming to IEC 60068-2-27
Ambient air temperature for operation	-20...50 °C
Fire resistance	960 °C conforming to IEC 60695-2-1

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------