

Datasheet

Stock No:1707017

# RS Pro BNC STRAIGHT BULKHEAD JACK RECEPTACLE

<b>NO</b>	<b>DESCRIPTION</b>	<b>DATE</b>
△	13-25-4/R13-025-04-00262204E	01.30.18
	→ 40130208400059	

  

Technical drawing details:  
 - Front view: MAX. PANEL 4.4(.173), 13.2(.520), 26.9±0.5(1.059±.020), 12.5(.492), 9.6(.378), 3/8"-32UNEF, Ø12.7(.500), Ø0.80(.031), Ø9.65(.380), 12.7(.500) HEX., 3/8"-32UNEF, .091(.23)  
 - Side view: Ø12.9(.508) REF.  
 - Mounting Hole: 8.85(.348), Ø9.65(.380)

MOUNTING HOLE

APPROVED by \_\_\_\_\_ DATE: \_\_\_\_\_

  

<b>DESCRIPTION</b> BNC STRAIGHT BULKHEAD JACK RECEPTACLE	
<b>DRAWN</b> Jackie	<b>品名</b> 40130208400059△
<b>CHECK</b> ATC	<b>DATE</b> 10.15.15
<b>APPROVAL</b> Jenny	<b>REV.</b> A-1
<b>TOLERANCE</b> X ±0.2	<b>UNIT</b> mm(in)
<b>CHECK</b> XX ±0.1	<b>SCALE</b> 4:1
<b>APPROVAL</b> XXX ±0.05	<b>DWG. NO.</b> 13-0600-Z
<b>ANGLE</b> ±5°	

  

<b>NO</b>	<b>DESCRIPTION</b>	<b>QTY</b>	<b>FINISH</b>
5	NUT	1	NICKEL
4	WASHER	1	NICKEL
3	CENTER CONTACT	1	GOLD 3µ MIN.
2	INSULATION	1	NONE
1	BODY	1	NICKEL 100µ MIN.
	<b>MATERIAL</b>		

  

**1.0 ELECTRICAL**

- 1.1 FREQUENCY RANGE: DC-6 GHz
- 1.2 NOMINAL IMPEDANCE: 75 OHMS
- 1.3 VOLTAGE RATING: 500 VOLTS MAX.
- 1.4 VSWR: 1.3 MAX.

**2.0 MATERIALS**

- 2.1 BODIES: BRASS PER JIS-C3604
- 2.2 CENTER CONTACT: BERYLLIUM COPPER PER ASTM B166 UNS C17300
- 2.3 INSULATION: TEFLON PER ASTM D1457 AND ASTM D1710

**3.0 FINISHES AND OTHERS**

3.1 SEE BELOW TABLE FOR DETAILS.

**4.0 MECHANICAL**

4.1 INTERFACE IN ACCORDANCE WITH: MIL-STD-846B

**5.0 ENVIRONMENTAL**

5.1 OPERATING TEMPERATURE RANGE: -65° C TO +165° C