

FEATURES

- Glass cartridge
- 5mm x 20mm cartridge size
- T Speed Rating
- Anti-surge
- Low Breaking Capacity

RS PRO, 3.15A Glass Cartridge Fuse, 5 x 20mm, Speed T

RS Stock No.: 563-621



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

Glass cartridge fuses are ideal for providing protection to devices or internal circuits from short circuits and overcurrent. They are deliberately weaker components which, when too much current is drawn, will blow. Once the fuse has blown it will need replacing in order to make the circuit complete and allow the flow of current.

General Specifications

Fuse Speed	T
Body Material	Glass
Application Category	GRL
Includes Indicator	No
Size Designation	Miniature
Applications	Industrial, Commercial, Home/Residential, Automotive

Electrical Specifications

Current Rating	3.15A
Voltage Rating	250V ac
High Rupture Capacity	No
Breaking Capacity (at Maximum Voltage Rating)	35A
Resistance	0.0187Ω

Mechanical Specifications

Fuse Size	5mm x 20mm
Overall Length	20mm
Diameter	5.2mm
Overall Dimensions	5.2mm x 20 mm

Operation Environment Specifications

Maximum Operating Temperature	125°C
Minimum Operating Temperature	-55°C

Approvals

Compliance/Certifications	CSA Acceptance, UL Recognised, RoHS Compliant, CCC, UTE, PSE, KTL, CQC, TUV, VDE, BSI, SEMKO Approved
---------------------------	---



S