



## Main

Range	Actassi
Product brand	Schneider Electric
Product type	Keystone modular jack
Provided equipment	Without shutter
Colour tint	Metal (zamak)
Wiring Colour configuration	TIA-568A/B
Type of packing	Plastic bag and carton
Quantity per set	Set of 1

## Complementary

[In] rated current	1.5 A at 25 °C
Voltage proof	1000 V AC/DC peak, between contacts
Contact resistance	20 mOhm
Insulation resistance	>= 500 MOhm
Connector type	RJ45
Tool type	Punch down tool Quick termination tool
Cable outer diameter	0.9...1.4 mm
Compatible LAN cable types	STP
Communication network category	6A
Supported applications	10GBASE-T
Product compatibility	RJ45 plug
Type of footprint	S-110 keystone
Targeted region	Asia Pacific.

## Environment

Operational temperature range	-10...60 °C
Ambient air temperature for storage	-20...70 °C
Relative humidity	0...93 %
Climatic category	40/070/21 (21 days)
Flame retardance	UL94-V0 conforming to UL listed
Product certifications	FCC part 68 F[RETURN]IEC 60603-7
Standards	ISO/IEC 11081 IEC 60603-7 ANSI/TIA/EIA-568-B

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.4 cm
Package 1 Width	4.8 cm
Package 1 Length	48.2 cm
Package 1 Weight	40.0 g

Unit Type of Package 2	CAR
Number of Units in Package 2	160
Package 2 Height	27.0 cm
Package 2 Width	32.0 cm
Package 2 Length	38.0 cm
Package 2 Weight	7.104 kg
Unit Type of Package 3	P12
Number of Units in Package 3	2880
Package 3 Height	95.0 cm
Package 3 Width	80.0 cm
Package 3 Length	120.0 cm
Package 3 Weight	127.872 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

### Contractual warranty

Warranty	18 months
----------	-----------