## STORAGE

## for Flammables



Using multiple cabinets helps you organize and segregate dangerous liquids.

## Sure-Grip® EX Safety Cabinets for Flammables

## Safety cabinets offer safe, dependable flammable liquid storage and protection

Protect workers, reduce fire risks, and improve productivity by storing flammable fuels and chemicals in code-compliant safety cabinets. Designed to meet OSHA and NFPA 30 standards, Sure-Grip® EX cabinets are constructed of sturdy 18-gauge (1-mm) thick double-wall, welded steel with 1-1/2-in (38-mm) of insulating air space for fire resistance. High-performance, self-latching doors close easily and securely for maximum protection under fire conditions. Fail-safe closing mechanism ensures three-point stainless steel bullet latching system works every time.

For added security, U-Loc™ handle comes with a cylinder lock and key set or accepts an optional padlock.

Haz-Alert™ reflective warning labels are highly visible under fire conditions or during power outages when illuminated with a flashlight.

Patented SpillSlope® galvanized steel shelves direct spills to back and bottom of a leakproof sump. They adjust on 3-in (76-mm) centers for versatile storage. Cabinets also feature a leakproof 2-in (51-mm) bottom sump, dual vents with flame arresters, four adjustable self-leveling feet, grounding connector and trilingual warning label. Durable lead-free epoxy/polyester powder-coat finish provides excellent chemical resistance.

All cabinets are FM-approved and come with a ten-year warranty.

Self-closing models also meet NFPA 1 and the International Fire Code. They shut and latch automatically when a fusible link melts at 165°F (74°C) under fire conditions. Unique, concealed self-closing mechanism offers obstruction-free access to contents















Capacity Gallons/Liters	Number of Doors	Dimensions H x W x D		Adj Shelves	Sump Capacity Gallons/Liters	Approv/Lstg	Sure-Grip® Model No	Ship Wt	Extra S Model
Gallons/Liters	and Style	Exterior	Interior	Sileives	Gallons/Liters	Regulation	Model No	lb/kg	Model
30/114	2 door, manual	44 x 43 x 18 in 1118 x 1092 x 457 mm	39.625 x 39.5 x 14.562 in 1006 x 1003 x 370 mm	1	5.2/19.7	FM,N,O,A	8930001	231/105	29937
	2 door, self-close					FM,N,O,A,I	8930201	238/108	
45/170	2 door, manual	65 x 43 x 18 in 1651 x 1092 x 457 mm	60.5 x 39.5 x 14.562 in 1537 x 1003 x 370 mm	2		FM,N,O,A	8945001	311/141	
	2 door, self-close					FM,N,O,A,I	8945201	313/142	
60/227	2 door, manual	65 x 34 x 34 in 1651 x 864 x 864 mm	60.5 x 30.75 x 30.34 in 1537 x 781 x 771 mm		8.3/31.5	FM,N,O,A	8960001	388/176	29944
	2 door, self-close					FM,N,O,A,I	8960201	392/178	
90/341*	2 door, manual	65 x 43 x 34 in 1651 x 1092 x 864 mm	60.5 x 39.5 x 30.34 in 1537 x 1003 x 771 mm		10.7/40.6	FM,N,O,A	8990001	481/218	29945
	2 door, self-close					FM,N,O,A,I	8990201		

<sup>\*</sup>OSHA 29CFR 1910.106(d)(3) states that not more than 60 gallons (227L) of Category 1, 2, or 3 flammable liquids, nor more than 120 gallons (454L) of Category 4 flammable liquids may be stored in a safety cabinet.

