



Elastifile 2.5 - 2.7

Dedicated Storage Mode (DSM)

Hardware Requirements Guide

July 2018

Document Revision: 0.1

Important Notice

This document is delivered subject to the following conditions and restrictions:

- This guide contains proprietary information belonging to Elastifile Inc. Such information is supplied solely for the purpose of assisting explicitly and properly authorized users of Elastifile Inc. products.
- No part of contents may be used for any other purpose, disclosed to any person or firm, translated or reproduced by any means, electronic and mechanical, without the express prior written permission of Elastifile Inc..
- The text and graphics are for the purpose of illustration and reference only, based on the current version of the product(s) described in this document.
- The software described in this document is furnished under a license agreement. The software may be used or copied only in accordance with the terms of that agreement.
- Information in this document is subject to change without notice. Corporate and individual names and data used in examples herein are fictitious unless otherwise noted.
- Elastifile Inc. makes no warranty of any kind with regard to this printed material, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. Elastifile Inc. shall not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance, or use of this material.
- Brand or product names are trademarks of their respective companies or organizations.

Copyright © 2018 Elastifile Inc. All rights reserved.

Table of Contents

1. Introduction	4
1.1 Document Scope	4
2. Hardware Requirements	5
2.1 General	5
2.2 Network	5
2.2.1 Switch	5
2.2.2 NICs	5
2.3 Storage	6
2.3.1 Storage Devices	6
2.3.2 Disk Controllers	6
2.4 Host Resources	6
2.4.1 EMS Hardware Requirements	6
2.4.2 Controller Hardware Requirements	6
2.4.3 Replication Service Machine Hardware Requirements (optional)	7

1. Introduction

1.1 Document Scope

This guide describes the hardware requirements , including a list of tested hardware, for Elastifile 2.5 - 2.7 systems based on Dedicated Storage Mode (DSM).

2. Hardware Requirements

2.1 General

Ensure that your hardware is compatible with the latest Red Hat Hardware Compatibility List.

2.2 Network

2.2.1 Switch

Elastifile's Data Network expects a 10GbE connection. In addition, we highly recommend a dedicated VLAN with MTU 9000 (jumbo) frame support for its internode data communication. Elastifile uses the VLAN to isolate its internal IP scheme.

The network switch should meet the following port configuration requirements:

- Minimum 10GbE full duplex; 25/40/100GbE also supported
- MTU=9000 - highly recommended
- Dedicated VLAN (trunk or access mode) - highly recommended



Elastifile requires using two 10GBe switches minimum (one switch for each Elastifile network).

2.2.2 NICs

NICs used in the Elastifile networks should meet the following requirements:

- 2 x 10GbE for the data network
- 10GbE minimum for the client network
- SR-IOV must be off for DSM

2.3 Storage

2.3.1 Storage Devices

- Up to 12 devices per Dedicated Storage node
- Maximum device size: 4TB
- Minimum data center grade devices:
 - NVMe SSD
 - SATA SSD

2.3.2 Disk Controllers

No RAID Controller is needed.



If the Disk Controller has a RAID controller, disable it and configure the controller to operate in JBOD mode.

2.4 Host Resources

2.4.1 EMS Hardware Requirements



The EMS can be installed as a physical server or a virtual server on VMware or KVM.

Each EMS requires the following resources:

- CPU:
 - Intel-based, 4th generation and higher
 - 4 virtual or physical cores minimum
- RAM: 8GB minimum
- SSD: 64GB minimum

2.4.2 Controller Hardware Requirements

Each Elastifile controller requires:

- CPU:
 - Intel-based, 4th generation and higher, dual-socket
 - 6 cores minimum per CPU
 - Up to 16 cores per CPU (ECFS uses up to 20 cores, the kernel uses spare cores)
 - Hyperthreading disabled.
- RAM: 96GB to 256GB RAM (DDR4 or higher).

- SSD: Boot device with minimum 128GB, 3.2 DWPD, or 256GB with 1.6 DWPD.

2.4.3 Replication Service Machine Hardware Requirements (optional)

Each replication service machine requires:

- CPU:
 - Intel-based, 4th generation and higher
 - 4 virtual or physical cores minimum.
 - Supports up to 4 concurrent bidirectional replications. Number of CPUs can be increased to support more concurrent replications.
 - Hyperthreading: Supported
- RAM: 16GB RAM minimum (should be increased if CPU count increases). Recommended: 4GB per CPU core
- SSD: Boot device with minimum 38GB.