

DESCRIPTION

Touch screen microphone station for emergency calls

The TSC6000-EN touch screen remore unit allows the sending of emergency live messages and evacuation/alert pre-recorded messages. The unit is equipped with a 7" touch screen backlighted display for zones selection and customization, while a group of LEDs give information about the emergency system state and faults.

FUNCTIONAL FEATURES

- Emergency key
- "Key pad" mode / "Numeric pad" mode
- Functions keys to create groups of zones
- Zone labels customization
- Live emergency calls
- Broadcast calls
- Status LEDs / Fault signaling LEDs
- Pre-recorder messages recall
- Emergency messages reset
- Warning signal muting


TSC6000-EN

EN 54 - 16


TOUCH SCREEN MICROPHONE STATION



NUMERIC PAD MODE



KEY PAD MODE




NOTE

The microphone is NOT included in the supply. It's posswible to match with TSC6000-EN unit these models:



MC132-V Dynamic microphone with flexible stem



TECHNICAL DATA

No of selectable zones	1 ÷ 216 from 20 to 60 zone selection keys +6 function keys
Typical output level	300mV
Frequency response	20 ÷ 20.000Hz
Distortion	< 1%
LOW CUT filter	-10dB / 100Hz
S/N ratio	> 60dB
Connection	RJ45 (IN/OUT)
Power supply voltage	24Vcc
Max. absorption @24Vdc	165mA
Dimensions (WxHxD)	230 x 80 x 200
Net weight (without micro)	1,6kg

DIMENSIONS

