

Passive Point Source

MAIN APPLICATIONS

- Ideal for fixed installation
- Corporate gigs
- Weddings
- House of worship



MAIN FEATURES

- 2-way coaxial
- 40W RMS recommended amplifier
- 3,4" low frequency woofer with 0,8" coil
- 0,6" high frequency driver with 0,6" coil
- Input connectors Euroblock 4 pin (in & thru)
- ABS enclosure
- Speaker wall/ceiling mount stand
- Available in black and white color

DESCRIPTION

The FBT CANTO 3C two-way coaxial speaker system features lightweight in ABS enclosure. Available in black or white finish, the FBT CANTO 3C provides fixed installations with an elegant design suitable for a wide range of applications. The FBT CANTO 3C incorporating a 3,4" coaxial low frequency woofer with 0,8" voice coil and 0,6" high frequency driver with 0,6" voice coil coupled to 120° dispersion. The SPL level of low-distortion audio can provide goes far beyond expectations of such a compact solution with a frequency range of 140Hz to 20kHz; its balanced sound is a big asset in near-field applications for the best intelligibility and high sensitivity with smooth and wide frequency response.

Adjustable support allow the use of the FBT CANTO 3C on wall or ceiling installations.

TECHNICAL SPECIFICATIONS

GENERAL

Configuration	way	2 - Coaxial
Low frequency woofer	inch	3,4 - 0,8 coil
High frequency driver	inch	0,6 - 0,6 coil

ACOUSTIC SPEC.

Frequency response	(@ -6dB)	140 Hz - 20kHz
SPL max. (cont / peak)	dB	105 / 108
Dispersion	H x V	120°

AMPLIFIER

Recommended amplifier	W RMS	40
Short term power IEC 268-5	W	80
Nominal impedance	Ohm	16

INPUTS / OUTPUTS

Connectors		Euroblock 4 pin
------------	--	-----------------

MECHANICAL SPEC.

Material		ABS
Net size (WxHxD)	inch	4,33 x 4,48 x 6,25
Net weight	Lbs	1,76

DIMENSIONAL DRAWING & INSTALLATION

