



Just Connect, Inflate and Go!™

- No jacks or tools required. Seals and inflates in minutes.
- For use on cars, vans and trailers
- Seals up to 5mm punctures

DIRECTIONS FOR USE (READ WARNINGS BEFORE USE):



REMOVE THE PRODUCT WITHIN 3 DAYS

1. If possible, move car slightly so that the puncture is in the 6 o'clock position.
2. **SHAKE CAN VIGOROUSLY FOR 30 SECONDS** before attaching hose to tyre. Remove cap, unwind hose and tightly screw nozzle clockwise onto tyre valve.
3. Hold can upright and push button down firmly. Product will be activated automatically. **DO NOT** shake can while hose is attached to valve stem to avoid hose breakage, which might cause contents to spray in eyes, on clothing or vehicle.
4. **ONLY** when product stops moving through the clear hose, release button. Then, unscrew hose.
5. Make sure tyre rim lifts off the ground.
6. **ONLY** if rim is off the ground, **DRIVE VEHICLE IMMEDIATELY** a short distance (2 to 3 miles) to allow tyre pressure to increase and sealant to spread evenly inside the tyre.
7. If needed, add air up to manufacturers recommended pressure.
8. **THIS IS AN EMERGENCY TYRE REPAIR.** Have tyre repaired by tyre professional within 3 days or 100 miles, whichever comes first. Be sure to deflate tyre before repair.

DANGER: Never weld on a rim. Welding on a rim with the tyre mounted could cause the tyre to explode regardless of whether tyre inflator is used. Welded and repaired rims are unsafe. Do not repair puncture with reamer/plugger. Spark may cause tyre to burst. In case of fire, allow it to burn off. Use flooding water or foam on ignited rubber.

NOTE: Fix-A-Flat® provides quick emergency repair. Treated tyres should be repaired by a qualified tyre professional within 3 days or 100 miles, whichever comes first. Advise tyre professional of product use and ensure that pressure sensors are properly cleaned. Deflate tyres containing Fix-A-Flat only in well-ventilated areas. If the rim does not lift off the ground after product use, have the tyre repaired. Fix-A-Flat will not repair the sidewall or severe damage, cracks or leaks in the tyre on the rim. If the temperature is below 0°C, stand the can in the footwell away from the vent warm up. If Fix-a-Flat is spilled on paint, wash off immediately with water.

FIX A FLAT

DANGER
Extremely flammable aerosol.

Keep out of reach of children. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use only outdoors or in a well-ventilated area. Dispose of contents/container in accordance with local regulations. Avoid breathing vapour/spray. CAUTION: Pressurised container: May burst if heated.

First Aid: IF SWALLOWED: Do not Induce Vomiting. Immediately call a POISON CENTER or doctor/physician. IF ON SKIN: Gently wash with plenty of soap and water.

ChemTel Inc. +1.813.248.0573 ChemTel Accepts Collect Calls from Outside of the United States.

500ml 650 e3

ITW Global Tire Repair Europe GmbH
Carl-Benz-Str. 10 88696 Owingen, Germany
+49-7551-9200-0.




WARRANTY: For a period of 90 days from date of purchase, manufacturer guarantees this product will meet the specifications when used as directed. Manufacturer's sole liability and Customer's sole remedy under any warranty claim is limited to refund of purchase price upon return of proof of purchase.

Fix-A-Flat® is a registered trademark of Illinois Tool Works, Inc. Just Connect, Inflate and Go!™ and Quick Connect™ are trademarks owned by Illinois Tool Works, Inc. Blended and canned in UK.



WWW.FIXAFLAT.COM
Questions or Comments?
Call +49-7551-9200-0

PART #S60176 01.11.16



3
1628150849
7