

Standard Equipment/Optional Equipment

Standard Equipment

Cushion rubber drive wheel	Solid and long-lasting Extraal® covers
Single polyurethane load wheels	Storage for shrink wrap, pens, gloves on the battery cover
Compact vertical change for BS battery	Hour meter and battery discharge indicator
Max. lift height to top of the pallet : 804mm	Key switch
Protection screen between mast channels	Horn
Compact lifting system for excellent visibility of the forks	Digital LAC controller
Fork length : 1150 mm	Automatic parking brake
Width over forks : 560 mm	Protection to -10°C

Optional Equipment

Drive wheels: polyurethane, non-marking, wet grip, treaded polyurethane, treaded cushion	Automatic lifting of the forks
Load wheels: tandem polyurethane or tandem polyurethane greaseable	Automatic lifting & lowering with foot protection
Fork length : 1190 mm	Lateral battery change for 2 PzS battery
Width over forks : 520 mm	Load backrest: 900 mm or 1290 mm high
Creep speed activated from the tiller head	Built-in charger - high frequency technology - 24V / 35A
Proportional speed according to the tiller angle	Cold store protection to -35°C
Additional buttons for lifting/lowering the forks on chassis side	LFM : Linde Fleet Management including PIN code access control
	Other options available on request.



Pallet Truck with ergonomic lift  
Capacity 1600 kg/800 kg  
T16L

Series 1152

Safety

The Linde T16L benefits from a long tiller with a low mounting point ensuring a large safety clearance between operator & chassis. While using optional buttons or automatic function from the chassis side, the lowering stops automatically to keep the operator’s feet safe. Creep speed and proportional speed functions, available as options, provide optimum safety while travelling or manoeuvring in tight corners.

Performance

The T16L shows its true efficiency on the job. The powerful lift & traction motors supply the performance needed to achieve a high level of productivity. The truck has a maximum capacity of 1600 kg. Wide spaced mast channels provide excellent stability for the load enabling a residual capacity of 800 kg in fully raised position.

Comfort

Empty pallets can be raised by 804 mm, eliminating back or upper body strain. This height adjustment is really appreciated when order picking, restocking shelves in retail stores or assembly line activities in manufacturing industries. Additional buttons located on the truck side and automatic functions enable all kind of loads to be lifted or lowered quickly and without fatigue.

Reliability

A rugged construction makes the T16L a pallet truck that can be relied on. The Extraal® motor cover is remarkably solid and resistant to damage. The sturdy mast and the durable carriage are made of high-grade rolled steel contributing to a long truck life as well as fast, easy and safe load handling.

Service

Linde pallet trucks are designed to keep maintenance costs low and provide high levels of up-time over many years. The service engineer has fast, easy access to all internal components thus enabling a quick maintenance turnaround.

Features

Safety

- Long tiller arm and low mounting point ensure ample safety clearance between operator and chassis
- Low chassis skirt protects operator’s feet when manoeuvring
- Ergonomic tiller head: wrap-around protection for the operator’s hands
- Feet protection on the lowering functions used from the chassis side
- Proportional traction speed according to the tiller angle (option)

Stability

- Integrated mast matched to chassis width
- Highly resistant fork carriage and load arms made of robust pressed steel



Controls

- Separate controls for initial lift and high lift
- OptiLift proportional lifting controls
- Additional lifting/lowering buttons on chassis sides (option)
- Automatic lifting or lifting/lowering function (option)
- Creep speed (option)
- All commands integrated to the tiller

Handling

- Chassis narrower than a pallet
- Compact dimensions and small turning radius
- Long tiller arm reduces steering effort to maximise manoeuvrability

Extraal cover

- Extremely strong - lasts the life time of the truck
- Easily removed for fast, convenient access to all components



AC Motor

- Powerful, smooth-running motor, 1.2 kw (at 100% output)
- Climbing ability -14%, fully laden
- Travel speed adjustable up to 6km/h max. laden or unladen



Braking

- Highly efficient mechanical brake when tiller is fully raised or lowered
- Automatic electric braking on releasing traction butterfly or reversing direction
- Truck slows before coming to a stop, remaining under total control at all times
- No roll-back when starting on a slope



Batteries and chargers

- BS or 2 PzS battery up to 250 Ah, suitable for vertical battery change
- Lateral change for 2 PzS compartment
- Easy battery charging - available with optional built-in charger suitable for any convenient electric outlet

Technical Data according to VDI 2198

Characteristics	1.1	Manufacturer		LINDE
	1.2	Model designation		<b>T 16 L</b>
	1.3	Power unit		Battery
	1.4	Operation		Pedestrian
	1.5	Load capacity	Q (t)	1.6 <sup>1)</sup>
	1.6	Load centre	c (mm)	600
	1.8	Axle centre to fork face	x (mm)	890 / 950 <sup>2) 3)</sup>
Weights	1.9	Wheelbase	y (mm)	1338 / 1404 <sup>2) 3)</sup>
	2.1	Service weight	(kg)	603 (556) <sup>4) 5)</sup>
	2.2	Axle load with load, front/rear	(kg)	805 / 1398 (758 / 1398) <sup>4) 5)</sup>
Wheels/Tyres	2.3	Axle load without load, front/rear	(kg)	458 / 145 (411 / 145) <sup>5) 4)</sup>
	3.1	Tyres rubber, SE, pneumatic, polyurethane		V+P/p <sup>6)</sup>
	3.2	Tyre size, front		Ø 230 x 75
	3.3	Tyre size, rear		Ø 85 x 90 (Ø 85 x 65) <sup>7)</sup>
	3.4	Auxiliary wheels (dimensions)		Ø 125 x 40
	3.5	Wheels, number front/rear (x = driven)		1x + 2 / 2 (1x + 2 / 4)
	3.6	Track width, front	b10 (mm)	482 <sup>7)</sup>
Dimensions	3.7	Track width, rear	b11 (mm)	340 / 380 <sup>5) 8)</sup>
	4.2	Height of mast, lowered	h1 (mm)	1275
	4.3	Free lift	h2 (mm)	550
	4.4	Lift	h3 (mm)	675 <sup>7)</sup>
	4.6	Initial lift	h5 (mm)	125
	4.9	Height of tiller arm in operating position, min/max	h14 (mm)	720 / 1240
	4.15	Height, lowered	h13 (mm)	85
	4.19	Overall length	l1 (mm)	1842 (1767) <sup>5) 3)</sup>
	4.20	Length to fork face	l2 (mm)	692 (617) <sup>5) 3)</sup>
	4.21	Overall width	b1/b2 (mm)	720 <sup>3)</sup>
	4.22	Fork dimensions	s/e/l (mm)	50 x 180 x 1150
	4.25	Fork spread, min/max	b5 (mm)	520 / 560 <sup>3)</sup>
	4.32	Ground clearance, centre of wheelbase	m2 (mm)	20 / 145 <sup>9)</sup>
	4.33	Aisle width with pallet 1000 x 1200 across forks	Ast (mm)	1935 (1860) <sup>5) 10)</sup>
	4.34	Aisle width with pallet 800 x 1200 along forks	Ast (mm)	2135 (2060) <sup>5) 10)</sup>
Performance	4.35	Turning radius	Wa (mm)	1625 / 1685 (1550 / 1610) <sup>2) 5)</sup>
	5.1	Travel speed, with/without load	(km/h)	6 / 6 <sup>11)</sup>
	5.2	Lifting speed, with/without load	(m/s)	0.115 / 0.184 (0.035 / 0.041) <sup>12) 4)</sup>
	5.3	Lowering speed, with/without load	(m/s)	0.326 / 0.13 (0.062 / 0.031) <sup>12) 4)</sup>
	5.8	Maximum climbing ability, with/without load	(%)	14.0 / 25.0
	5.9	Acceleration time, with/without load	(s)	7.5 / 6.5
Drive	5.10	Service brake		Electro-magnetic
	6.1	Drive motor, 60 minute rating	(kW)	1.2
	6.2	Lift motor, rating at S3 15%	(kW)	1.2
	6.3	Battery according to DIN 43531/35/36 A,B,C,no		43 535 / B / 2Pz5 (BS)
	6.4	Battery voltage/rated capacity (5h)	(V/Ah)	24 / 180 (24 / 150)
	6.5	Battery weight (± 5%)	(kg)	212 (157)
	6.6	Power consumption according to VDI cycle	(kWh/h)	0,38
Others	8.1	Type of drive control		LAC
	8.4	Noise level at operator's ear	(dB(A))	62

1) Load distribution e.g. 800 kg on the forks, 800 kg on the fork arms.  
Total load max. 1600 kg.

2) Forks upraised / lowered

3) (± 5 mm)

4) (± 10%)

5) Figures in parenthesis refer to short version with BS cells

6) Solid rubber + polyurethane / polyurethane

7) Figures in parenthesis with tandem load wheels.

8) Depending on the forks spread; see 4.25

9) min./max.

10) Including a 200 mm (min.) operating aisle clearance.

11) (± 5%)

12) Figures in parenthesis with initial lift

