

Pigment Yellow 830

C.I. Name	Pigment Yellow 83
C.I. No.	21108

CAS. No.	5567-15-7
Chemical Group	Diarylide

Product Description

Yellow 830 is an opaque red shade diarylide yellow pigment with good all-round fastness properties. It is for general industrial applications, automotive refinishes, powder coatings, and wood stains.

Physical Data

Density (g/cm ³)	1.5
Form of Supply	Yellow Powder
Oil Absorption (g/100g)	50~70
Moisture (%)	≤1.5
PH Value	5.0~7.0
Light Fastness	7~8
Heat Stability	200°C / 392°F

Chemical Resistance

Acid	5
Alkali	5
Alcohol	5
Ester	5
Ketone	5
Soap	5
Migration	-

Applications

- Coatings

Automotive Coating	●
Industrial Coating	●
Decorative Coating	●
Coil Coating	●
Wood Coating	●
Powder Coating	●

- Plastics

PVC	○
PE/PP/PO	○
ABS	-
PS	-
PA	-
Rubber	○

- Inks

Offset Ink	○
Solvent based	○
Water based	○
UV / EB	○
Inkjet	

● Recommend

○ Limited Suitability

- Not Recommended

Product Specification

Test Property	Specification	Test Method
dE	≤1.0	AFTM-P 2.1
Color Strength	100±5%	AFTM-P 2.1

Packaging, Shipping & Storage

Pigment Yellow 830 is supplied in powder form. The product is packed in 25kg/55lb paper bag and shipped on pallets (400kg). Please keep the product stored under normal temperatures, dry and protected from weather.

All the information above is based on data obtained at laboratory and is not to be used for certifying the suitability of the product. Users are advised to test the product in their own system before purchase.