

# Nano Nucleating Agent Masterbatch NB Series

According to EC Directive 91/155/EEC

## 1. Identification

**Product:** Nucleating Agent Masterbatch

**Product Name(s):** Nano Nucleating Agent Masterbatch (NB-PP)

*Manufacturer/Supplier Identification*

**Manufacturer/Supplier:** Formula Chemicals Co., Ltd.

**Emergency telephone number:** +886-922582639; +886-2-26685339

## 2. Hazards Identification

Information Pertaining To Particular Dangers for Man And Environment

Negligible hazard at ambient temperature (-180C to +500C)

Classification System

Product is NOT considered to be hazardous under normal processing conditions.

## 3. Composition / Information on Ingredients

| CHEMICAL NAME         | CONTENT | CAS NUMBER |
|-----------------------|---------|------------|
| Polypropylene         | >90%    | 9003-07-0  |
| Proprietary additives | <10%    | Mixture    |

## 4. Emergency and First Aid Procedure

### GENERAL INFORMATION

At room temperature the product is neither an irritant nor gives off hazardous vapors. The measures listed below apply to critical situations (Fire, incorrect process conditions).

#### Skin Contact

If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissues and polymer. Do not attempt to peel the polymer from skin. Obtain immediately emergency medical attention if burn is deep or extensive.

#### Eye Contact

Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists.

#### Inhalation

If symptoms are experienced, move victim to fresh air. Obtain medical attention if breathing difficulty persists.

#### Ingestion

Adverse health effects due to ingestion are not anticipated.

---

## 5. Firefighting Measures

Flash Ignition Temperature : 335°C  
Auto Ignition Temperature : 350°C  
Flammable Limits : NA

**Suitable Extinguishing Media:** Water, Foam, Carbon Dioxide, Dry Chemical Powder

**For Safety reasons, unsuitable extinguishing media:** None

**Protective Equipment:** Respiratory & Eye protection for fire-fighting personnel

**Special hazards caused by the material, its products of combustion or resulting gases:**

In case of fire it can release: Carbon dioxide (CO<sub>2</sub>), and when lacking oxygen (O<sub>2</sub>), carbon monoxide (CO), Ketones & Aldehydes. The products of the burning are dangerous. The formation of hydrocarbons and aldehydes are possible in the initial stages of a fire (especially in between 400 °C and 700 °C).

### Additional information

Heat value: 8000 - 11000 kcal/kg

---

## 6. Accidental Release Measures

Spill and Leak procedure : Sweep up spilled material for use or disposal. Good

House-keeping must be maintained to avoid potential slipping problem.

Caution : Keep walking surface free of spilled material to avoid slipping hazard.

---

## 7. Handling and Storage

### HANDLING

**Information for safe handling:**

No special requirements necessary, if handled at room temperature. Avoid spilling the product, as this might cause falls.

### STORAGE

**Requirements to be met by storerooms and containers:**

This product may react with strong oxidizing agents & should not be stored near such materials. Store the bags in areas protected with automatic sprinklers. Storage temperature should be below 60°C. Do not smoke.

Take precautionary measures to prevent the formation of static electricity.

Electric safety equipment.

Open flames prohibited.

Store the product in bags, car silos, container, or large cartons.

**Information about storage in one common storage facility:** Not required.

**Further information about storage conditions:**

Protect from heat and direct sunlight. Store container in a well ventilated position. Store under dry conditions.

**Specific applications** For safe stacking follow the storage recommendations specific for this Product.

**8. Exposure/ Protection method****ENGINEERING CONTROLS:**

Use in a well-ventilated area. If handling results in dust generation, special ventilation may be needed to minimize dust exposure. If heated material generates vapor or fumes, use process enclosures, local exhaust ventilation, or other engineering controls to control exposure.

**PERSONAL PROTECTIVE EQUIPMENT:**

Respiratory system

Product processing, heat sealing of film or operations involving the use of wires or blades heated above 300 °C may produce dust, vapor or fumes. To minimize risk of over exposure to dust, vapor or fumes it is recommended that a local exhaust system is placed above the equipment, and that the working area is properly ventilated. If ventilation is inadequate, use certified respirator that will protect against dust/mist.

**Skin and body**

Hot material: Wear heat-resistant protective gloves, clothing and face shield able to withstand the temperature of the molten product. Cold material: None required; however, use of gloves is good industrial practice.

**Hand**

Hot material: Wear heat-resistant protective gloves able to withstand the temperature of the molten product. Cold material: None required; however, use of gloves is good industrial practice. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

**Eyes**

Safety glasses with side shields. Use dust goggles if high dust concentration is generated.

**9. Physical and Chemical Data**

| General Information              |                                            |
|----------------------------------|--------------------------------------------|
| Form                             | : Solid Granules                           |
| Colour                           | : Translucent to White                     |
| Odour                            | : Slight Waxy Odour                        |
| Melting point/Melting range      | : 130-167 °C                               |
| Flash point                      | : > 329°C                                  |
| Ignition temperature             | : > 400 °C                                 |
| Decomposition temperature        | : > 300 °C                                 |
| Danger of explosion              | : Product is not explosive.                |
| Density                          | : 0.89-0.94 g/cm <sup>3</sup>              |
| Solubility in / Miscibility with | : Insoluble                                |
| Additional information           | : Soluble in boiling, aromatic chlorinated |

---

## 10. Stability and Reactivity

### Chemical stability

This product is stable under normal use conditions for shock, vibration, pressure or Temperature.

### Chemical stability - Condition to Avoid

Avoid strong oxidizing agents. Avoid Processing Material over 300 °C

### Hazardous Polymerization

Not likely to occur

### Corrosivity

Product is not corrosive

**Dangerous products of decomposition:** No hazardous decomposition products known at room temperature. At elevated temperature the material will begin to decompose producing fumes that can contain CO<sub>2</sub>, CO, Ketones & Aldehydes.

---

## 11. Toxicological Data:

### ACUTE TOXICITY:

#### Primary irritant effect:

- **on the skin:** No irritant effect.
- **on the eye:** No irritant effect.
- **Sensitization:** No sensitizing effect known.

### ADDITIONAL TOXICOLOGICAL INFORMATION:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

---

## 12. Ecological Information

**Information about elimination (persistence and degradability): Other information:** The product is not biodegradable.

### General notes:

The product is not toxic, small particles can have physical effects on water and soil organisms.

---

## 13. Disposal Considerations

### Product: Recommendation

Recycle (Reprocess)

Disposal through controlled incineration or authorized waste dump in accordance with Local, State or Federal Regulations.

### Uncleaned Packaging:

**Recommendation:** Disposal must be done according to official regulations.

---

## 14. Transport Data

**Transport/Additional information:**

Not regulated as a dangerous goods for transportation

---

## 15. Regulatory Information

**National regulations, other regulations, limitations and prohibitive regulations**

PP manufactured by IOCL shall meet the requirement stipulated in IS: 10910 on

“Specification for Polypropylene and its copolymer for safe use in contact with foodstuff, Pharmaceuticals & Drinking Water”.

Additives incorporated in this grade conform to the positive list of constituents as prescribed in IS: 10909.

The product & additives incorporated in it also comply with FDA: CFR Title 21.177.1520 Olefin Polymer.

---

## 16. Other Information

This data sheet was prepared in accordance with Directive 91/155/EEC.

MSDS Prepared by: Formula Chemicals Documentation Department.

MSDS Version / Prepared or Revised on: Version 5.0 2018/01/08

*The information presented has been compiled from sources considered to be dependable and is accurate to the best of Formula Chemicals' knowledge; however, Formula Chemicals makes no warranty regarding the accuracy of such data or the results to be obtained from use.*

*We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.*