


TRI-PENTAERYTHRITOL

For Lubricant Industry



NAME OF COMMODITY:	TRI-PENTAERYTHRITOL
ANALYSIS METHOD	GAS PHASE CHROMATOGRAPHY
MOLECULAR WEIGHT	372.4086

CAS. No.	78-24-0
EINECS NO.	201-097.4
HS CODE	29054200
MOLECULAR FORMULA:	C ₁₅ H ₃₂ O ₁₀ 

PRODUCT DESCRIPTION

APPEARANCE	WHITE POWDER
DENSITY:	1.384 g/cm ³
CONTENT OF TRI-PENTA WT, % ≥	80.00
CONTENT OF MONO-PENTA WT, % ≤	5.00
CONTENT OF DI-PENTA WT, % ≤	12.00
HYDROXYL VALUE % ≥	33.00-36.00
ASH, WT, % ≤	1.00
MOISTURE, WT, % ≤	1.00

All the information above is based on data obtained at laboratory and is not to be used for certifying the suitability of the product. Users are advised to test the product in their own system before purchase.

TRI-PENTAERYTHRITOL

APPLICATIONS:

- HIGH PERFORMANCE LUBRICATING OIL FOR AEROSPACE INDUSTRY
- HIGH PERFORMANCE LUBRICATING OIL FOR AUTOMOTIVE INDUSTRY
- ENGINEERING PLASTICS
- FIREPROOF COATING AND SOLVENT FREE UV COATING
- POLYMER INDUSTRY
- PAINT INDUSTRY
- TEXTILE INDUSTRY
- COSMETIC INDUSTRY
- PLASTIC ADDITIVES AND POLYMER MODIFIED MATERIALS
- PVC STABILIZERS & PLASTICIZERS
- ALKYD RESINS, ROSIN ESTERS, HIGH-GRADE ACRYLIC RESINS

PACKING & SHELF LIFE:

Packing: 25kg bag / 500kg per pallet or 500kg jumbo bags

Shelf Life: 1 year

All the information above is based on data obtained at laboratory and is not to be used for certifying the suitability of the product. Users are advised to test the product in their own system before purchase.