

Technical Specification								
#	ITEM	SPECIFICATION	QUANTITY	BRAND	MODEL	Bider complainace to the Specs (Y/N)	Details of any Alternatives	Remarks
1	SELF CLEANING FILTER	CAPACITY: 2M3/HR, END CONNECTION: 3/4" ,PORE SIZE: 100MIC.	5					
2	ULTRA FILTRATION MEMBRANE	MAX. CAPACITY: 38 LPM, INLET & OUTLET CONNECTION: 1"	5					
3	NaOCL DOSING PUMP	CAPACITY: 0 - 2.5 LPH & 7 BAR PRESSURE, POWER: 230 V 50Hz IP65, MAUAL ADJUSMENT 0-100%, ASS: LEVEL SWITCH, FOOT VALVE	5					
4	UV BULB		5					
5	PRESSURE GAUGE	PRESSURE RANGE: 0 - 7 BAR, DIAL SIZE: 2.5"	10					
6	LEVEL SWITCH	TYPE: FLOAT DISK, FLOAT MOC: PP, CABLE LENGTH: 3 MTRS WITH ADJUSTABLE STOPER	5					
7	BALL VALVE	SIZE: 1", MOC: PVC	5					
8	FLOAT SWICTHES	TYPE: FLOAT DISK, FLOAT MOC: PP, CABLE LENGTH: 3 MTRS WITH ADJUSTABLE STOPER	10					
9	FLOAT SWICTHES	TYPE: FLOAT DISK, FLOAT MOC: PP, CABLE LENGTH: 6 MTRS WITH ADJUSTABLE STOPER	10					
10	PRESSURE SWITCHES	SIZE: 1.5", MOC: PVC	5					
11	FOOT VALVES	SIZE: 90MM, MOC: PVC HIGH PRESSURE	5					

Delivered Equipments and Materials fulfill the Technical Specification

Name:
Company:
Date:
Sign: