

Request for Quotations

For

Procurement of ICT Equipment for Authentic Maldives Outlet at Gan International Airport

RFQ: MV-MoED-368103-GO-RFQ

3rd July 2023

Ministry of Economic Development Republic of Maldives

Procurement of:

Procurement of ICT Equipment for Authentic Maldives Outlet at Gan International Airport

Ref No: MV-MoED-368103-GO-RFQ

Project: Maldives: Enhancing Employability and Resilience of Youth Project

Employer: Ministry of Economic Development

Country: Maldives

Issued on: 3rd July 2023

Table of Contents

Request for Quotations	. 4
ANNEX 1: Technical Requirements	. 9
ANNEX 2: Quotation Forms	. 9

Request for Quotations

RFQ Ref No.: MV-MoED-368103-GO-RFQ

RFQ Date: 3rd July 2023

To: All Vendor

Request for Quotation (RFQ)

- 1. The Government of Maldives has received financing from the World Bank toward the cost of the Maldives: Enhancing Employability and Resilience of Youth project and intends to apply part of the proceeds toward payments under the contract for the Procurement of ICT Equipment for Authentic Maldives Outlet at Gan International Airport.
- 2. The **Ministry of Economic Development** now invites quotations from contractors for the Goods described in Annex 1: Technical Requirements, attached to this RFQ.

Fraud and Corruption

- 3. The Bank requires compliance with the Bank's Anti-Corruption Guidelines and its prevailing sanctions policies and procedures as set forth in the WBG's Sanctions Framework, as set forth in Appendix A to the Contract Conditions.
- **4.** In further pursuance of this policy, Contractors shall permit and shall cause their agents (where declared or not), subcontractors, subconsultants, service providers, suppliers, and personnel, to permit the Bank to inspect all accounts, records and other documents relating to the RFQ and Contract performance (in the case of award), and to have them audited by auditors appointed by the Bank.

Eligible Materials, Equipment and Services

5. The materials, equipment and services to be supplied under the Contract and financed by the Bank may have their origin in any country subject to Para. 9. At the Employer's request, Contractors may be required to provide evidence of the origin of materials, equipment and services.

Eligible Contractors

- 6. In case the Contractor is a joint venture (JV), all members shall be jointly and severally liable for the execution of the entire Contract in accordance with the Contract terms. The JV shall nominate a representative who shall have the authority to conduct all business for and on behalf of any and all the members of the JV during the Request for Quotations process and, in the event the JV is awarded the Contract, during contract execution.
- 7. A Contractor may have the nationality of any country, subject to the restrictions pursuant to paras. 8 and 9 hereinafter. A Contractor shall be deemed to have the

nationality of a country if the Contractor is constituted, incorporated or registered in, and operates in conformity with, the provisions of the laws of that country, as evidenced by its articles of incorporation (or equivalent documents of constitution or association) and its registration documents, as the case may be. This criterion also shall apply to the determination of the nationality of proposed subcontractors or subconsultants for any part of the Contract including Related Services.

- 8. Firms and individuals may be ineligible if so indicated in para.9 below and:
 - (a) as a matter of law or official regulations, the Borrower's country prohibits commercial relations with that country, provided that the Bank is satisfied that such exclusion does not preclude effective competition for the supply of goods or the contracting of works or services required; or
 - (b) by an act of compliance with a decision of the United Nations Security Council taken under Chapter VII of the Charter of the United Nations, the Borrower's country prohibits any import of goods or contracting of works or services from that country, or any payments to any country, person, or entity in that country.
- 9. In reference to paras. 5 and 7, for the information of Contractors, at the present time firms, goods and services from the following countries are excluded from this procurement process:
 - (a) Under para. 5 and 8 (a) none
 - (b) Under para. 5 and 8 (b): none
- 10. A Contractor that has been sanctioned by the Bank, pursuant to the Bank's Anti-Corruption Guidelines, in accordance with its prevailing sanctions policies and procedures as set forth in the WBG's Sanctions Framework as described in the appendix to the Contract Conditions (Appendix A) paragraph 2.2 d., shall be ineligible to submit Quotations or be awarded or otherwise benefit from a Bank-financed contract, financially or otherwise, during such period of time as the Bank shall have determined. A list of debarred firms and individuals is available on the Bank's external website: http://www.worldbank.org/debarr.
- 11. Contractors that are state-owned enterprises or institutions in the Employer's country may be eligible to compete and be awarded a Contract(s) only if they can establish, in a manner acceptable to the Bank, that they:
 - (a) are legally and financially autonomous.
 - (b) operate under commercial law; and
 - (c) are not under supervision of the Employer.
- 12. A Contractor shall not have a conflict of interest. Any Contractor found to have a conflict of interest shall be disqualified. A Contractor may be considered to have a conflict of interest for the purpose of this Request for Quotations process, if the Contractor:
 - (a) directly or indirectly controls, is controlled by or is under common control with another Contractor that submitted a Quotation.

(b) receives or has received any direct or indirect subsidy from another Contractor that submitted a Quotation.

- (c) has the same legal representative as another Contractor that submitted a Quotation.
- (d) has a relationship with another Contractor that submitted a Quotation, directly or through common third parties, that puts it in a position to influence the Quotation of another Contractor, or influence the decisions of the Employer regarding this Request for Quotations process; or
- (e) or any of its affiliates participated as a consultant in the preparation of the design or technical specifications of the works that are the subject of the Request for Quotations process; or
- (f) or any of its affiliates has been hired (or is proposed to be hired) by the Employer or Borrower for implementing the Contract; or
- (g) would be providing goods, works, or non-consulting services resulting from, or directly related to consulting services for the preparation or implementation of the project specified in this Request for Quotations, that it provided or were provided by any affiliate that directly or indirectly controls, is controlled by, or is under common control with that firm; or
- (h) has a close business or family relationship with a professional staff of the Borrower (or of the project implementing agency, or of a recipient of a part of the loan) who:
 (i) are directly or indirectly involved in the preparation of the Request for Quotations or specifications and/or the evaluation of Quotations, of the subject Contract; or (ii) would be involved in the implementation or supervision of such Contract unless the conflict stemming from such relationship has been resolved in a manner acceptable to the Bank throughout the Request for Quotations process and execution of the Contract.

Validity of Quotations

13. The quotations shall be valid until 10th October 2023

Price

- 14. The Contractor shall quote its total price in the Contractor's Quotation Form Lump-Sum contract
- 16. The Contractor shall also fill in a breakdown of its lump-sum price in the attached Activity Schedules.
 - The quoted price shall include all duties, taxes, and other levies payable by the Contractor under the Contract, as of the date 7 (seven) days prior to the deadline for submission of quotations.]
- 17. The currency of the Quotation and the currency of payments shall Maldivian Rufiyaa (MVR).

Clarifications

18. For Clarification of RFQ purposes only, the Purchaser's address is:

Thaasyn Hilmy

Project Director

Project Management Unit

Ministry of Economic Development

Velaanaage

Ameeru Ahmed Magu

Tel: +960 3323668

Email Address: tender.pmu@trade.gov.mv

Cc: meery.pmu@trade.gov.mv

Request for clarification should be received by the employer no later than: 9th July 2023 (4:00 pm)

Submission of Quotations

- 19. The deadline for submission of Quotations is 12th July 2023 at 11:00 am
- 20. The address for submission of Quotations is:

Ministry of Economic Development

Velaanaage 11th Floor

Ameer Ahmed Magu

Male' Maldives.

Attn: Mr. Thaasyn Hilmy

Project Director

Tel: +960 3323668

Bidders *shall not* have the option of submitting their Bids electronically.

Opening of Quotations

21. Quotations will be opened by the Employer's representatives in the presence of the Bidders' designated representatives and anyone who chooses to attend at the address below on 12th July 2023 at 11:00 am.

Evaluation of Ouotations

22. The RFQ will be evaluated using the following Criteria.

Details	Points	
Certificate of Registration	Prerequisite	
GST Registration Certificate (If Applicable)	Prerequisite	
Bidders Experience:		
Completed similar projects in past 3 years – (at least 3 successfully	Prerequisite	
completed works)	1	
*Reference/completion letters should be provided.		
Duration (work must be completed latest by 60 Calendar Days)	Prerequisite	
Technical Specification (must meet with the minimum requirement	Prerequisite	
of the announced specification)	Trerequisite	
Price (In calculating the score under this criterion, the party quoting the lowest		
Price will get 100 points allocated under this criterion and the points for the	100	
remaining bidders will be distributed on a pro rata basis in descending order)		

Note: Points for Price are calculated as follows: (Submitted lowest Price / Submitted Price per bidder) * Allocated Percentage

Contract Award

- 23. The Contract will be awarded to the Contractor who meets the eligibility requirements in accordance with the RFQ, offers the lowest evaluated price and the highest Technical Specifications and guarantees supply of goods by the specified date.
- 24. The Employer shall invite by email the successful Contractor for any discussion that may be needed to conclude the contract or otherwise for contract signature.
- 25. The Employer shall communicate by email with the other Contractors on its contract award decision. An unsuccessful Contractor may request clarifications as to why its quotation was not determined to be successful. The Employer will address this request within a reasonable time.
- 26. The Employer shall publish a contract award notice on its website with free access, if available, or in a newspaper of national circulation, within 15 (fifteen) days after award of contract. The information shall include the name of the successful Contractor, the Contract Price, the Contract duration, summary of its scope and the names of the Contractors and their quoted and evaluated prices.

On behalf of the Employer:

Name: Thaasyn Hilmy

Title/position: Project Director

Attachments:

Annex 1: Technical Requirements (Attached)

Annex 2: Quotation Form (Included)

ANNEX 1: Technical Requirements

Tablet with Keyboard, Mouse and Tablet Docking station, Thermal Receipt Printer, Barcode Scanner

Name	QTY	Specification
Tablet With Mouse, Keyboard & Tablet Docking Station	1	 Standing screen display size: 13 Inches Screen Resolution: 2880 x 1920 Pixels Processor: 4.8 GHz core i7 RAM: 16 GB LPDDR4 Hard Drive: 256GB SSD Wireless Type: 802.11ax Warranty: 1 Year warranty OS: Windows 11 Keyboard: Detachable Keyboard Mouse: Wireless Optical Mouse Tablet Docking Station: - 4 x USB Type-C - 2 x USB Type-A - 1 x 3.5mm Audio Jack - 1 x Ethernet - Surface Connect Connector - Compatibility Surface Pro 8
Thermal Receipt Printer	1	 Print Method: Thermal line printing Print Speed: 250 mm/sec Print Life: 100 Km Print Command: ESC / POS print commands set Multi I/O Interface (Serial + Ethernet + USB) Cash Drawer Connection Port (RJ-11) DPI: 203 Paper Auto-Cutter Warranty: 1 Year warranty
Barcode Scanner	2	 Wireless, Handheld with Base Light Source Red LED(630nm) Scanning Patterns Image scanning Scanning Speed 200 times/s Minimum Resolution 0.10mm Decoding Depth 0-260mm Scanning Angle 60°, 40°, 360° (skew, pitch, roll) Decoding Capabilities EAN-8, EAN-13, UPC-A, UPC-E, Code 39, Code 93, Code 128, EAN128, Codaber, Industoal 2 of 5, Interleave 2 of 5, Matrix 2 of 5, MSI, GS1,QR CODE, PDF417, Data Matrix, Aztec code, Maxi code Decoding Error Rate 1/5 million Indicator Beeper, LED

 Operating Modes Hand-held, Auto-detection Warranty: 1 Year warranty 	
--	--

I year warranty and support (after sales service is required if applicable)

IP CCTV Camera with 8CH NVR

Name	QTY	Specification
		Up to 2 megapixel high resolution
		• 2.8 mmm fixed lens
		• H.265, H.265+, H.264+, H.264
		•120dB Wide Dynamic Range
ID C D	0	• 3D Digital Noise Reduction
IP Camera Dome	8	• DC12V & PoE (802.3af)
		• IR range: up to 30 m
		Support on-board storage, up to 128 GB
		• IP67, IK10
		Warranty: 1 Year warranty
	1	Third-party network cameras supported
		Up to 8 Megapixels resolution recording
		• Support 1-ch HDMI, 1-ch VGA, HMDI at up to
		4K(3840x2160)
		• 8/16-ch network cameras can be connected with
IP POE NVR		80M/160M incoming bandwidth
		4TB Surveillance HDD Installed
		• Plug & Play with up to 8 independent PoE network
		interfaces
		•Support H.265/H.264/MPEG4 video formats
		Warranty: 1 Year warranty

I year warranty and support (after sales service is required if applicable)

Name	QTY	Specification
Fingerprint/time attendance machine	1	 User Capacity: 3,000 Fingerprint Capacity: 1,000 ID Card Capacity: 3,000 Record Capacity: 50,000 Display: 2.8' color screen Communication: TCP/IP, WiFi, USB-host Standard Functions: 9 Digit User ID, T9 Input, SMS, DST, Self-Service Query, Automatic Status Switch, Ring bell, Cloud/Web Server (ADMS) Optional Functions: ID/Mifare, RS232 External Printer Access Control Interface: 3rd Party Electric Lock, Exit Button Software Support: BioTime 8. BioTime 8.5 Warranty: 1 Year warranty
IP Desk Phone	1	• 2 SIP accounts, 2 line keys, 3-way conferencing, 3 XML programmable context-sensitive soft keys

		HD audio on speakerphone and handset
		Dual-switched Gigabit ports, integrated PoE
		8 dual-colored BLF/speed dial keys
		EHS support for Plantronics headsets
		Up to 1000 contacts, call history up to 200 records
		Warranty: 1 Year warranty
		Category: UTP CAT 6 Can deuten Towns Salid Boar Commun.
		Conductor Type: Solid Bare CopperConductor AWG: 23 AWG
Network Cable Roll	1	
		• Length: 305 Meters
		Warranty: 1 Year warranty
		Functions: Print, Scan, Copy
		Paper: A4
		Printer Type: color
		Print speed: min 18 PPM
		• 2 Side printing (Auto Duplex)
		Resolution: up to 600 DPI
Printer/Scanner	1	Scanner: automatic document feeder
		• paper tray: min 50 Sheets A4
		 Paper handling. Min 90GSM A4
		Connectivity: LAN, USB, Wifi
		Parts and Warranty: 1 Year warranty & Consumables
		Should be available locally
Passport MRZ reader	1	 USB powered (no power supply), single interface cable Bi-directional swiping Desktop mount for stable, non-slip swiping Read success is shown using a red, green, blue LED indicator Operating Systems Windows 10 Reading Capability MRZ, MSR Warranty: 1 Year warranty
WiFi Access point	2	 Wireless Frequency Bands: 2.4 GHz, 5 GHz Dual-Band MU-MIMO Support: 3 x 3 WLAN Mode: Wi-Fi 5 (802.11ac) Throughput 1750 Mb/s Total, 2.4 GHz: 450 Mb/s, 5 GHz: 1300 Mb/s Interface Ports 2 x 10/100/1000 Mb/s Gigabit Ethernet (RJ45) PoE+ Warranty: 1 Year warranty
Background sound system	1	 9.1 True Wireless Surround Sound Bar 820W Output power Built-in Dolby Atmos and DTS: X decoding With detachable, battery powered surround speakers you can enjoy real surround sound without the wires

		 Experience deep bass with a 300W, 10" powered subwoofer Ultra HD 4K Pass-through with Dolby Vision Connector Type: Optical Wireless Communication Technology: Wi-Fi, Bluetooth Warranty: 1 Year warranty
Laptop	1	• Core i7, 256GB SSD, 8GB RAM, 14 inch
Thermal barcode printer	1	Thermal Transfer and Thermal Direct, 1D & 2D Barcode Label Printer
Barcode Label Roll	100	 Size: 30x20x800 Adhesive on one side.

I year warranty and support (after sales service is required if applicable)

POS System - QTY 1

System			
Processor	Intel® Celeron J1900 Quad-Core processor (2.0 GHz)		
System Memory	8GB Standard, DDR3L 1333MHz (Upgraded)		
Storage Device	128GB SSD Standard (Upgraded)		
Operating System	Windows 7, Windows 8, Windows 10 IoT Enterprise		
Audio	Realtek ALC662		
Display and Touch			
Туре	15" TFT LCD, LED Backlight		
Resolution	1024×768		
Touch Screen	Projected Capacitive Touch Screen		
Customer Display	LED (8C digital tube)		
External I/O Ports			
VGA	1*DB-15		
USB	5* USB 2.0,1* USB 3.0		
Serial	1*RS232(Max.4pcs)		
LAN	1*RJ45		
Audio	1* 1*Line-out		
Power			
Power Supply	Adaptor 12V DC 5A		
Other Peripherals			
2nd Display	12.1" TFT LCD		
Customer Display	20 columns × 2 Lines		
MSR	Tracks		
Fingerprint	USB fingerprint reader (SLK20R)		

I year warranty and support (after sales service is required if applicable)

Mirrorless Camera with Lense, UV Filter, Camera Bag, Battery, Battery Charger, and SD Card - QTY 1

Name	QTY
Camera	1
Imaging	
Lens Mount	Canon RF
Sensor Resolution	Actual: 25.6 Megapixel
	Effective: 24.2 Megapixel (6000 x 4000)
Image Sensor	35.9 x 23.9 mm (Full-Frame) CMOS
Image Stabilization	Sensor-Shift, 5-Axis
Built-In ND Filter	None
Capture Type	Stills & Video
Exposure Control	
Shutter Type	Electronic Shutter, Mechanical Focal Plane Shutter
Shutter Speed	Mechanical Shutter
	1/8000 to 30 Seconds
	Electronic Shutter
	1/16000 to 30 Seconds
Bulb/Time Mode	Bulb Mode
ISO Sensitivity	100 to 102,400 in Manual, Auto Mode (Extended: 50 to 204,800)
Metering Method	Center-Weighted Average, Evaluative, Partial, Spot
Exposure Modes	Aperture Priority, Manual, Program, Shutter Priority
Exposure Compensation	-3 to +3 EV (1/3, 1/2 EV Steps)
Metering Range	-3 to 20 EV
White Balance	Presets: Auto, Cloudy, Color Temperature, Custom, Daylight, Flash, Fluorescent (White), Shade, Tungsten
Continuous Shooting	Mechanical Shutter
	Up to 12 fps at 24 MP for up to 1000 Frames (JPEG) / 110 Frames (Raw)
	Electronic Shutter
	Up to 40 fps at 24 MP for up to 190 Frames (JPEG) / 75 Frames (Raw)
Interval Recording	Yes
Self-Timer	2/10-Second Delay
Still Image Capture	
Aspect Ratio	1:1, 3:2, 4:3, 16:9
Image File Format	C-RAW, HEIF, JPEG
Bit Depth	14-Bit
Video Capture	
Internal Recording Modes	H.264/H.265/MPEG-4 4:2:2 10-Bit

1920 x 1080 at 23.98/25/29.97/50/59.94/100/150 fps [12 to 270 Mb/s]		UHD 4K (3840 x 2160) at 23.98/25/29.97/50/59.94 fps [60 to 340 Mb/s]		
Gamma Curve Canon Log 3, HDR-PQ Recording Limit None IP Streaming Yes Built-In Microphone Type Stereo Audio Recording LPCM Audio Interface LPCM Audio Media/Memory Card Slot Dual Slot: SD/SDHC/SDXC (UHS-II) Video I/O 1 x Micro-HDMI Output Audio I/O 1 x 1/8" / 3.5 mm TRS Stereo Microphone Input on Camera Body Power I/O 1 x USB-C Input Other I/O 1 x USB-C (USB 3.2 / 3.1 Gen 2) Data/Tether Input/Output (Shared with Power Input) 1 x 2.5 mm Sub-Mini Control 1 x 2.5 mm Sub-Mini Control Wireless 2.4 / 5 GHz Wi-Fi 5 (802.11ac) Control Bluetooth Bluetooth Size 3.0" Resolution 1,620,000 Dot Display Type Articulating Touchscreen LCD Viewfinder Type Built-In Electronic (OLED) Size 0.5" Resolution 3,690,000 Dot Eye Point 23 mm Coverage 100% Magnification Approx. 0.76x Di		1920 x 1080 at 23.98/25/29.97/50/59.94/100/150 fps [12 to 270 Mb/s]		
Gamma Curve Canon Log 3, HDR-PQ Recording Limit None IP Streaming Yes Built-In Microphone Type Stereo Audio Recording LPCM Audio Interface Interface Media/Memory Card Slot Dual Slot: SD/SDHC/SDXC (UHS-II) Video I/O 1 x Micro-HDMI Output Audio I/O 1 x 1/8" / 3.5 mm TRS Stereo Microphone Input on Camera Body Power I/O 1 x USB-C Input Other I/O 1 x USB-C Input Wireless 2.4 / 5 GHz Wi-Fi 5 (802.11ac) Control Bluetooth Bluetooth Size 3.0" Resolution 1,620,000 Dot Display Type Articulating Touchscreen LCD Viewfinder Type Built-In Electronic (OLED) Size 0.5" Resolution 3,690,000 Dot Eye Point 23 mm Coverage 100% Magnification Approx. 0.76x Diopter Adjustment -4 to +2 Focus Mode Continuous-Servo AF, Manual Focus, Single-Servo AF <	External Recording Modes	Raw via HDMI		
Recording Limit None P Streaming Yes Built-In Microphone Type Audio Audio Recording LPCM Audio AAC Audio AAC Audio Audio Media/Memory Card Slot Video I/O		6144 x 4032 up to 59.94 fps		
IP Streaming Yes Built-In Microphone Type Stereo Audio Recording LPCM Audio Interface Media/Memory Card Slot Dual Slot: SD/SDHC/SDXC (UHS-II) Video I/O 1 x Micro-HDMI Output Audio I/O 1 x 1/8" / 3.5 mm TRS Stereo Microphone Input on Camera Body Power I/O 1 x USB-C Input Other I/O 1 x USB-C (USB 3.2 / 3.1 Gen 2) Data/Tether Input/Output (Shared with Power Input) Power I/O 1 x USB-C (USB 3.2 / 3.1 Gen 2) Data/Tether Input/Output (Shared with Power Input) Wireless 2.4 / 5 GHz Wi-Fi 5 (802.11ac) Control Bluetooth Bluetooth Size 3.0" Resolution 1,620.000 Dot Display Type Articulating Touchscreen LCD Viewfinder Type Built-In Electronic (OLED) Size 0.5" Resolution 3,690,000 Dot Eye Point 23 mm Coverage 100% Magnification Approx. 0.76x Diopter Adjustment -4 to +2 Focus Focus Mode Continuous-Servo AF, Manual Focus, Singl	Gamma Curve	Canon Log 3, HDR-PQ		
Built-In Microphone Type Stereo Audio Recording LPCM Audio Interface Media/Memory Card Slot Dual Slot: SD/SDHC/SDXC (UHS-II) Video I/O 1 x Micro-HDMI Output Audio I/O 1 x 1/8" / 3.5 mm TRS Stereo Microphone Input on Camera Body Power I/O 1 x USB-C Input Other I/O 1 x USB-C Input Wireless 2.4 / 5 GHz Wi-Fi 5 (802.11ac) Control Bize 3.0" Resolution 1,620,000 Dot Display Type Articulating Touchscreen LCD Viewfinder Type Built-In Electronic (OLED) Size 0.5" Resolution 3,690,000 Dot Eye Point 23 mm Coverage 100% Magnification Approx. 0.76x Diopter Adjustment -4 to +2 Focus Auto and Manual Focus Focus Mode Continuous-Servo AF, Manual Focus, Single-Servo AF Focus Bode Continuous-Servo AF, Manual Focus, Single-Servo AF Autofocus Sensitivity -6.5 to +21 EV	Recording Limit	None		
Audio Recording	IP Streaming	Yes		
AAC Audio Interface Media/Memory Card Slot Dual Slot: SD/SDHC/SDXC (UHS-II) Video I/O	Built-In Microphone Type	Stereo		
Interface Media/Memory Card Slot Dual Slot: SD/SDHC/SDXC (UHS-II)	Audio Recording	LPCM Audio		
Media/Memory Card Slot Dual Slot: SD/SDHC/SDXC (UHS-II) Video I/O 1 x Micro-HDMI Output Audio I/O 1 x 1/8"/3.5 mm TRS Stereo Microphone Input on Camera Body Power I/O 1 x USB-C Input Other I/O 1 x USB-C Input Other I/O 1 x USB-C (USB 3.2 / 3.1 Gen 2) Data/Tether Input/Output (Shared with Power Input) 1 x 2.5 mm Sub-Mini Control Wireless 2.4 / 5 GHz Wi-Fi 5 (802.11ac) Control Bluetooth Size 3.0" Resolution 1,620,000 Dot Display Type Articulating Touchscreen LCD Viewfinder Viewfinder Type Built-In Electronic (OLED) Size 0.5" Resolution 3,690,000 Dot Eye Point 23 mm Coverage 100% Magnification Approx. 0.76x Diopter Adjustment -4 to +2 Focus Focus Type Auto and Manual Focus Focus Mode Continuous-Servo AF, Manual Focus, Single-Servo AF Autofocus Points Photo, Video Contrast Detection, Phase Detection: 1053		AAC Audio		
Video I/O 1 x Micro-HDMI Output Audio I/O 1 x 1/8"/3.5 mm TRS Stereo Microphone Input on Camera Body Power I/O 1 x USB-C Input Other I/O 1 x USB-C (USB 3.2 / 3.1 Gen 2) Data/Tether Input/Output (Shared with Power Input) I x USB-C (USB 3.2 / 3.1 Gen 2) Data/Tether Input/Output (Shared with Power Input) Wireless 1 x 2.5 mm Sub-Mini Control Bluetooth Bluetooth Size 3.0" Resolution 1,620,000 Dot Display Type Articulating Touchscreen LCD Viewfinder Type Built-In Electronic (OLED) Size 0.5" Resolution 3,690,000 Dot Eye Point 23 mm Coverage 100% Magnification Approx. 0.76x Diopter Adjustment -4 to +2 Focus Auto and Manual Focus Focus Type Auto and Manual Focus Focus Mode Continuous-Servo AF, Manual Focus, Single-Servo AF Autofocus Points Photo, Video Contrast Detection, Phase Detection: 1053 Autofocus Sensitivity -6.5 to +21 EV	Interface			
Audio I/O	Media/Memory Card Slot	Dual Slot: SD/SDHC/SDXC (UHS-II)		
1 x 1/8" / 3.5 mm TRS Stereo Headphone Output on Camera Body	Video I/O	1 x Micro-HDMI Output		
Power I/O	Audio I/O	1 x 1/8" / 3.5 mm TRS Stereo Microphone Input on Camera Body		
Other I/O 1 x USB-C (USB 3.2 / 3.1 Gen 2) Data/Tether Input/Output (Shared with Power Input)		1 x 1/8" / 3.5 mm TRS Stereo Headphone Output on Camera Body		
Power Input) 1 x 2.5 mm Sub-Mini Control	Power I/O	1 x USB-C Input		
Wireless 2.4 / 5 GHz Wi-Fi 5 (802.11ac) Control Bluetooth Bluetooth Size 3.0" Resolution 1,620,000 Dot Display Type Articulating Touchscreen LCD Viewfinder Type Built-In Electronic (OLED) Size 0.5" Resolution 3,690,000 Dot Eye Point 23 mm Coverage 100% Magnification Approx. 0.76x Diopter Adjustment -4 to +2 Focus Focus Type Focus Type Auto and Manual Focus Focus Mode Continuous-Servo AF, Manual Focus, Single-Servo AF Autofocus Points Photo, Video Contrast Detection, Phase Detection: 1053 Autofocus Sensitivity -6.5 to +21 EV	Other I/O	1 x USB-C (USB 3.2 / 3.1 Gen 2) Data/Tether Input/Output (Shared with Power Input)		
Bluetooth				
Size 3.0" Resolution 1,620,000 Dot Display Type Articulating Touchscreen LCD Viewfinder Type Built-In Electronic (OLED) Size 0.5" Resolution 3,690,000 Dot Eye Point 23 mm Coverage 100% Magnification Approx. 0.76x Diopter Adjustment -4 to +2 Focus Focus Type Auto and Manual Focus Focus Mode Continuous-Servo AF, Manual Focus, Single-Servo AF Autofocus Points Photo, Video Contrast Detection, Phase Detection: 1053 Autofocus Sensitivity -6.5 to +21 EV	Wireless	1		
Resolution 1,620,000 Dot Display Type Articulating Touchscreen LCD Viewfinder Type Built-In Electronic (OLED) Size 0.5" Resolution 3,690,000 Dot Eye Point 23 mm Coverage 100% Magnification Approx. 0.76x Diopter Adjustment -4 to +2 Focus Focus Type Auto and Manual Focus Focus Mode Continuous-Servo AF, Manual Focus, Single-Servo AF Autofocus Points Photo, Video Contrast Detection, Phase Detection: 1053 Autofocus Sensitivity -6.5 to +21 EV Flash				
Display Type Articulating Touchscreen LCD Viewfinder Type Built-In Electronic (OLED) Size 0.5" Resolution 3,690,000 Dot Eye Point 23 mm Coverage 100% Magnification Approx. 0.76x Diopter Adjustment -4 to +2 Focus Focus Type Focus Mode Continuous-Servo AF, Manual Focus, Single-Servo AF Autofocus Points Photo, Video Contrast Detection, Phase Detection: 1053 Autofocus Sensitivity -6.5 to +21 EV Flash	Size	3.0"		
Viewfinder Built-In Electronic (OLED) Size 0.5" Resolution 3,690,000 Dot Eye Point 23 mm Coverage 100% Magnification Approx. 0.76x Diopter Adjustment -4 to +2 Focus Focus Type Focus Type Auto and Manual Focus Focus Mode Continuous-Servo AF, Manual Focus, Single-Servo AF Autofocus Points Photo, Video Contrast Detection, Phase Detection: 1053 Autofocus Sensitivity -6.5 to +21 EV Flash				
Type Built-In Electronic (OLED) Size 0.5" Resolution 3,690,000 Dot Eye Point 23 mm Coverage 100% Magnification Approx. 0.76x Diopter Adjustment -4 to +2 Focus Focus Type Focus Type Auto and Manual Focus Focus Mode Continuous-Servo AF, Manual Focus, Single-Servo AF Autofocus Points Photo, Video Contrast Detection, Phase Detection: 1053 Autofocus Sensitivity -6.5 to +21 EV		Articulating Touchscreen LCD		
Size 0.5" Resolution 3,690,000 Dot Eye Point 23 mm Coverage 100% Magnification Approx. 0.76x Diopter Adjustment -4 to +2 Focus Focus Type Auto and Manual Focus Focus Mode Continuous-Servo AF, Manual Focus, Single-Servo AF Autofocus Points Photo, Video Contrast Detection, Phase Detection: 1053 Autofocus Sensitivity -6.5 to +21 EV	Viewfinder			
Resolution 3,690,000 Dot Eye Point 23 mm Coverage 100% Magnification Approx. 0.76x Diopter Adjustment -4 to +2 Focus Focus Type Focus Type Auto and Manual Focus Focus Mode Continuous-Servo AF, Manual Focus, Single-Servo AF Autofocus Points Photo, Video Contrast Detection, Phase Detection: 1053 Autofocus Sensitivity -6.5 to +21 EV	Туре	Built-In Electronic (OLED)		
Eye Point 23 mm Coverage 100% Magnification Approx. 0.76x Diopter Adjustment -4 to +2 Focus Focus Type Auto and Manual Focus Focus Mode Continuous-Servo AF, Manual Focus, Single-Servo AF Autofocus Points Photo, Video Contrast Detection, Phase Detection: 1053 Autofocus Sensitivity -6.5 to +21 EV	Size	0.5"		
Coverage 100% Magnification Approx. 0.76x Diopter Adjustment -4 to +2 Focus Focus Type Auto and Manual Focus Focus Mode Continuous-Servo AF, Manual Focus, Single-Servo AF Autofocus Points Photo, Video Contrast Detection, Phase Detection: 1053 Autofocus Sensitivity -6.5 to +21 EV	Resolution	3,690,000 Dot		
Magnification Approx. 0.76x Diopter Adjustment -4 to +2 Focus Focus Type Auto and Manual Focus Focus Mode Continuous-Servo AF, Manual Focus, Single-Servo AF Autofocus Points Photo, Video Contrast Detection, Phase Detection: 1053 Autofocus Sensitivity -6.5 to +21 EV Flash	Eye Point	23 mm		
Diopter Adjustment Focus Focus Type Auto and Manual Focus Focus Mode Continuous-Servo AF, Manual Focus, Single-Servo AF Autofocus Points Photo, Video Contrast Detection, Phase Detection: 1053 Autofocus Sensitivity Flash -4 to +2 Auto and Manual Focus Continuous-Servo AF, Manual Focus, Single-Servo AF Photo, Video Contrast Detection: 1053	Coverage			
Focus Focus Type Auto and Manual Focus Focus Mode Continuous-Servo AF, Manual Focus, Single-Servo AF Autofocus Points Photo, Video Contrast Detection, Phase Detection: 1053 Autofocus Sensitivity Flash Flash	Magnification	Approx. 0.76x		
Focus Type Auto and Manual Focus Focus Mode Continuous-Servo AF, Manual Focus, Single-Servo AF Autofocus Points Photo, Video Contrast Detection, Phase Detection: 1053 Autofocus Sensitivity -6.5 to +21 EV Flash	Diopter Adjustment	-4 to +2		
Focus Mode Continuous-Servo AF, Manual Focus, Single-Servo AF Autofocus Points Photo, Video Contrast Detection, Phase Detection: 1053 Autofocus Sensitivity -6.5 to +21 EV Flash	Focus			
Autofocus Points Photo, Video Contrast Detection, Phase Detection: 1053 Autofocus Sensitivity -6.5 to +21 EV Flash	Focus Type	Auto and Manual Focus		
Contrast Detection, Phase Detection: 1053 Autofocus Sensitivity -6.5 to +21 EV Flash	Focus Mode	Continuous-Servo AF, Manual Focus, Single-Servo AF		
Autofocus Sensitivity -6.5 to +21 EV Flash	Autofocus Points	Photo, Video		
Flash		Contrast Detection, Phase Detection: 1053		
	Autofocus Sensitivity	-6.5 to +21 EV		
Built-In Flash No	Flash			
	Built-In Flash	No		

Maximum Sync Speed	1/250 Second			
Flash Compensation	-3 to +3 EV (1/3, 1/2 EV Steps)			
Dedicated Flash System	eTTL			
External Flash Connection	Intelligent Hot Shoe			
General				
Battery Type	1 x LP-E6NH Rechargeable Lithium-Ion, 7.2 VDC, 2130 mAh (Approx. 760 Shots)			
Tripod Mounting Thread	1 x 1/4"-20 Female (Bottom)			
Camera Cover	Canon R-F-5			
Camera Strap	Yes			
Battery Charger	1			
Compatibility	LP-E6NH			
Number of Battery Bays	1			
Power I/O	1 x USA Type-A Plug			
AC Input Power	100 to 240 VAC, 50 / 60 Hz			
Battery	2			
Battery Series	LP-E6NH			
Battery Capacity	2130 mAh			
Output Voltage	7.2 VDC			
Battery Chemistry	Lithium-Ion			
Dimensions	2.24 x 1.51 x 0.83" / 56.8 x 38.4 x 21 mm			
SD Card	2			
Card Type	SDXC			
Storage Capacity	128 GB			
Bus Type	UHS-II			
Speed Class	10			
UHS Speed Class	U3			
Video Speed Class	V90			
Read Speed	Maximum: 300 MB/s			
Write Speed	Maximum: 260 MB/s			
	Minimum: 90 MB/s			
Operating Temperature	-13 to 185°F / -25 to 85°C			
Storage Temperature	-40 to 185°F / -40 to 85°C			
Built-in Write-Protect Switch	Yes			
24-105mm f/4 L IS USM Lens	1			
Focal Length	24 to 105mm			
Maximum Aperture	f/4			
Minimum Aperture	f/22			
Lens Mount	Canon RF			

Angle of View 84° to 23° 20' Minimum Focus Distance 1.48" / 45 cm Maximum Magnification 0.24x Optical Design 18 Elements in 14 Groups Disphragm Blades 9, Rounded Focus Type Autofocus Image Stabilization Yes Filter Size 77 mm (Front) Dimensions (e x L) 3.29 x 4.22" / 83.5 x 107.3 mm Length at Maximum Extension 5.94" / 151 mm Extension Weight 1.54 lb / 700 g Weight I. 54 lb / 700 g UV Filter 77mm I I Filter Factor 1x (0-Stop) I Circular Size 77 mm Filter Thread I Rotating No I Front Accessory Thread / Physical Features Slim I Filter Thickness 0.13" / 3.2 mm I Filter Material Glass Glass Ring Material Brass Ring Material Brass Runding Material Brass I Focal Length 16mm <	Lens Format Coverage	Full-Frame
Maximum Magnification 0.24x Optical Design 18 Elements in 14 Groups Diaphragm Blades 9, Rounded Focus Type Autofocus Image Stabilization Yes Filter Size 77 mm (Front) Dimensions (ø x L) 3.29 x 4.22" / 83.5 x 107.3 mm Length at Maximum Extension 5.94" / 151 mm Weight 1.54 lb / 700 g UV Filter 77mm I Filter Type UV Filter Factor 1x (0-Stop) Circular Size 77 mm Filter Thread Rotating No Front Accessory Thread / Bayonet 77 mm Goatings Multi-Coating, Resistance Coating Physical Features Slim Filter Thickness 0.13" / 3.2 mm Filter Material Glass Ring Material Brass Knurling Side, Top Iomm f2.8 STM Lens I Focal Length Ifmm Maximum Aperture f/2.8 Lens Format Coverage Full-Frame Angle of View	Angle of View	84° to 23° 20'
Optical Design 18 Elements in 14 Groups Diaphragm Blades 9, Rounded Focus Type Autofocus Image Stabilization Yes Filter Size 77 mm (Front) Dimensions (ø x L) 3.29 x 4.22" ; 83.5 x 107.3 mm Length at Maximum Extension 5.94" / 151 mm Weight 1.54 lb / 700 g UV Filter 77mm I Filter Type UV Filter Factor 1x (0-Stop) Circular Size 77 mm Filter Thread Rotating No Front Accessory Thread / Payonet Multi-Coating, Resistance Coating Physical Features Slim Filter Thickness 0.13" / 3.2 mm Filter Thickness 0.13" / 3.2 mm Filter Material Glass Ring Material Brass Knurling Side, Top Iomm f2.8 STM Lens I Focal Length Iomm Maximum Aperture f/2.8 Lens Format Coverage Full-Frame Angle of View 108° 10" Minimum	Minimum Focus Distance	1.48' / 45 cm
Diaphragm Blades 9, Rounded	Maximum Magnification	0.24x
Focus Type	Optical Design	18 Elements in 14 Groups
Image Stabilization Yes Filter Size 77 mm (Front) Dimensions (ø x L) 3.29 x 4.22" / 83.5 x 107.3 mm Length at Maximum Extension 5.94" / 151 mm Weight 1.54 lb / 700 g UV Filter 77mm I Filter Type UV Filter Factor 1x (0-Stop) Circular Size 77 mm Filter Thread Rotating No Front Accessory Thread / Bayonet 77 mm Coatings Multi-Coating, Resistance Coating Physical Features Slim Filter Material Glass Ring Material Brass Knurling Side, Top 16mm f2.8 STM Lens 1 Focal Length 16mm Maximum Aperture f2.8 Minimum Aperture f2.8 Manimum Aperture f2.2 Lens Format Coverage Full-Frame Angle of View 108° 10' Minimum Focus Distance 5.1" / 13 cm Maximum Magnification 0.26x Optical Design 9 Elem	Diaphragm Blades	9, Rounded
Filter Size 77 mm (Front) Dimensions (ø x L) 3.29 x 4.22" / 83.5 x 107.3 mm Length at Maximum Extension 5.94" / 151 mm Weight 1.54 lb / 700 g UV Filter 77mm I Filter Type UV Filter Factor 1x (0-Stop) Circular Size 77 mm Filter Thread Rotating No Front Accessory Thread / Bayonet 77 mm Coatings Multi-Coating, Resistance Coating Physical Features Slim Filter Thickness 0.13" / 3.2 mm Filter Material Glass Ring Material Brass Knurling Side, Top Iomm f2.8 STM Lens I Focal Length 16mm Maximum Aperture f22.8 Minimum Aperture f22.8 Lens Format Coverage Full-Frame Angle of View 108° 10' Minimum Focus Distance 5.1" / 13 cm Maximum Magnification 0.26x Optical Design 9 Elements in 7 Groups Diaphragm Bl	Focus Type	Autofocus
Dimensions (Ø x L) 3.29 x 4.22" / 83.5 x 107.3 mm Length at Maximum Extension 5.94" / 151 mm Weight 1.54 lb / 700 g UV Filter 77mm I Filter Type UV Filter Factor 1x (0-Stop) Circular Size 77 mm Filter Thread Rotating No Front Accessory Thread / Bayonet 77 mm Coatings Multi-Coating, Resistance Coating Physical Features Slim Filter Thickness 0.13" / 3.2 mm Filter Material Glass Ring Material Brass Knurling Side, Top Iomm f2.8 STM Lens I Focal Length 16mm Maximum Aperture f22.8 Minimum Aperture f22.8 Lens Mount Canon RF Lens Format Coverage Full-Frame Angle of View 108° 10' Minimum Focus Distance 5.1" / 13 cm Maximum Magnification 0.26x Optical Design 9 Elements in 7 Groups Diaphragm Blades<	Image Stabilization	Yes
Length at Maximum Extension S.94" / 151 mm	Filter Size	77 mm (Front)
Extension I.54 lb / 700 g Weight 1.54 lb / 700 g UV Filter 77mm I Filter Type UV Filter Factor 1x (0-Stop) Circular Size 77 mm Filter Thread Rotating No Front Accessory Thread / Bayonet 77 mm Bayonet Coatings Multi-Coating, Resistance Coating Physical Features Slim Filter Thickness 0.13" / 3.2 mm Filter Material Glass Knurling Side, Top I6mm f/2.8 STM Lens I Focal Length 16mm Maximum Aperture f/2.8 Minimum Aperture f/22 Lens Mount Canon RF Lens Format Coverage Full-Frame Angle of View 108° 10' Minimum Focus Distance 5.1" / 13 cm Maximum Magnification 0.26x Optical Design 9 Elements in 7 Groups Diaphragm Blades 7, Rounded Focus Type Autofocus	Dimensions (ø x L)	3.29 x 4.22" / 83.5 x 107.3 mm
UV Filter 77mm I Filter Type UV Filter Factor 1x (0-Stop) Circular Size 77 mm Filter Thread Rotating No Front Accessory Thread / Bayonet 77 mm Coatings Multi-Coating, Resistance Coating Physical Features Slim Filter Thickness 0.13" / 3.2 mm Filter Material Glass Ring Material Brass Knurling Side, Top 16mm f2.8 STM Lens 1 Focal Length 16mm Maximum Aperture f/2.8 Minimum Aperture f/2.2 Lens Mount Canon RF Lens Format Coverage Full-Frame Angle of View 108° 10' Minimum Focus Distance 5.1" / 13 cm Maximum Magnification 0.26x Optical Design 9 Elements in 7 Groups Diaphragm Blades 7, Rounded Focus Type Autofocus		5.94" / 151 mm
Filter Type UV Filter Factor 1x (0-Stop) Circular Size 77 mm Filter Thread Rotating No Front Accessory Thread / Bayonet Coatings Multi-Coating, Resistance Coating Physical Features Slim Filter Thickness 0.13" / 3.2 mm Filter Material Glass Ring Material Brass Knurling Side, Top 16mm f/2.8 STM Lens Maximum Aperture f/2.8 Minimum Aperture f/22 Lens Mount Canon RF Lens Format Coverage Full-Frame Angle of View 108° 10' Minimum Focus Distance 5.1" / 13 cm Maximum Magnification 0.26x Optical Design 9 Elements in 7 Groups Diaphragm Blades 7, Rounded Focus Type Autofocus Image Stabilization No	Weight	1.54 lb / 700 g
Filter Factor Ix (0-Stop) Circular Size 77 mm Filter Thread Rotating No Front Accessory Thread / 77 mm Bayonet Coatings Multi-Coating, Resistance Coating Physical Features Slim Filter Thickness 0.13" / 3.2 mm Filter Material Glass Ring Material Brass Knurling Side, Top Iomn f/2.8 STM Lens I Focal Length I6mm Maximum Aperture f/2.8 Minimum Aperture f/22 Lens Mount Canon RF Lens Format Coverage Full-Frame Angle of View 108° 10' Minimum Focus Distance 5.1" / 13 cm Maximum Magnification 0.26x Optical Design 9 Elements in 7 Groups Diaphragm Blades 7, Rounded Focus Type Autofocus Image Stabilization No	UV Filter 77mm	1
Circular Size 77 mm Filter Thread Rotating No Front Accessory Thread / 77 mm Bayonet Coatings Multi-Coating, Resistance Coating Physical Features Slim Filter Thickness 0.13" / 3.2 mm Filter Material Glass Ring Material Brass Knurling Side, Top 16mm f/2.8 STM Lens I Focal Length 16mm Maximum Aperture f/2.8 Minimum Aperture f/2.8 Minimum Aperture f/22 Lens Mount Canon RF Lens Format Coverage Full-Frame Angle of View 108° 10' Minimum Focus Distance 5.1" / 13 cm Maximum Magnification 0.26x Optical Design 9 Elements in 7 Groups Diaphragm Blades 7, Rounded Focus Type Autofocus Image Stabilization No	Filter Type	UV
Rotating No Front Accessory Thread / Bayonet Coatings Multi-Coating, Resistance Coating Physical Features Slim Filter Thickness 0.13" / 3.2 mm Filter Material Glass Ring Material Brass Knurling Side, Top 16mm f/2.8 STM Lens 1 Focal Length 16mm Maximum Aperture f/2.8 Minimum Aperture f/22 Lens Mount Canon RF Lens Format Coverage Full-Frame Angle of View 108° 10' Minimum Focus Distance 5.1" / 13 cm Maximum Magnification 0.26x Optical Design 9 Elements in 7 Groups Diaphragm Blades 7, Rounded Focus Type Autofocus Image Stabilization No	Filter Factor	1x (0-Stop)
Front Accessory Thread / Bayonet Coatings Multi-Coating, Resistance Coating Physical Features Slim Filter Thickness 0.13" / 3.2 mm Filter Material Glass Ring Material Brass Knurling Side, Top 16mm f/2.8 STM Lens 1 Focal Length 16mm Maximum Aperture f/2.8 Minimum Aperture f/22 Lens Mount Canon RF Lens Format Coverage Full-Frame Angle of View 108° 10' Minimum Focus Distance 5.1" / 13 cm Maximum Magnification 0.26x Optical Design 9 Elements in 7 Groups Diaphragm Blades 7, Rounded Focus Type Autofocus Image Stabilization No	Circular Size	77 mm Filter Thread
Bayonet Coatings Multi-Coating, Resistance Coating Physical Features Slim Filter Thickness 0.13" / 3.2 mm Filter Material Glass Ring Material Brass Knurling Side, Top 16mm f/2.8 STM Lens I Focal Length 16mm Maximum Aperture f/2.8 Minimum Aperture f/22 Lens Mount Canon RF Lens Format Coverage Full-Frame Angle of View 108° 10' Minimum Focus Distance Maximum Magnification 0.26x Optical Design Diaphragm Blades 7, Rounded Focus Type Autofocus Image Stabilization No	Rotating	No
Physical Features Slim Filter Thickness 0.13" / 3.2 mm Filter Material Glass Ring Material Brass Knurling Side, Top 16mm f/2.8 STM Lens I Focal Length I6mm Maximum Aperture f/2.8 Minimum Aperture f/22 Lens Mount Canon RF Lens Format Coverage Full-Frame Angle of View 108° 10' Minimum Focus Distance 5.1" / 13 cm Maximum Magnification 0.26x Optical Design 9 Elements in 7 Groups Diaphragm Blades 7, Rounded Focus Type Autofocus Image Stabilization No		77 mm
Filter Thickness 0.13" / 3.2 mm Filter Material Glass Ring Material Brass Knurling Side, Top I6mm f/2.8 STM Lens I Focal Length 16mm Maximum Aperture f/2.8 Minimum Aperture f/22 Lens Mount Canon RF Lens Format Coverage Full-Frame Angle of View 108° 10' Minimum Focus Distance 5.1" / 13 cm Maximum Magnification 0.26x Optical Design 9 Elements in 7 Groups Diaphragm Blades 7, Rounded Focus Type Autofocus Image Stabilization No		Multi-Coating, Resistance Coating
Filter Material Ring Material Brass Knurling Side, Top 16mm f/2.8 STM Lens I Focal Length I6mm Maximum Aperture f/2.8 Minimum Aperture f/22 Lens Mount Canon RF Lens Format Coverage Full-Frame Angle of View 108° 10' Minimum Focus Distance Maximum Magnification O.26x Optical Design Pillements in 7 Groups Diaphragm Blades 7, Rounded Focus Type Autofocus Image Stabilization No	Physical Features	Slim
Ring Material Brass Knurling Side, Top 16mm f/2.8 STM Lens Focal Length 16mm Maximum Aperture f/2.8 Minimum Aperture f/22 Lens Mount Canon RF Lens Format Coverage Full-Frame Angle of View 108° 10' Minimum Focus Distance 5.1" / 13 cm Maximum Magnification 0.26x Optical Design 9 Elements in 7 Groups Diaphragm Blades 7, Rounded Focus Type Autofocus Image Stabilization No	Filter Thickness	0.13" / 3.2 mm
Knurling Side, Top 16mm f/2.8 STM Lens 1 Focal Length 16mm Maximum Aperture f/2.8 Minimum Aperture f/22 Lens Mount Canon RF Lens Format Coverage Full-Frame Angle of View 108° 10' Minimum Focus Distance 5.1" / 13 cm Maximum Magnification 0.26x Optical Design 9 Elements in 7 Groups Diaphragm Blades 7, Rounded Focus Type Autofocus Image Stabilization No	Filter Material	Glass
16mm f/2.8 STM LensFocal Length16mmMaximum Aperturef/2.8Minimum Aperturef/22Lens MountCanon RFLens Format CoverageFull-FrameAngle of View108° 10'Minimum Focus Distance5.1" / 13 cmMaximum Magnification0.26xOptical Design9 Elements in 7 GroupsDiaphragm Blades7, RoundedFocus TypeAutofocusImage StabilizationNo	Ring Material	Brass
Focal Length 16mm Maximum Aperture f/2.8 Minimum Aperture f/22 Lens Mount Canon RF Lens Format Coverage Full-Frame Angle of View 108° 10' Minimum Focus Distance 5.1" / 13 cm Maximum Magnification 0.26x Optical Design 9 Elements in 7 Groups Diaphragm Blades 7, Rounded Focus Type Autofocus Image Stabilization No	Knurling	Side, Top
Maximum Aperture f/2.8 Minimum Aperture f/22 Lens Mount Canon RF Lens Format Coverage Full-Frame Angle of View 108° 10' Minimum Focus Distance 5.1" / 13 cm Maximum Magnification 0.26x Optical Design 9 Elements in 7 Groups Diaphragm Blades 7, Rounded Focus Type Autofocus Image Stabilization No	16mm f/2.8 STM Lens	1
Minimum Aperture f/22 Lens Mount Canon RF Lens Format Coverage Full-Frame Angle of View 108° 10' Minimum Focus Distance 5.1" / 13 cm Maximum Magnification 0.26x Optical Design 9 Elements in 7 Groups Diaphragm Blades 7, Rounded Focus Type Autofocus Image Stabilization No	Focal Length	16mm
Lens MountCanon RFLens Format CoverageFull-FrameAngle of View108° 10'Minimum Focus Distance5.1" / 13 cmMaximum Magnification0.26xOptical Design9 Elements in 7 GroupsDiaphragm Blades7, RoundedFocus TypeAutofocusImage StabilizationNo	Maximum Aperture	f/2.8
Lens Format Coverage Full-Frame Angle of View 108° 10' Minimum Focus Distance 5.1" / 13 cm Maximum Magnification 0.26x Optical Design 9 Elements in 7 Groups Diaphragm Blades 7, Rounded Focus Type Autofocus Image Stabilization No	Minimum Aperture	f/22
Angle of View 108° 10' Minimum Focus Distance 5.1" / 13 cm Maximum Magnification 0.26x Optical Design 9 Elements in 7 Groups Diaphragm Blades 7, Rounded Focus Type Autofocus Image Stabilization No	Lens Mount	Canon RF
Minimum Focus Distance 5.1" / 13 cm Maximum Magnification 0.26x Optical Design 9 Elements in 7 Groups Diaphragm Blades 7, Rounded Focus Type Autofocus Image Stabilization No	Lens Format Coverage	Full-Frame
Maximum Magnification0.26xOptical Design9 Elements in 7 GroupsDiaphragm Blades7, RoundedFocus TypeAutofocusImage StabilizationNo	Angle of View	108° 10'
Optical Design 9 Elements in 7 Groups Diaphragm Blades 7, Rounded Focus Type Autofocus Image Stabilization No	Minimum Focus Distance	5.1" / 13 cm
Diaphragm Blades 7, Rounded Focus Type Autofocus Image Stabilization No	Maximum Magnification	0.26x
Focus Type Autofocus Image Stabilization No	Optical Design	9 Elements in 7 Groups
Image Stabilization No	Diaphragm Blades	7, Rounded
-	Focus Type	Autofocus
Filter Size 43 mm (Front)	Image Stabilization	No
l	Filter Size	43 mm (Front)

Dimensions (ø x L)	1.6 x 2.7" / 40.1 x 69.2 mm		
Weight	5.8 oz / 165 g		
UV Filter 43mm	1		
Filter Type	UV		
Filter Factor	1x (0-Stop)		
Circular Size	43 mm Filter Thread		
Rotating	No		
Front Accessory Thread / Bayonet	43 mm		
Coatings	Multi-Coating, Resistance Coating		
Physical Features	Slim		
Filter Thickness	0.13" / 3.2 mm		
Filter Material	Glass		
Ring Material	Brass		
Knurling	Side, Top		
Camera Bag	1		
Space	Holds Camera, 1-2 Lenses & Accessories		
Carry/Transport Options	Handle, Sling Strap		
Type of Closure	Zipper		
Interior Type	Adjustable Dividers (Hook & Loop)		
Monopod/Tripod Holder	Yes		
Water Resistance	Water Resistant (Material)		
Materials	Exterior: Nylon		
Dimensions	Exterior 14 x 8.3 x 5.1" / 35.56 x 21.08 x 12.95 cm Interior 13.1 x 8 x 4.5" / 33.27 x 20.32 x 11.43 cm		

I year warranty and support (after sales service is required if applicable)

ANNEX 2: Quotation Forms

Vendor Quotation Form

From:	[Insert Vendor's name; in case of a joint venture, specify the name of the joint venture]	
Contractor's Representative:	[Insert name of Vendor's Representative]	
Title/Position:	[Insert Representatives title or position]	
Address:	[Insert Vendor's address]	
Email:	[Insert Vendor's email address]	

To:	Ministry of Economic Development		
Employer's Representative:	Mr. Thaasyn Hilmy		
Title/Position:	Project Director		
Address:	Velaanaage 11th Floor Ameer Ahmed Magu Male' Maldives.		
	Tel: +960 3323668 E-mail: tender.pmu@trade.gov.mv		
RFQ Ref No.:	MV-MoED-368103-GO-RFQ		
Date of Quotation:			

Dear:

SUBMISSION OF QUOTATION

1. Conformity and No Reservations

In response to the above named RFQ, we offer to execute the supply of goods as per this Quotation and in conformity with the RFQ and Delivery. We confirm that we have examined and have no reservations to the RFQ, including the Contract.

2. Eligibility

We meet the eligibility requirements and have no conflict of interest, in accordance with the Request for Quotations.

3. Suspension and Debarment

We, along with any of our subcontractors, suppliers, consultants, manufacturers, or service providers for any part of the contract, are not subject to, and not controlled by any entity or individual that is subject to, a temporary suspension or a debarment imposed by the World Bank Group or a debarment imposed by the World Bank Group in accordance with the Agreement for Mutual Enforcement of Debarment Decisions between the World Bank and other development banks. Further, we are not ineligible under the Employer's Country laws or official regulations or pursuant to a decision of the United Nations Security Council.

4. **Quotation Price**

The total price of our offer is [Insert one of the options below as appropriate]

Total price is: [insert the total quoted price in words and figures, indicating the various amounts and the respective currencies];

5. Quotation Validity

Our Quotation shall be valid until the date specified in the RFQ, and it shall remain binding upon us and may be accepted at any time before it expires.

6. Commissions, gratuities, fees

We have paid, or will pay the following commissions, gratuities, or fees with respect to this Quotation

[If none has been paid or is to be paid, indicate "none."]

Name of Recipient	Address	Reason	Amount

7. Not Bound to Accept

We understand that you reserve the right to:

- **a.** accept or reject any Quotation and are not bound to accept the lowest evaluated cost Quotation, or any other Quotation that you may receive, and
- **b.** annul the RFQ process at any time prior to the award of the Contract without incurring any liability to Contractors.

8. Fraud and Corruption

We hereby certify that we have taken steps to ensure that no person acting for us, or on our behalf, engages in any type of Fraud and Corruption.

On behalf of the Contractor:

Name of the person duly authorized to sign the Quotation on behalf of the Vendor: <u>[insert complete name of person duly authorized to sign the Quotation]</u> *

Title of the person signing the Quotation: <u>[insert complete title of the person signing the Quotation]</u>

Signature of the person named above: [insert signature of person whose name and capacity are shown above]

Date signed [insert date of signing] day of [insert month], [insert year]

*The board resolution / power of attorney shall be attached to the Quotation.

Note:

The written confirmation of authorization to sign on behalf of the Entity shall indicate:

- 1. Board Resolution, if the Letter of Bid / Quotation Form was signed by the Managing Director or Director of the bidding entity demonstrating the authority of the signatory, if applicable
- 2. Power of Attorney and Board Resolution, if the Letter of Bid / Quotation Form was signed by anyone other than the Owner or any of the Board Directors of the bidding entity, if applicable.