



Secretariat of the Neykurendhoo Council
H Dh. Neykurendhoo, Republic of Maldives

ދިވެހިރާއްޖޭގެ ޖުމްހޫރިއްޔާ ގުޅިގެން
ނެއިކުލަންދޫ ސަރުކާރުގެ ޖުމްހޫރިއްޔާ ގުޅިގެން
ސަރުކާރުގެ ޖުމްހޫރިއްޔާ ގުޅިގެން

4MP IP Bullet Camera (Outdoor) x 8

Camera	
Sensor	1/3", 4.0-megapixel, progressive scan, CMOS
Day/Night	IR-cut filter with auto switch (ICR)
Adjustment angle	Pan: 0° to 360°, Tilt: 0° to 90°, Rotate: 0° to 360°
WDR	DWDR
Lens	
Lens Type	2.8mm @2.0, Fixed-focal
Illuminator	
IR Range	Up to 30m (98ft) IR range
IR On/Off Control	Auto/Manual
Video	
Video Compression	Ultra 265, H.265, H.264, MJPEG
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL/TLS, SNMP
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API, SDK
Security	Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
	Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+
Interface	
Network	1 * RJ45 10M/100M Base-TX Ethernet
General	
Power	DC 12V±25%, PoE (IEEE 802.3af)
	Power consumption: Max 5.5W
Power Interface	Ø 5.5mm coaxial power plug
Ingress Protection	Ingression protection: IP67





Secretariat of the Neykurendhoo Council
H Dh. Neykurendhoo, Republic of Maldives

ދިވެހިރާއްޖޭގެ ޖުމްހޫރިއްޔާ ގުޅިގެން
ނެއިކުލަންދޫ ސަރުކާރުގެ ޖުމްހޫރިއްޔާ ގުޅިގެން
ނެއިކުލަންދޫ ސަރުކާރުގެ ޖުމްހޫރިއްޔާ ގުޅިގެން

NVR (Network Video Recorder) x 1

Video/Audio Input	
IP Video Input	16-ch
Two-way Audio Input	t 1-ch, RCA
Network	
Protocols	P2P, UPnP, NTP, DHCP, PPPoE, SSL, TLS, HTTPS
Video/Audio Output	
HDMI/VGA Output	HDMI: 3840x2160(4K), 1920x1080p, 1600x1200, 1280x1024, 1280x720, 1024x768 VGA: 1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
Audio Output	1-ch, RCA
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Synchronous Playback	16-ch
Decoding	
Decoding format	Ultra265/H.265/H.264
Live view/ Playback	k 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	1 x 4K@30, 1 x 6MP@30, 1 x 5MP@30, 2 x 4MP@30, 4 x 1080p@30, 8 x 720p@30, 16 x D1
Hard Disk	
SATA	2 SATA interfaces
Capacity	Up to 8TB for each disk
Smart	
VCA Detection	Face detection, Intrusion detection, Line Cross detection, Audio detection, Defocus detection, Scene change detection, Auto tracking
VCA Search	Face search, Behavior search
External Interface	
Network Interface	1 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface
USB Interface	Rear panel: 1 x USB2.0, Front panel: 1 x USB2.0
PoE	
Interface	16 independent 100Mbps PoE network interfaces
Max Power	Max 30W for single port Max 240W in total (15W for each)
Supported Standard	IEEE 802.3af/at

ސަފުހާ 1 75

ނެއިކުލަންދޫ ސަރުކާރުގެ ޖުމްހޫރިއްޔާ ގުޅިގެން، 02130 ސަރުކާރުގެ ޖުމްހޫރިއްޔާ ގުޅިގެން



