

ر 1 ر 0 . حربر تر قر.

1. مورس مرد ورسوم ورد مرد مرد مرد . ۱

٠٠٠٠ ، ٠٠٠ ، ٥٠ ، ٥٠ ، ٥٠ ، ٥٠ ، ٥٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠ ١٠] سامس ، ماريز سرعوم ، تر مر مر ترسروس ، حر كر مر و مرور خرم ، مرد هو ، دهر در و ، در سرو ، . ٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ، ٠٠٠ ،

#	Quantity	Details	Features	Remarks
1	4 PC	Horn Speaker with Drive Unit (50W, 100V)	 Sound Pressure Level: 110 dB (1 W, 1 m) (When operated with a driver.) Frequency Response: 200 Hz - 6,000 Hz (When operated with a driver.) Dust/Water Protection: IP65 (When operated with a driver.) 	Preferably TOA OR Yamaha Brand
2	1 PC	Amplifier 120W	 70V, 100V & 4-16 Ω, rated power 120W 3 microphone inputs, Mic 1 with priority and muting function 2 aux line input & 1 line output for additional mixer or amplifier link Individual volume control for each microphone and line input Bass and treble control 	Preferably DSPPA OR Yamaha Brand

	Secretariat of the South Huy	vadhu Atoll Nadella Council / Lily Road, Nadella, Rep. of the Maldives	
()+(960)6840007	projects@nadellacouncil.gov.mv	www.nadellacouncil.gov.mv	Section: A
Page 1 of 7		2	



ניגניגני יניני תפצער סיצ צעיות שיא ייתי צעצ ער ייקצ איצע ייקי געלי איקצער איקצער איקצע איקצע איקצע איקצע איקצע איקצע איקצע איק ייקי איקצער איקצער איקצער איקצער איקצער איקצער איקצע איקצ

				/ /
			 Mic2,3: 600Ω, ≤3mV, unbalanced; AUX1,2, MIC1: 10kΩ, ≤300mV 50Hz - 16kHz (±3dB) 	
3	1 PC	Condenser Mic (Studio Mic)	 Connectivity Technology: Wired Connector Type: XLR Special Feature: Stand Polar Pattern: Unidirectional Cardiod characteristics Transmission range: 40 - 20,000 Hz Max. SPL (1% THD @ 1 kHz): 136 dB Impedance 100 Ohm Transformer less FET input circuit 	Preferably Behringer Brand
4	2 PC	Gooseneck Mic with Base	 Electret condenser microphone with inline preamp Integrated desktop base Cardioid polar pattern with tailored response for speech maximizes intelligibility in speech while reducing the chance for feedback Polar Pattern Cardioid Frequency Range: 70 Hz to 16 kHz Maximum SPL: 120 dB SPL (1 kHz, 1% THD) Power Sources: Phantom Power 	Preferably Behringer, Shure OR Yamaha Brand
5	100 MTR	Speaker Cable (2 Core 1.5mm ²)	Cores: 2 Core Size: 1.5 sq. mm Length: 100 Meters (Continuous)	Preferably Laser, ADJ OR Yamaha Brand

	Secretariat of the South H	uvadhu Atoll Nadella Council / Lily Road, Nadella, Rep. of the Maldives	
¢» +(960)6840007	projects@nadellacouncil.gov.mv	www.nadellacouncil.gov.mv	Section: A



			Material: Oxygen Free Copper	
			Insulation: High Density PVC Wall	
6	8 PC	XLR Microphone Cable (1 MTR)	 Microphone XLR cable with low-wear rubber jacket Material: Oxygen Free Copper XLR Female to XLR Male Length: 1M (Each Piece / 8 PCS) 	Preferably ADJ OR Yamaha Brand
7	1 PC	Wireless Headset Microphone System	 Range of up to 300 feet (100m) 14 hours of power from a single pair of AA batteries Run up to 12 channels per frequency band Diversity: Antenna Diversity Max Operating Range: 300' / 91.4 m (Line of Sight) Receiver Type: Tabletop Microphone Type: Headset Polar Pattern: Cardioid 	Preferably Shure OR Yamaha Brand
8	1 PC	Power Amplifier (300W, 2 CH @8 Ohms)	 Amplifier Power Rating Amplifier Power Rating Amplifier Power Rating Amplifier Power Channel 1000 W Bridged Channel 1000 W Bridged Ohms: 300 W per Channel 	Preferably Behringer OR Yamaha Brand

	Secretariat of the South Huvadh	u Atoll Nadella Council / Lily Road, Nadella, Rep. of the Maldives	
^{ری} +(960)6840007	projects@nadellacouncil.gov.mv	www.nadellacouncil.gov.mv	Section: A
Page 3 of 7			



◆ Amplifier Class Class-D
 Frequency Response: 20 Hz to 20 kHz ±1 dB (at 1 W, 8 Ohms) Input Impedance: 10 Kilohms (Unbalanced) 20 Kilohms (Balanced) Max Gain: 35.1 dB (at 8 Ohms) Max Input Level: +24 dBu SNR: 100 dB THD+N: 0.1% (1 kHz, at 10 W) 0.3% (1 kHz, at 1/2 Power) Crosstalk < -60 dB
◆ Sample Rate: 48 kHz
 ◆ AD/DA Conversion: A/D: 24-Bit, 128 x Over-Sampling D/A: 24-Bit, 128 x Over-Sampling
◆ Latency 1.5ms
◆ Audio Delay Adjustable Up to 74ms
• EQ 6-Band Parametric EQ
 ◆ Filters High-Pass: 20 Hz to 20 kHz Low-Pass: 20 Hz to 20 kHz
◆ Limiting Yes

	Secretariat of the South H	Huvadhu Atoll Nadella Council / Lily Road, Nadella, Rep. of the Maldives	
<i>د</i> ش+(960)6840007	projects@nadellacouncil.gov.mv	www.nadellacouncil.gov.mv	Section: A
Page 4 of 7		8	



		ד דר אית באית באיר ביצי בידי בידי באיקיבי בידי שיוש יייייי			
			 Analog Audio I/O USB 	2 x XLR 3- Pin Input 2 x 1/4" TRS Input 2 x SpeakON NL4 Output 2 x Binding Post Pair Output 2 x 1/4" TS Output 1 x USB-A	
				(2.0)	
9	2 PC	Microphone Stand without Microphone Holder	 to hold a microphot (microphone clip so height you choose Long boom arm w counterweight; ac height for singing o height for playing a Versatile design for straight mic stand; inches; base width 2 	one stand designed ne securely in place old separately) at the with molded plastic ljust to standing r speaking or seated n instrument olds flat for use as max height 85.75	Preferably Carlsbro OR Yamaha Brand

	Secretariat of the South H	Huvadhu Atoll Nadella Council / Lily Road, Nadella, Rep. of the Maldives	
¢ +(960)6840007	projects@nadellacouncil.gov.mv	www.nadellacouncil.gov.mv	Section: A
Page 5 of 7			



/	 	/	
	• Compatible with 3/8-in	nch to 5/8-inch	
	adapter		

2.1 שעבר מתכל בהעבר שנייני שניי ביי ביי ביי ביי 2.1

2.3 ھۆرمور مىشىرى 80 بۇسىرى (80%) بوۋىترۇ مەۋىرى ئە ھەند ھە بوغەر ھەند ۋە ئەرمۇدىر باسەنىمۇ ۋېرىتىردى بېرىرىدى بوغۇر سىسى تەزىچەر بوھۇ ئىرۇدۇ. 2.4 ھەندىرى ئېرىرى ھۆرمۇر قىرغانىي قىرغانى ھۆرمۇر ئىغانى ھەنۇسۇرى سەئۇمۇرى، چۆرمۇ سۇرۇر ئىسىر ئەدۇسە ھۆرمە ئىزسە

3. مسور مروع مشور مرم و مرموس مرمور.

4. وترسر ج

	Secretariat of the South Huva	adhu Atoll Nadella Council / Lily Road, Nadella, Rep. of the Maldives	
()+(960)6840007	projects@nadellacouncil.gov.mv	www.nadellacouncil.gov.mv	Section: A
Page 6 of 7			



4.2

. בי הרא הא הל אצית.

5. כישהתעה ענתכית.

	Secretariat of the South Huva	hthu Atoll Nadella Council / Lily Road, Nadella, Rep. of the Maldives	
د +(960)6840007	projects@nadellacouncil.gov.mv	www.nadellacouncil.gov.mv	Section: A
Page 7 of 7			