

دَوْرَةُ مَوْتِدَانِ مَوْتِدَانِ (IUL)14-PR/1/2024/46 دَوْرَةُ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ

مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ

1. دَوْرَةُ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ مَوْتِدَانِ

#	Description	Qty
1	<b>Canon EOS R6 Mark II Body Specification</b>	
1.1	AF Modes	One-Shot AF, AI Focus AF, Servo AF
1.2	AF Point Selection	Spot AF, 1-point AF, Expand AF area. (above/below/left/right or around), Flexible Zone AF 1 / 2 / 3, Whole area AF
1.3	AF System Points	Max. 1053 AF frame zones (Stills/Movies)
1.4	Closest Focusing Distance (cm)	0.20 / 0.34 (AF, f=24/105mm) 0.13 / 0.34 (MF, f=24/105mm)
1.5	Continuous Shooting Speed (Shots Per Sec) (Up To)	Mechanical shutter & Electronic 1st curtain: 12 Electronic shutter: 40
1.6	Digital Zoom	Digital Tele-converter x2.0 & x4.0
1.7	Dimensions (Excl. Protrusions) (mm) (Approx.)	138.4 x 98.4 x 88.4
1.8	Drive System	Leadscrew-type STM
1.9	Effective ISO	Stills: 100–102,400 (L:50 / H:204,800) Movie: 100–25,600 (H:204800) Canon Log movies: ISO 800–25,600 (L:100-640, H:32,000 - 204,800) HDR PQ movies: ISO 100–25,600
1.10	Effective Pixels (Megapixels)	24.2
1.11	Exposure Compensation	±3 stops in 1/3-stop or 1/2-stop increments. AEB: ±3 stops in 1/3-stop or 1/2-stop increments
1.12	Eye Detection AF	Auto/ Left Eye/ Right Eye (Auto, People and Animal AF mode)
1.13	Focal Length (35mm Equivalent)	24-105mm
1.14	Image Resolution	6000×4000 (JPEG L/RAW/C-RAW/HEIF) 3984×2656 (HEIF, JPEG M) 2976×1984 (HEIF, JPEG S1) 2400×1600 (HEIF, JPEG S2)
1.15	Image Stabilizer	In-body 5-axis sensor-shift image stabilization (Still/Movie) Movie Digital IS
1.16	LCD Monitor (Size) (Inch)	3.0
1.17	LCD Monitor Resolutions (dots)	1.62 million
1.18	Manual Focus	Yes



1.19	Memory Card Type	Dual Card Slots (SD, SDHC*, SDXC*) *UHS-II cards supported
1.20	Metering Mode	Stills: Evaluative, Partial, Spot, Center-weighted average Movie: Evaluative (when faces are detected), Center-weighted average (when no faces are detected/When set to Canon Log 3)
1.21	Movie Format	MP4
1.22	Optical Zoom	4.3x
1.23	Optional Power	AC Power (AC Adapter AC-E6N and DC Coupler DR-E6) USB Power (PD-E1)
1.24	Peripheral Connections	USB Type-C (SuperSpeed Plus USB (USB 3.2 Gen 2) equivalent) External microphone IN Headphone terminal HDMI micro (Type D) Remote control (BR-E1 via Bluetooth connection)
1.25	Processor Type	DIGIC X
1.26	Sensor Size	Full-frame CMOS
1.27	Shooting Modes	A+/Special scene mode/Creative filters/Fv/P/Tv/Av/M/B/C1/C2/C3
1.28	Shutter Speed Range (Sec.)	Stills: Mechanical / Electronic 1st-curtain: 30 - 1/8000 Electronic shutter: 30 - 1/16000  Movie recording: Auto exposure: 1/60* - 1/8000 Shutter-priority/Manual exposure: 1/8* - 1/8000 *Varies by shooting mode and frame rate
1.29	Silent Shutter	Yes
1.30	Standard Power Supply	LP-E6NH
1.31	Still Image Format	JPEG, HEIF, RAW, C-RAW
1.32	Viewfinder Coverage (Approx.)	100%
1.33	Viewfinder Type	0.5-inch OLED, approx. 3.69million dots 59.94/119.88 fps Refresh Rate
1.34	Weight (g) (Including the battery and memory card) (Approx.) *For camera kits, weight includes kit lens(es).	1065
1.35	White Balance	Auto (Ambience priority / White priority), Daylight, Shade, Cloudy (Effective in twilight and sunset), Tungsten light, White fluorescent light, Flash*, Custom, Color temperature setting. (approx. 2500–10000 K)  Shoot to set white balance (Live View), White balance shift and white balance bracketing features available.  *Flash color temperature information transmission possible (EX / EL Series Speedlite)
1.36	X-sync (sec.)	Mechanical shutter: 1/200, Electronic 1st curtain: 1/250
1.37	Warranty	Minimum One Year Service (Manufacturing Faults)
<b>2</b>	<b>Canon RF24-70mm f/2.8L IS USM Lens Specification</b>	
2.1	Angle of View (Diagonal)	84°00'– 34°00'
2.2	Angle of View (Horizontal)	74°00'– 29°00'
2.3	Angle of View (Vertical)	53°00'– 19°30'
2.4	Closest Focusing Distance (m, ft)	0.21 / 0.69



2.5	Construction (Groups Elements)	15-21	
2.6	Diameter x Length (mm) (Approx.)	88.5 × 125.7	
2.7	Drive System	Nano USM	
2.8	Filter Size (mm)	82	
2.9	Max. Magnification (x)	0.30 (at 32mm)	
2.10	Min. Aperture	22	
2.11	No. of Diaphragm Blades	9	
2.12	Anti-dust and Moisture	Supported	
2.13	Weight (g) (Approx.)	900	
2.14	Warranty	Minimum Six Months (Manufacturing Faults)	
<b>3</b>	<b>Godox SK300II-E Dual Studio Flashes Kit</b>		
3.1	Flash Head x 2		01
3.2	Light Stand 304 (2m height) x 2		
3.3	Softbox SB-BW (60x90cm) x 1		
3.4	Carrying Bag CB-04 x 1		
3.5	Umbrella UB-002 (40" black & silver) x 1		
3.6	Umbrella UB-004 (40" black & white) x 1		
3.7	Wireless Power-Control Flash Trigger XT16 x 1		
3.8	Warranty (Minimum Six Months (Manufacturing Faults))		
<b>4</b>	<b>Canon Speedlite 430EX III-RT Specification</b>		
4.1	Guide Number	141.08' / 43 m at ISO 100 (105 mm Position)	01
4.2	Coverage	Full-Frame 24 to 105 mm 14 mm (with Wide-Angle Adapter)	
4.3	Angle of Coverage	23.3 to 84° 114° (with Wide-Angle Adapter)	
4.4	Auto Zoom Head	Yes	
4.5	Bounce Head	0 to +90°	
4.6	Swivel Head	330°	
4.7	Recycle Time	Approx. 0.1 to 3.5 Seconds	
4.8	Exposure Control	Canon E-TTL / E-TTL II	
4.9	Flash Modes	Hi-Speed Sync, Second-Curtain Sync	
4.10	Power Range	1/1 to 1/64	
4.11	Flash Compensation	-3 to +3 EV (1/3, 1/2 EV Steps)	
4.12	Wireless Operation	Radio (TTL/Manual) Up to 98.43' / 30 m Optical Pulse (TTL/Manual) Up to 49.21' / 15 m	
4.13	Wireless Channels	15	
4.14	Wireless Groups	5	
4.15	Internal Power	4 x AA (Alkaline, NiMH)	
4.16	Mount	Shoe	
4.17	Dimensions (W x H x D)	2.8 x 4.5 x 3.9" / 70.5 x 113.8 x 98.2 mm	
4.18	Weight	10.41 oz / 295.12 g	
4.19	Warranty	Minimum Six Months (Manufacturing Faults)	







3.8. جڙتو ڪوٺا ٿيڻ تي سڄي ڀاڱي ۾ لائينڊنگ ٿيڻ، انهن ٽي سڀني ڀاڱي ۾.

3.9. انٽرنيشنل ٽريڊنگ، ڪوٺا ٿيڻ تي سڄي ڀاڱي ۾ لائينڊنگ ٿيڻ، انهن ٽي سڀني ڀاڱي ۾ لائينڊنگ ٿيڻ، انهن ٽي سڀني ڀاڱي ۾ لائينڊنگ ٿيڻ، انهن ٽي سڀني ڀاڱي ۾ لائينڊنگ ٿيڻ.

ڪوٺا ٿيڻ، انهن ٽي سڀني ڀاڱي ۾ لائينڊنگ ٿيڻ، انهن ٽي سڀني ڀاڱي ۾ لائينڊنگ ٿيڻ، انهن ٽي سڀني ڀاڱي ۾ لائينڊنگ ٿيڻ، انهن ٽي سڀني ڀاڱي ۾ لائينڊنگ ٿيڻ.

3.10. ٽريڊنگ انٽرنيشنل ٽريڊنگ ڊيپارٽمنٽ ٽريڊنگ ڊيپارٽمنٽ، ٽريڊنگ ڊيپارٽمنٽ، ٽريڊنگ ڊيپارٽمنٽ، ٽريڊنگ ڊيپارٽمنٽ، ٽريڊنگ ڊيپارٽمنٽ.

**4. ڪوٺا ٿيڻ تي**

انٽرنيشنل ٽريڊنگ ٽريڊنگ ڊيپارٽمنٽ ٽريڊنگ ڊيپارٽمنٽ، ٽريڊنگ ڊيپارٽمنٽ، ٽريڊنگ ڊيپارٽمنٽ، ٽريڊنگ ڊيپارٽمنٽ، ٽريڊنگ ڊيپارٽمنٽ.

80 ڪوٺا	• ٽريڊنگ ٽريڊنگ
20 ڪوٺا	• ڪوٺا ٿيڻ تي سڄي ڀاڱي ۾ لائينڊنگ ٿيڻ
100 ڪوٺا	• ڪوٺا ٿيڻ

**4.1. ٽريڊنگ انٽرنيشنل ٽريڊنگ ڊيپارٽمنٽ**

ٽريڊنگ انٽرنيشنل ٽريڊنگ ڊيپارٽمنٽ، ٽريڊنگ ڊيپارٽمنٽ، ٽريڊنگ ڊيپارٽمنٽ، ٽريڊنگ ڊيپارٽمنٽ، ٽريڊنگ ڊيپارٽمنٽ، ٽريڊنگ ڊيپارٽمنٽ، ٽريڊنگ ڊيپارٽمنٽ، ٽريڊنگ ڊيپارٽمنٽ، ٽريڊنگ ڊيپارٽمنٽ، ٽريڊنگ ڊيپارٽمنٽ.

$$\frac{\text{ٽريڊنگ انٽرنيشنل ٽريڊنگ ڊيپارٽمنٽ}}{\text{ٽريڊنگ ڊيپارٽمنٽ}} \times 80$$

**4.2. ڪوٺا ٿيڻ تي سڄي ڀاڱي ۾ لائينڊنگ ٿيڻ**

ڪوٺا ٿيڻ، انهن ٽي سڀني ڀاڱي ۾ لائينڊنگ ٿيڻ، انهن ٽي سڀني ڀاڱي ۾ لائينڊنگ ٿيڻ، انهن ٽي سڀني ڀاڱي ۾ لائينڊنگ ٿيڻ، انهن ٽي سڀني ڀاڱي ۾ لائينڊنگ ٿيڻ، انهن ٽي سڀني ڀاڱي ۾ لائينڊنگ ٿيڻ.

$$\frac{\text{ٽريڊنگ انٽرنيشنل ٽريڊنگ ڊيپارٽمنٽ}}{\text{ٽريڊنگ ڊيپارٽمنٽ}} \times 20$$



