







# Vaisala BAROCAP® Digital Barometer PTB330 - One Sensor

		1	2	3	4	5	6	7	8	9	10	11	12	13	14	PRICE
Digital Barometer with One Pressure Sensor		PTB330														
1 Accuracy Class	<b>Class A</b> Class B	A	B													
2 Display	<b>No display</b> <i>Graphical LCD with backlight</i>	0	1													
3 Power Supply	<b>10...35 VDC</b> 10...35 VDC with external power on/off triggering 10...35 VDC, 24 VAC, galvanical isolation for outputs (DCDC-1) Internal AC-power (110...240 VAC) (POWER-1) Internal AC-power (110...240 VAC) + US power cord (216017) External US AC-adaptor (Not IP65) (MI70USADAPTER)	A	B	C	D	F	K									
4 Signal Output	<b>RS-232 only, no analog output</b> Analog output 4...20 mA 0...20 mA 0...1 V 0...5 V 0...10 V	A	C	D	E	F	G									
5 Pressure range	<b>500...1100 hPa</b> 50...1100 hPa								H	J						
6 Optional Module (slot 3)	<b>No module</b> <i>Relay module (Select A with internal AC power)</i> (RELAY-1)	A	B													
7 Optional Module (slot 4)	<b>No module</b>	A														
8 Customer Connection	<b>Cable bushing for 10...14 mm cable</b> Conduit fitting NPT 1/2" 8-pole M12 connector with 5 m cable (212142) 8-pole M12 connector with screw terminals (212416) D9 connector Not IP65								G	D	E	F	P			
9 Pressure Fitting	<b>Barbed fitting 3/8"</b> Quick connector 1/8" (19886, 25328 + 25329)									L						
10 Optional Connection	<b>None</b> <b>Plugged</b> Cable bushing for 10...14 mm cable Conduit fitting NPT 1/2"										A	B	C	D		
11 Installation	<b>Normal mounting</b> <i>Adapter plate (for replacing PTB220)</i> (214829) <i>Pole installation kit</i> (215108) <i>Pole installation kit with Rain Shield</i> (215109) <i>DIN rail kit</i> (215094)											0	1	2	3	4
12 Calibration	<b>ISO 9001 compliant factory calibration / No calibration contract</b> <i>ISO/IEC 17025 Accredited calibration</i> (Separate order form required)													A	B	
13 Service contract	<b>No Service Contract</b>															0
14 User's Guide language	<b>No User's Guide</b> English															A
															TOTAL VALUE	
															QTY	
															TOTAL VALUE	

Items in bold are included in the basic price.  
 Selections in *italic* are available at an additional cost.  
 Shaded sections indicate typical selections.

Example of order code with typical settings:

PTB330 - One Sensor

Accessories to be ordered separately. Description:

Interface cables	Order Code:
Serial Interface Cable	19446ZZ
Software Interface Kit (MI70LINK + serial interface cable)	215005
USB-RJ45 Serial Connection Cable	219685
MI70LINK software for Windows® + USB-RJ45 Serial Connection Cable	219916

# **BAROMETER**

## PTB330 Digital Barometer for Professional Meteorology, Aviation, and Industrial Users



Vaisala BAROCAP® Digital Barometer PTB330 with a new trend display.

Vaisala BAROCAP® Digital Barometer PTB330 is a new generation barometer, designed for a wide range of high-end atmospheric pressure measurement. The pressure measurement of the PTB330 is based on the Vaisala in-house, silicon

capacitive, absolute pressure sensor - the Vaisala BAROCAP® Sensor. It provides high measurement accuracy and excellent long-term stability.

### Highly Accurate

The PTB330 series is highly accurate. The Class A barometers for the most demanding applications are fine-tuned and calibrated against a high-precision pressure calibrator. Class B barometers are adjusted and calibrated using electronic working standard. All the PTB330 barometers come with a NIST traceable, factory calibration certificate.

### Reliability through Redundancy

According to customers' choice, the PTB330 can incorporate one, two or three BAROCAP® sensors. When two or three sensors are used, the barometer continuously compares the readings of the pressure sensors

against one another and provides information on whether these are within the set internal difference criteria. This unique feature provides redundancy in pressure measurement.

Thus, users also get a stable and reliable pressure reading at all times as well as a pre-indication of when to service or recalibrate the barometer.

### QNH and QFE

The PTB330 can be set to compensate for QNH and QFE pressure used especially in aviation. The QNH represents the pressure reduced to sea level, based on the altitude and temperature of the observation site. The QFE represents the height corrected pressure of small differences in altitude, for example, the air pressure at the airfield elevation.

### Graphical Display

The PTB330 features a multi-lingual, graphical display allowing users to monitor measurement trends. The graph is updated automatically while measuring and it provides a one-year measurement history. In addition to instant pressure, the PTB330 also provides the WMO pressure trend and tendency codes.

### Applications

The PTB330 can be used successfully for aviation, professional meteorology, and for demanding industrial pressure measurement applications such as accurate laser interferometric measurement and exhaust gas analysis in engine test benches.

### Features/Benefits

- Vaisala BAROCAP® sensor
- Accurate measurement
- Excellent long-term stability
- Added reliability through redundancy
- Graphical trend display with 1-year history data
- Height and altitude corrected pressure (QFE, QNH)
- For professional meteorology and aviation, laboratories, demanding industrial applications



# Technical Data

## Performance

BAROMETRIC PRESSURE RANGE 500 ... 1100 hPa		
	Class A	Class B
Linearity*	±0.05 hPa	±0.10 hPa
Hysteresis*	±0.03 hPa	±0.03 hPa
Repeatability*	±0.03 hPa	±0.03 hPa
Calibration uncertainty**	±0.07 hPa	±0.15 hPa
Accuracy at +20 °C (+68 °F) ***	±0.10 hPa	±0.20 hPa

BAROMETRIC PRESSURE RANGE 50 ... 1100 hPa		
	Class A	Class B
Linearity*		±0.20 hPa
Hysteresis*		±0.08 hPa
Repeatability*		±0.08 hPa
Calibration uncertainty**		±0.15 hPa
Accuracy at +20 °C ***		±0.20 hPa

TEMPERATURE DEPENDENCE****		
500 ... 1100 hPa		±0.1 hPa
50 ... 1100 hPa		±0.3 hPa

TOTAL ACCURACY -40 ... +60 °C (-40 ... +140 °F)		
	Class A	Class B
500 ... 1100 hPa	±0.15 hPa	±0.25 hPa
50 ... 1100 hPa		±0.45 hPa

LONG-TERM STABILITY		
500 ... 1100 hPa		±0.1 hPa/year
50 ... 1100 hPa		±0.1 hPa/year

\* Defined as ±2 standard deviation limits of endpoint non-linearity, hysteresis or repeatability error.

\*\* Defined as ±2 standard deviation limits of inaccuracy of the working standard including traceability to NIST.

\*\*\* Defined as the root sum of the squares (RSS) of endpoint non-linearity, hysteresis error, repeatability error and calibration uncertainty at room temperature.

\*\*\*\* Defined as ±2 standard deviation limits of temperature dependence over the operating temperature range.

## Operating Environment

Pressure range	500 ... 1100 hPa, 50 ... 1100 hPa
Temperature range	
operating	-40 ... +60 °C (-40 ... +140 °F)
with local display	0 ... +60 °C (+32 ... +140 °F)

## Data Transfer Software

MI70 Link Interface Software	
Requirement:	Microsoft® Windows OS Microsoft® Excel

## Inputs and Outputs

Supply voltage	10 ... 35 VDC
Supply voltage sensitivity	negligible
Typical power consumption at +20 °C (U <sub>in</sub> 24 VDC, one pressure sensor)	
RS-232	25 mA
RS-485	40 mA
U <sub>out</sub>	25 mA
I <sub>out</sub>	40 mA
display and backlight	+20 mA
Serial I/O	RS232C, RS485/422
Pressure units	hPa, mbar, kPa, Pa inHg, mmH <sub>2</sub> O, mmHg, torr, psia
	Class A      Class B
Resolution	0.01 hPa      0.1 hPa
Settling time at power-up (one sensor)	4 s      3 s
Response time (one sensor)	2 s      1 s
Acceleration sensitivity	negligible
Pressure connector	M5 (10-32) internal thread
Pressure fitting	barbed fitting for 1/8" I.D. tubing or quick connector with shutoff valve for 1/8" hose
Maximum pressure limit	5000 hPa abs.
Compliance	EMC standard EN61326-1:1997 + Am1:1998 + Am2:2001: Industrial Environment

## Mechanics

Housing material	G AlSi10 Mg (DIN 1725)
Housing classification	IP66 IP65 (NEMA4) with local display
Weight	1 - 1.5 kg

## Analog Output (optional)

Current output	0 ... 20 mA, 4 ... 20 mA
Voltage output	0 ... 1 V, 0 ... 5 V, 0 ... 10 V
Accuracy at pressure range	500 ... 1100 hPa      50 ... 1100 hPa
at +20 °C	±0.30 hPa      ±0.40 hPa
at -40 ... +60 °C	±0.60 hPa      ±0.75 hPa

## Accessories

Serial interface cable	19446ZZ
USB-RJ45 serial connection cable	219685
Software interface kit	215005
Wall mounting kit	214829
Outdoor installation kit (weather shield)	215109
Installation kit for pole or pipeline	215108
Power supply module	POWER-1
Temperature compensated analog output module	AOUT-1T
Isolated RS-485 module	RS485-1
DIN Rail Kit	215094

# VAISALA

Please contact us at  
[www.vaisala.com/requestinfo](http://www.vaisala.com/requestinfo)



[www.vaisala.com](http://www.vaisala.com)



CE