

١٠٠٠ ١٠٠٠ ١٠٠٠ ١٠٠٠ ١٠٠٠ ١٠٠٠ ١٠٠٠ ١٠٠٠ ١٠٠٠ ١٠٠٠

[illegible]


تَجَوُّدًا وَتَقْوًى

- [illegible]

وَقَدْ خَرَجَ مَعَهُ

ج د س ر ز ه ح ط ث ذ ز ع ف ق ك غ ل م ن ي ا ب ج د ه و ز ح ط ث ذ

دَرَجَت	مَقَرَر	مَقَرَر
90%	مَقَرَر / مَقَرَر / مَقَرَر × 90	مَقَرَر
10%	مَقَرَر / مَقَرَر / مَقَرَر × 10	مَقَرَر





- مَنْ يَتَّقِ اللَّهَ يَجْعَلْ لَهُ مَخْرَجًا

- **مَنْ يَتَّقِ اللَّهَ يَجْعَلْ لَهُ مَخْرَجًا** وَمِنْ أَمْوَالِهِ يُجْزِي السَّكِينَةَ
- **وَمَنْ يَتَّقِ اللَّهَ يَجْعَلْ لَهُ مَخْرَجًا** وَمِنْ أَمْوَالِهِ يُجْزِي السَّكِينَةَ
- **وَمَنْ يَتَّقِ اللَّهَ يَجْعَلْ لَهُ مَخْرَجًا** وَمِنْ أَمْوَالِهِ يُجْزِي السَّكِينَةَ




1

Refrigerant Reclaim System - Spare Parts Specifications

 Refrigerant 22		
Spare parts List		
Name / Description / Specs	Qty.	Picture
1. Low Pressure Cut-Out Make: Johnson Controls Model: P70AB - 12 Range: 12" Hg. Vac./ 80 PSIG	01	
2. High Pressure Cut-Out Make: Johnson Controls Model: P70EA - 11 Range: 176 / 426 PSIG / 80 PSIG	01	
3. Refrigerant Drier P/N 26 – 001 WP500 PSIG / 3448KPa	24	
4. Compressor Brand: Copeland Model: RST80C1E-PFZ-201 R- 22 220/240 Volts, 1Ph, 50HZ	01	
5. Solenoid Valve Brand: Sporlan Model: E3S13C Connection: 3 /8" Soldering Type R- 22 220/240 Volts, 1Ph, 50HZ	02	



6. Low Pressure Cut-out Panel Mount Type Range: 12" Hg. Vac./ 300 PSIG Connection: 1 /4" Flare Type R- 22	01	
7. High Pressure Cut-out Panel Mount Type Range: 0 PSIG / 500 PSIG Connection: 1 /4" Flare Type R- 22	01	
8. Four Way Manifold Vacuum Gauge Set R-22, R-134, R-407C, R-410A Kit with case. Specifications: 1. Material: Aluminum Housing 2. Type: 4-Way Valve Manifold 3. Works for: R410, R22, R134, R407C, R-32, R-290 4. Burst Pressure: 4000PSI 5. Max Working Pressure: 800PSI 6. Extra Large Sight Glass: Included 7. Degrees Celsius: (°C) Reading 8. Quick Disconnect Couplers for High/Low Fittings to be Included 9. Function: Each Coupler Have a Shut off Valve to Prevent Loss of Refrigerant 10. Low Pressure Gauge: 0-550 PSI 11. High Pressure Gauge: 0-750 PSI 12. Red and Blue 60" Long Charging Hose: R12, R22, R134A SAE (1/4" x 60") 13. Yellow 60" Long Charging Hose: R12, R22, R134A SAE (1/4" x 60") 14. Black 60" Long Charging Hose: R12, R22, R134A SAE (elbow end thread 5/16" and elbow end thread 1/4" x 60") 15. 1/2" adapter is included (1/2" Female to 1/4" Male) for R134 16. 1/4" adapter is included (1/4" Female to 5/16" Male) for R410 17. Case: Included	01	



3 pcs. R134A, R410A, R22, 800 PSI Shut Valves Set with Ball Valve	01	
9. Refrigerant Identifier Specifications: - Analyzed Refrigerants: R22, R32, R134a, R404A, R407C, R410a, Hydrocarbons (HC) and Air - Identified Refrigerants: R12, R1234yf, R408A, R409A, R417A, R421A, R421B, R422A, R422B, R422C, R427A and Hydrocarbons (HC) - Accuracy: +/- 2% of indicated gasses or better - Power requirements: 12 VDC, 2A via 110/220 VAC Adapter; Built-in rechargeable Battery pack - Approvals: CE, UL, CUL - User interface: Graphic display, soft keys, built in printer - Sample gas extraction: Pressure from system or cylinder - Temperature range: 10°C to 48°C - Response time: Less than 5 Minutes - Humidity: 0-95% RH non-condensing - Test sample size: 5g per test maximum - Accessories - Sample hose - Carrying case - Power cord - Liquid sample syringe - Quick battery charger - Spare parts 5 sample filters 5 printer paper rolls 2 Sample hoses	01	



10. Filter Drier 1/4" Flare Connection, R- 22	10	
--	-----------	--