

بِسْمِ اللّٰهِ الرَّحْمٰنِ الرَّحِیْمِ



ދިވެހިސަރުކާރުގެ ގެޒެޓް ގައި ބަޔާންކުރި ސަރުކާރުގެ ސިޔާސަތު
 ގެ ދަށުން ދެނެގަތިގެން

ANNEX 1

ލިޔެކިޔުންތަކާއި ގުޅޭގޮތުން ސަލާމަތްކުރާ ނިޒާމް:

ލިޔެކިޔުންތަކާއި ގުޅޭގޮތުން 200 ވަނަ ސަލާމަތްކުރާ ނިޒާމް ބަޔާންކުރި ސަރުކާރުގެ ސިޔާސަތު.

VoIP Phone's Minimum Specifications

Brand	Grandstream (GXP)
Gigabit Network Ports	Dual-switched auto-sensing 10/100/1000mbps network ports
POE	Built-in PoE to power the device and give it a network connection
HD Audio	HD audio on the handset and speakerphone; full duplex speakerphone
Zero Config	Use with Grandstream's UCM series of IP PBXs for Zero Config provisioning
Conference Call Protocols/Standards	Audio conferencing for easy conference calls; 4-Way Conference SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, PPPoE, SSH, TELNET, TFTP, NTP, STUN, SIMPLE, LLDP, LDAP, TR-069, 802.1x, TLS, SRTP, IPV6, CDP/SNMP/RTCP-XR
LCD Display	2.8 inch (320x240) TFT color LCD
Feature Keys	8 line keys with up to 4 SIP accounts, 4 XML programmable context sensitive softkeys, 5 navigation/menu keys, 11 dedicated function keys for : MESSAGE (with LED indicator), PHONEBOOK, TRANSFER, CONFERENCE, HOLD, HEADSET, MUTE, SEND/REDIAL, SPEAKERPHONE, VOL+, VOL
Voice Codecs	Support for G.729A/B, G.711μ/a-law, G.726, G.722(wide-band),G723.1, iLBC, Opus, in-band and out-of-band DTMF (in audio, RFC2833, SIP INFO), VAD, CNG, AEC, PLC, AJS, AGC
Telephony Features	Hold, transfer, forward (unconditional/no-answer/busy), call park/pickup, conference, downloadable phone book (XML, LDAP, more than 100 records), call waiting, call history (more than 100 records), off-hook auto dial, auto answer, click-to-dial, flexible dial plan, personalized music ringtones, server redundancy & fail-over
Headset Jack	RJ9 headset jack (allowing EHS with Plantronics headsets)
Base Stand	Yes, 2 angled positions available, wall mountable



بِسْمِ اللّٰهِ الرَّحْمٰنِ الرَّحِیْمِ



ދިވެހިސަރުކާރުގެ ގެޒެޓް ގައި ބަޔާންކުރި ގޮތުގައި
މިއަހަރުގެ ފެބްރުއަރީ 2023 ވަނަ އަދަދުގައި

Security Encryptions	User and administrator level access control, HTTPS, TLS and SRTP security encryption technology to protect calls and accounts
Multi-language	Yes
Upgrade/Provisioning	Firmware upgrade via TFTP / HTTP / HTTPS, Auto Provisioning
Power	Universal Power Supply Input 100-240VAC 50-60Hz; Output +5VDC, 600mAPoE: IEEE802.3 af Class 2, 3.84W-6.49W

މިއަހަރުގެ ފެބްރުއަރީ 2023 ވަނަ އަދަދުގައި ބަޔާންކުރި ގޮތުގައި
މިއަހަރުގެ ފެބްރުއަރީ 2023 ވަނަ އަދަދުގައި ބަޔާންކުރި ގޮތުގައި

