

## Stadium Outdoor Led Screen:

- Size: Length 6 m, Width 4 m (24sqm)

- Video Processor: 2 units

### SPECIFICATION:

#### OUTDOOR P10 LED SCREEN TECHNICAL

Unit Module	Item:	Parameter
	Model:	PH10 outdoor
	Pixel Pitch:	10mm
	Pixel configuration:	RGB
	Module Size:	320mm * 160mm
	Module Resolution:	32dots(W) * 16dots(H)
	Module Thickness:	14MM
	Module Weight:	0.5 KG
	LED type:	SMD3535
	Max Power:	≤ 25W
	Pixel Density:	10000 dots / SQM
	Driving Method:	Constant Current Driving
	Scan Method:	2S
	Interface Way:	HUB75
	Brightness:	≥6000CD /SQM
Unit Cabinet	Cabinet Size:	960 * 960mm (Customize)
	Cabinet Composing:	18pcs
	Power Supply Mode:	5V/40A
	Cabinet Resolution:	96 * 96dots
	Optimal Viewing Distance:	10-200M (according to the big screen size)
	Optimal Viewing Angle:	Horizontal angle: 120 degree; Vertical angle: 60 degree
	Environment Temperature:	Storage: -40 degree ~ +85 degree Work: -20 degree ~ +60 degree
	Relative Humidity:	10% ~ 95%
Power	Operating Voltage:	AC:100V~120V AC:220~240V
	Average Power:	≤ 300W/SQM
	Max Power Consumption:	≤ 600W/SQM
Control System	Computer:	Pentium4 or I3 or above
	Operate System:	Win98/2000/NT/XP/Win7/Win10
	Control Mode:	Synchronization with PC
Main Technical Parameter	Driving Device:	IC Constant Current Driving
	Refresh Rate:	≥ 1920Hz
	Gray/Color:	RGB each 256 grade, can display 16.7color
	MTPF:	≥ 9000hours
	Power Switch:	Automatic Switch
Display Mode:	1920*1080\1024*768\1280*960	

### Bid Evaluation Points Criteria

Price – 70% (Seventy Percentages)

Duration – 30% (Thirty Percentages)