















1- 2026

2- 2026

3- 2026

25. 2026

26. 2026

27. 2026

28. 2026

29. 2026

30. 2026

31. 2026

32. 2026

33. 2026

34. 2026

35. 2026

36. 2026

37. 2026

38. 2026

39. 2026

40. 2026





3 -

Split AC Installation Guidelines

Split systems require separate indoor and outdoor units connected by refrigerant and electrical lines.

(1) Split AC Installation Guidelines

1. The indoor unit should be installed in a well-ventilated area, away from direct sunlight and heat sources. The unit should be installed at least 20 inches from the side walls and 4 inches from the ceiling. The outdoor unit should be installed in a well-ventilated area, away from direct sunlight and heat sources. The unit should be installed at least 70 inches from the ground and 4 inches from the side walls.
2. The indoor unit should be installed in a well-ventilated area, away from direct sunlight and heat sources. The unit should be installed at least 20 inches from the side walls and 4 inches from the ceiling. The outdoor unit should be installed in a well-ventilated area, away from direct sunlight and heat sources. The unit should be installed at least 70 inches from the ground and 4 inches from the side walls.
3. The indoor unit should be installed in a well-ventilated area, away from direct sunlight and heat sources. The unit should be installed at least 20 inches from the side walls and 4 inches from the ceiling. The outdoor unit should be installed in a well-ventilated area, away from direct sunlight and heat sources. The unit should be installed at least 70 inches from the ground and 4 inches from the side walls.
4. The indoor unit should be installed in a well-ventilated area, away from direct sunlight and heat sources. The unit should be installed at least 20 inches from the side walls and 4 inches from the ceiling. The outdoor unit should be installed in a well-ventilated area, away from direct sunlight and heat sources. The unit should be installed at least 70 inches from the ground and 4 inches from the side walls.

Split AC Installation Guidelines

Split systems require separate indoor and outdoor units connected by refrigerant and electrical lines.

Indoor Unit Placement:

- Maintain a minimum clearance of 6-8 inches (15-20 cm) from the ceiling to allow for proper airflow.
- Maintain a minimum clearance of 4-7.5 inches (12 cm) from the side walls to allow for proper airflow.
- Ensure the mounting bracket is slightly tilted (about 2-3 degrees) toward the drainpipe side to prevent indoor water leakage.
- It is not recommended to drill any structural elements (columns or beams) to install bracket. However, if drilling is unavoidable, drilling depth shall not exceed 25mm.

Outdoor Unit Placement:

- Place the unit on a flat, stable surface (like a concrete pad or manufacturer recommended bracket) to minimize vibrations that can damage the compressor.













10	$10 \times \frac{\text{دستبرد شدہ اثاثہ}}{\text{دستبرد شدہ اثاثہ کا مجموعہ}}$	30 مئی
100	30 مئی	

6 - مقررہ
نہیں ہوگا

Form of Bank Guarantee for Advance Payment

To: .....  
[name & address of Purchaser]

.....  
[name of Contract]

Gentlemen:

In accordance with the provisions of the Conditions of Contract, of the above-mentioned Contract, .....[name and address of Supplier] (hereinafter called “the Supplier”) shall deposit with ..... [name of Purchaser] a Bank Guarantee to guarantee his proper and faithful performance under the said Clause of the Contract in an amount of .....[amount of Guarantee] .....[amount in words].

We, the ..... [Bank or Financial Institution], as instructed by the Supplier, agree unconditionally and irrevocably to guarantee as primary obligator and not as Surety merely, the payment to ..... [name of Purchaser] on his first demand without whatsoever right of objection on our part and without his first claim to the Supplier, in the amount not exceeding \* ..... [amount of Guarantee]..... [amount in words].

We further agree that no change or addition to or other modification of the terms of the Contract or of Works to be performed there under or of any of the Contract documents which may be made between .....[name of Purchaser] and the Supplier, shall in any way release us from any liability under this Guarantee, and we hereby waive notice of any such change, addition, or modification.

\* An amount is to be inserted by the Bank or Financial Institution representing the amount of the Advance Payment, in Maldivian Rufiyaa.

This Guarantee shall remain valid and in full effect from the date of the advance payment under the Contract until .....[name of Purchaser] receives full repayment of the same amount from the Supplier.

Yours truly,  
SIGNATURE AND SEAL: .....  
NAME & ADDRESS OF BANK/INSTITUTION .....