

General

Form Factor
Display

Desktop
5.5" Color Touchscreen

Channels of I/O
Built-In DSP
Maximum Sampling Rate
Number of Microphone Inputs
Built-In Microphone
Input Level Adjustment
Number of Headphone Mixes

Analog:
4 Inputs / 4 Outputs
Yes
48 kHz / 24-Bit
4
No
6x Fader
4x Assignable with Mix-Minus

Signal Processing

Pad
Gain/Trim Range
Solo/Mute

No
0 to 76 dB
Solo-in-Place/AFL, Mute, PFL per Input Channel

Connectivity

Analog Audio I/O
Phantom Power
Digital Audio I/O
Host Connection / USB
Host Connection Protocol
USB (Non-Host)
MIDI I/O
Expansion Slots
Wireless

4x Combo XLR-1/4" TRS Balanced/Unbalanced M
2x 1/4" TRS Balanced Line Output
4x 1/4" TRS Unbalanced Headphone Output
48 V, Selectable On/Off
No
2x USB-C
USB 3.0 / 3.1/3.2 Gen 1
No
No
No
Wi-Fi / Bluetooth

Performance

Frequency Response

Maximum Output Level
Headphone Output Power

Mic Inputs:
20 Hz to 20 kHz
Monitor Outputs:
20 Hz to 20 kHz
Line Outputs:
+4 dBu
250 mW

Impedance
EIN

Mic Inputs:
4 Kilohms
Hi-Z Inputs:
1 Megohm
-131.5 dBV A-Weighted

Digital Audio

Sample Rates
Sample Rate Conversion
Bit Depths

48 kHz
No
24-Bit

Audio Storage & Playback



Media/Memory Card Slot

Single Slot: microSD/microSDHC/microSDXC

Compatibility

OS Compatibility

Computer: macOS 10.15 or Later / Windows 10.18

Mobile Device Compatibility

Mobile: iPadOS Only

Power

Power Requirements

iPad

AC/DC Power Adapter

AC/DC Power Adapter (Included) or USB Bus Pow
15 VDC at 2 A (Included)

Physical

Dimensions

12.2 x 10.7 x 3.3" / 30.9 x 27.3 x 8.3 cm

Weight

4.4 lb / 2.0 kg

Packaging Info

Package Weight

7.02 lb

Box Dimensions (LxWxH)

12.9 x 11.9 x 5.6"

Microphone

Microphone Type

Broadcast/Podcast

Polar Pattern

Cardioid

Element Type

Dynamic

Sound Field

Mono

Orientation

End Address

Controls

No

Pad

No

Circuitry

Solid-State

Performance

Frequency Response

20 Hz to 20 kHz

Sensitivity

-57 dB (at 1 kHz)

Connectivity

Analog Output Connector

1x XLR 3-Pin Male

Power

Power Sources

No Power Required

Physical

Color

Black

Mounting Thread Size

5/8"-27 Female

Dimensions

H: 2.4 x W: 4.3 x L: 6.8" / H: 62 x W: 109 x L: 172

Weight

2.1 lb / 937 g

Packaging Info

Package Weight

2.6 lb

Box Dimensions (LxWxH)

8.9 x 6.7 x 3.8"



Microphone Mounting

Mic Thread Size

5/8"-27 Male

Audio I/O to Mic

XLR 3-Pin Female

Boom

Total Reach

40" / 101.6 cm

Riser & Base

Maximum Height

14.00" / 35.56 cm

Base Clamp Range

2.3" / 5.8 cm

Cable

Included Cable

Integrated

Cable Length

15' / 457.2 cm

Audio Connector to Host Device

XLR 3-Pin Male

Physical

Color

Black

Load Capacity

5 lb / 2.27 kg

Weight

4.47 lb / 2.02 kg

Packaging Info

Package Weight

6.2 lb

Box Dimensions (LxWxH)

23.5 x 7.4 x 3.5"



[Handwritten signature]

Headphone

Wearing Style	Dual Ear with Headband
Earpiece Design	<i>Foldable: Yes</i>
Open/Closed-Back	<i>Earpiece Swivel: Yes</i>
Sound Field	Over-Ear (Circumaural)
Driver Type	Closed-Back
Driver Size	Stereo
Impedance	Dynamic
Active Noise Cancellation	1.6" / 40 mm
Frequency Response	64 Ohms
Sensitivity	No
Maximum Power Handling	20 Hz to 20 kHz
Built-In Controls	96 dB
Microphone	1200 mW
Built-In Mic	No
Connectivity	No
Wired Audio Connector	1x 1/8" / 3.5 mm TRS
Included Adapter	1/4" TRS
Connector Plating	Gold
Cable Design	Detachable / Straight
Cable Length	3' / 0.9 m (Audio Cable/Straight) 10' / 3 m (Audio Cable/Coiled)
Physical	
Color	Black
Environmental Resistance	No
Weight	7.5 oz / 213 g
Packaging Info	
Package Weight	1.965 lb
Box Dimensions (LxWxH)	9.2 x 8.7 x 4.1"



Handwritten signature in blue ink.

Quantity	1
Card Type	microSDHC with Full-Size SD Adapter
Storage Capacity	32 GB
Bus Type	UHS-I
Speed Class	Class 10 / U1 / V10 / A1
Read Speed	Maximum: 100 MB/s
Write Speed	Minimum: 10 MB/s
Built-in Write-Protect Switch	On Adapter Only
Operating Conditions	32 to 158°F / 0 to 70°C
Storage Conditions	-13 to 185°F / -25 to 85°C
Packaging Info	
Package Weight	0.03 lb
Box Dimensions (LxWxH)	3.8 x 2.9 x 0.3"



[Handwritten signature]