

[illegible][illegible][illegible]

3.5 د داسو په پرتله تر ۴۵٪ زیاتره رښتیا لري چې د ۴۵٪ تر ۶۰٪ پورې وي. په دې توګه،

[illegible][illegible]

4.2 نَسْرَتُو سِرْ | اَجْعَلْ سِرَّ سِرِّهِمْ | نَاجِيْكَمْ وَ سَوِّرْ | اَرْدِ اَرْوَ قُمْ قَرْسُوْ | وَ اَنْزِلْ قُرْسُوْ | نَحْنُ سَوِّرْ سِرْ | نَاجِيْكَمْ

[illegible][illegible][illegible][illegible][illegible]

5.2 $\frac{1}{2} \frac{1}{2} \frac{1}{2} \frac{1}{2} \frac{1}{2}$

[illegible]

(م) اِجْرَاوُ تَجْتَرِسْ وِهَاجْزِي تَرْسِرْ هَوَسِرْ زَرْزَسْرَدِ اَنْجَمَزْدِ اِجْرَاوُ سَرْدِي زَغَوْزِو

اِنَارَسَرْدِ هَسَرِ تَجْتَرِسْ خُسِرْ سَرُو سَهْمَدَرْهَوُ وَ هَوَانِدَرْهَوُ.

[illegible]

3.9 مەلۇم / نىزىرىدىكى / دىنارنىڭ ئۆسۈش سۈرئىتى:

[illegible]

4.9 $\omega_{\text{max}} = 2\pi \times 10^3 \text{ rad/s}$

[illegible][illegible][illegible]

1.5.9 $\text{أَلَمْ يَكُنْ لَهُ الْكُتُبُ الْأُولَىٰ} \text{ أَلَمْ يَكُنْ لَهُ الْكُتُبُ الْأُولَىٰ} \text{ أَلَمْ يَكُنْ لَهُ الْكُتُبُ الْأُولَىٰ}$
 $\text{أَلَمْ يَكُنْ لَهُ الْكُتُبُ الْأُولَىٰ} \text{ أَلَمْ يَكُنْ لَهُ الْكُتُبُ الْأُولَىٰ} \text{ أَلَمْ يَكُنْ لَهُ الْكُتُبُ الْأُولَىٰ}$

$$\text{CP} \cdot 0.005 \cdot \text{LD} = (\frac{\pi}{6} \pm \frac{\pi}{18}) \approx \frac{\pi}{9} \quad \text{CP}$$

$$\overline{\nu} \overline{\nu}^c \overline{e} e = \text{LD}$$

[illegible][illegible][illegible]

INFORMATION SHEET FOR UNIVERSAL TOILET CONSTRUCTION

Project: Universal Toilet Block (Single-Story)

Overall Building Size: 12 ft × 10 ft

Purpose: Construction of an accessible, universal-design toilet block with two cubicles, wash area, and ramp.

1. BUILDING DIMENSIONS

- **Total Building Footprint:** 12 ft (length) × 10 ft (width)
- **Toilet Cubicles:**
 - Two units, each 6 ft × 5 ft
- **Wash Area:**
 - Located in front of toilet cubicles
 - Approx. 12 ft × 2–3 ft (depending on wall thickness)
- **Building Height:**
 - 9 ft floor-to-ceiling (recommended for ventilation and comfort)
 - Optional parapet: 1 ft above roof level

2. ACCESSIBILITY REQUIREMENTS (UNIVERSAL DESIGN)

Entrance Ramp

- Width: 8 ft
- Slope: **1:12 ratio** (for every 1-inch rise → 12 inches length)
- Handrails on both sides
- Non-slip surface

Doors

- Minimum width: **36 inches (3 ft)**
- Outward-opening
- Lever-type handles

Flooring

- Non-slip tiles (wet-area grade)
- Slope towards floor drain

3. TOILET CUBICLE SPECIFICATIONS (EACH 6 ft × 5 ft)

Fixtures

- **Universal (Western) toilet seat**
- **Grab bars:**
 - Horizontal bar beside toilet
 - Vertical bar near door
 - Rear support bar
- **Handheld bidet spray**
- **Toilet paper holder**
- **Clothes hook** (accessible height)
- **Emergency call button** (low-level)

Clearances

- Wheelchair turning radius: **5 ft** (at least one cubicle)
- Clear side space for wheelchair transfer

4. WASH AREA

- **Two wash basins**
- Basin height: **32–34 inches**
- **Lever or sensor taps**
- **Mirrors** at accessible height
- **Soap dispensers**
- **Hand dryer** or paper towel dispenser
- Floor drain with proper slope

5. STRUCTURAL & MATERIAL DETAILS

Walls

- Concrete block or cement board
- Waterproofing layer
- Interior tiles up to 7 ft height

- Exterior weather-resistant paint

Roof

- GI roofing sheet or concrete slab
- Proper rainwater runoff
- Ventilation gaps or exhaust fan

Floor

- Anti-slip ceramic tiles
- Proper drainage slope

Doors

- PVC or aluminum wet-area doors
- Minimum width: 3 ft

Windows / Ventilation

- Louvered windows or ventilation blocks
 - Exhaust fan recommended
-

6. ELECTRICAL & PLUMBING

Electrical

- LED light in each toilet
- LED light in wash area
- Exhaust fan
- Waterproof switches outside each toilet

Plumbing

- Inlet and outlet pipes for each toilet
 - Floor drains
 - Water tank connection (if required)
 - Proper sewage connection
-

7. EXTERNAL WORKS

- **Ramp** with handrails
- **Paved pathway** to entrance

• פדף ארז חסר סוף יד סגור פדף ארז חסר סוף