

[illegible][illegible]

12:00 ، 2026 10

سُورَةُ النُّجُومِ : ٥٦

(I)288/2026/048

وَحَدَّثَنَا أَبُو بَكْرِ بْنُ أَبِي شَيْبَةَ عَنْ يَحْيَى بْنِ سَعْدٍ عَنْ زَيْدِ بْنِ جَدَانَ عَنْ عَبْدِ اللَّهِ بْنِ مَرْثَدَةَ عَنْ أَبِي هُرَيْرَةَ رَضِيَ اللَّهُ عَنْهُ أَنَّ رَسُولَ اللَّهِ صَلَّى اللَّهُ عَلَيْهِ وَسَلَّمَ قَالَ:

02 ۰۰۰۰۰۰۰۰ ۲۰۲۶

13:00 ، 2026 17

مَدْرَسَةُ

1

[illegible]

2026 ڇڏو 15 ڏينهن ۾ ڏيکارڻ جي ڳالهه ڪئي. (I)288/2026/042 ڊسٽرڪٽ ڊسٽرڪٽ

[illegible][illegible][illegible]

2

2.1 $\frac{d}{dt} \left(\frac{1}{2} m v^2 \right) = \frac{1}{2} m \frac{d}{dt} (v^2) = m v \frac{dv}{dt} = m v a$

[illegible]

لَا تُرَوِّدُنَا فِي سُبُلِ الْفِتْنَةِ وَتُجَاهِدْ بَيْنَنَا وَبَيْنَ الْكُفَرِ وَالْمُنَافِقِينَ وَتُجَاهِدْ بَيْنَنَا وَبَيْنَ الْيَهُودِ وَالنَّصَارَى وَالْمَجُوسِ وَالْمَغَافِرِينَ.

2.2 اَرْتَاوَجَع مَرِي سَوَجَر مَرِي سَوَسَر

(٢٠٢ ٢٠٢٠)



مجلس الوزراء
السلطة الفلسطينية
السلطة الفلسطينية
السلطة الفلسطينية

Category	Specifications
General	
Type	Excavator
Recommended Brand/Model	Kobelco, JCB
Year and Manufacture	2000 or later
Tonnage (Tons)	7-8 Tons
Working weight (Kg)	7,820 – 8,950 kg
Bucket Capacity (m ³)	0.28 – 0.35 m ³
Bucket Type	Backhoe Bucket
Dozer blade	Must include
Gradeability	58% (30°)
Shoe Width	≥ 450 mm
Tail Swing	≥ Short Radius (SR)
Engine	
Engine Fuel Type	Diesel
Rated power (kW/rpm)	52.3–53.7 kW (70–72 hp) @ 2,100 rpm
Cooling method	Water cooling
Number of cylinders	4 - 6
Displacement (L)	2 – 2.5L
Type	Direct injection, turbocharges, built-in intercooling
Maxium torque	200 N·m/1,600 min-1 or higher





Speed	
Travel Speed (km/h)	$\geq 2.7 / 5.0$ km/h
Hydraulic System	
Pump type & Pump info:	One variable displacement pump + gear pump
Cab & Control	
Cab features	All-weather, sound-suppressed steel cab mounted on the silicon-sealed viscous mounts and equipped with a heavy, insulated floor mat or similar
Control	Two hand levers and two-foot pedals for travel, Electric rotary-type engine throttle or similar
Oil/Fuel Capacity	
Fuel Tank (L)	120 L
Hydraulic Tank (L)	60 - 80
Engine Oil change (L)	10 - 20
Coolant (L)	8 - 15
Hydraulic system	Twin Variable Displacement Axial Piston Pumps
Dimensions	
Length (mm)	≥ 6.1 m
Width (mm)	≥ 2.3 m
Height (mm)	≥ 2.7 m
Track Gauge	≥ 1.85 m
Ground Clearance	≥ 350 mm



Additional Spare/Tool Kit to be Delivered with the Vehicle (Standard Kit which comes with Excavator)

Key Features

- ## Suitable Applications

- Harbor and jetty construction
- Utility trenching
- Island infrastructure projects
- Road works
- Material handling
- Landscaping and dredging support

[illegible][illegible][illegible][illegible][illegible]

4.3 $\frac{100.00}{100} \times 100 = 100.00$ (100% of the total)

[illegible][illegible][illegible]

7720700438001
 7720700438001

4.6

5

6

- 7

- مەھسۇس تەربىيە ئۆزگەرتىش ۋە تەربىيە ۋەزىپىسى 2026 يىلى 17 ئاينىڭ 17 كۈنى قوشۇمچە 13:00 سائەتتە
 تەكشۈرۈلگەن.
- مەھسۇس تەربىيە ئۆزگەرتىش ۋە تەربىيە ۋەزىپىسى 2026 يىلى 17 ئاينىڭ 17 كۈنى قوشۇمچە 13:00 سائەتتە
 تەكشۈرۈلگەن.

- [illegible]

8

سُورَةُ النُّحْلِ: فِي ثَمَانِ عَشَرَ آيَةً، وَفِيهَا مِائَتَانِ وَخَمْسُونَ كَلِمَةً، وَفِيهَا ثَمَانُونَ حَرْفًا، وَفِيهَا ثَمَانُونَ وَخَمْسُونَ حَرْفًا، وَفِيهَا ثَمَانُونَ وَخَمْسُونَ حَرْفًا، وَفِيهَا ثَمَانُونَ وَخَمْسُونَ حَرْفًا.