

<p>1.1.3 Cooling Equipment</p> <p>1.1.4 Exhaust system</p> <p>1.1.5 Alternator</p> <p>1.1.6 Generator arrangement and drive</p> <p>1.1.7 Fuel system</p> <p>1.2 Factory testing</p> <p>1.3 Finishing</p>	<p>Cooling equipment compromising a heavy-duty tropical radiator, together with pusher type cooling fan and guards to be fitted. The radiator core should be electroplated with silver solder tin plated to prevent early failure due to corrosion. Coupon plated radiators are acceptable. the radiator has to be mounted on the vibration mounts and it should have enough strength to with stand the radiator.</p> <p>450 mm of stainless steel below type flexible exhaust, together with suitable flanges and fittings shall be supplied for each silencer.</p> <p>The alternator shall be brushless revolving type altenator, having class H insulation on both the stator and field windings. It shall be built and rated to BS 5000, tropically impregnated with voltage regulation being in the order of +/- 1.5% from no load to full load under the steady state conditions assuming a speed variation not exceeding 4% on the engine. Anti-Condensation Coil to be fitted in the Alternator.</p> <p>The simplex type base plate is of heavy duty rolled steel constructed, bolted and electrically welded, drilled on the underside to allow the fitting of foundation bolts. The engine and the alternator are to be mounted on a base plate and vibration mounts to be mounted underside of the base plate. The vibration mounts are to be supplied as loose item.</p> <p>A fuel day tank of 12 hours capacity complete with level indicator, drain plug, filler, fuel return with fuel outlet connections and a fuel filter fitted with outlet connection is to be mounted. These mounts are are to be supplied as loose item. All necessary fittings to be supplied in conformity with fuel flow diagram.</p> <p>The generator should be fully tested at the manufacturer workshop in the presence of client/apointees to check the ratings, overload, functional tests on a dummy load prior to dispatch in case the bidder is unable to provide factory test as mentined, the bidder shall provide an extended warranty of one extre year than mentioned in iteme no 10 of this document.</p>	<p>Nos.</p>	<p>1</p>
---	---	-------------	----------



		ދަތުރުފުޅު	
	After assembling the genset zinc coated self-etching primer should be applied to the complete set.		
1.4	Warranty Generator set should carry a warranty of one year from the date of commissioning the equipment.		
1.5	Literature and drawings		
1.5.1	How to handle the generation equipment	Nos.	1
1.5.2	Electrical wiring diagram	Nos.	1
1.5.3	Engine operation and maintenance manual	Nos.	1
1.5.4	Engine parts catalogue	Nos.	1
1.5.5	Generator parts catalogue	Nos.	1
1.5.6	Generator operation and maintenace manual	Nos.	1
1.5.7	Generator AVR manual	Nos.	1
1.5.8	Governor control unit manual	Nos.	1
1.5.9	Engine shop manual	Nos.	1
	*Two separate manuals for the generator set shall be supplied and all the manuals to be enclosed in a fiber box file and the file should be labeled as "FENAKA CORP. LTD.400kW Generator Manuals".		
1.6	Accessories The Components shall meet the British Standard and ISO standards. Items are for the above mentioned generator sets.		
1.6.1	Primary silencer barrel(to match engine exhaust)	Nos.	1
1.6.2	Secondary silencer barrel(to match engine exhaust)	Nos.	1
1.6.3	3m Exhaust pipe dia(to match engine exhaust)	Nos.	4
1.6.4	Elbows having dia (to match the engine exhaust)	Nos.	4
1.6.5	Flanges having dia (to match the engine exhaust)	Nos.	8

އިތުރު ސަފުހާތަކުގައި ބަޔާންކޮށްފައިވާ ގޮތުގައި ޖެނެރެޓަރުގެ ޕާޓްތަކުގެ ނަންބަރުތައް ހިމާރުކޮށްފައިވާ ފޯމުގައި ފުރިހަމަކުރުމަށް ފަސޭހަވާނެއެވެ.

ފަނަކާ ޕްރައިވެޓް ލިމިޓެޑް:

- ޖެނެރެޓަރުގެ ސަފުހާތަކުގައި ބަޔާންކޮށްފައިވާ ގޮތުގައި (ޖެނެރެޓަރުގެ ޕާޓްތަކުގެ ނަންބަރުތައް ހިމާރުކޮށްފައިވާ ފޯމުގައި) ފުރިހަމަކުރުމަށް ފަސޭހަވާނެއެވެ. ޖެނެރެޓަރުގެ ޕާޓްތަކުގެ ނަންބަރުތައް ހިމާރުކޮށްފައިވާ ފޯމުގައި ފުރިހަމަކުރުމަށް ފަސޭހަވާނެއެވެ.
- ޖެނެރެޓަރުގެ ސަފުހާތަކުގައި ބަޔާންކޮށްފައިވާ ގޮތުގައި ފުރިހަމަކުރުމަށް ފަސޭހަވާނެއެވެ.
- ޖެނެރެޓަރުގެ ސަފުހާތަކުގައި ބަޔާންކޮށްފައިވާ ގޮތުގައި ފުރިހަމަކުރުމަށް ފަސޭހަވާނެއެވެ. ޖެނެރެޓަރުގެ ޕާޓްތަކުގެ ނަންބަރުތައް ހިމާރުކޮށްފައިވާ ފޯމުގައި ފުރިހަމަކުރުމަށް ފަސޭހަވާނެއެވެ.
- ޖެނެރެޓަރުގެ ސަފުހާތަކުގައި ބަޔާންކޮށްފައިވާ ގޮތުގައި ފުރިހަމަކުރުމަށް ފަސޭހަވާނެއެވެ.

