Technical Specification

QTY	Specification
	IR Network IP Dome Indoor Camera (Minimum 5MP)
	Image Sensor: Progressive Scan CMOS
	Day & Night: IR cut Filter
	IR Range: Minimum up to 15m
	Angle Adjustment: Pan: 0° to 355°, tilt: 0° to 75°
	Video Compression: H.265+
	Simultaneous Live: Minimum up to 5 channels
	Power Supply: PoE
35	Other Features / Smart Functions:
	Intelligent IR
	Auto iris Control
	Wide Dynamic Range (WDR)
	Motion Detection, Line Cross Detection,
	Intrusion Detection, Object Removal detection, Face Detection
	3D Digital Noise Reduction
	Must Support ONVIF
	Accessories: Junction Box for Selected Camera
	IR Network IP Bullet Indoor Camera (Minimum 5MP)
	Image Sensor: Progressive Scan CMOS
	Day & Night: IR cut Filter
	IR Range: Minimum up to 15m
25	Field of View: Horizontal Field of View 90° (minimum)
	Video Compression: H.265+
	Simultaneous Live: Minimum up to 5 channels
	Power Supply: PoE
	Other Features / Smart Functions:
	Intelligent IR

[Auto iris Control
	Wide Dynamic Range (WDR)
	Motion Detection, Line Cross Detection,
	Intrusion Detection, Object Removal detection, Face Detection
	3D Digital Noise Reduction
	Must Support ONVIF
	Accessories: Junction Box for Selected Camera
	360° IP Indoor Dome Camera (Minimum 12MP)
	Image Sensor: Progressive Scan CMOS
	Day & Night: IR cut Filter
	IR Range: Minimum up to 15m
	Field of View: 360° Viewing angle
	Video Compression: H.265+
	Simultaneous Live: Minimum up to 5 channels
	Power Supply: PoE
12	Multi-View Streaming: 360° Overview, Dewarped Panorama, Corridor
	and Quad views
	Other Features / Smart Functions:
	Intelligent IR
	Wide Dynamic Range (WDR)
	Motion Detection
	3D Digital Noise Reduction
	Must Support ONVIF
	Accessories: Junction Box for Selected Camera
	Outdoor Network PTZ Camera (Minimum 4MP)
	Image Sensor: Progressive Scan CMOS
	Zoom: Optical 40x & Digital 16x
2	Day & Night: IR cut Filter
	IR Range: Minimum up to 150m
	Pan/Tilt Range: Pan: 0° to 360° endless, Tilt: -15° to 90°
	Video Compression: H.265+
L	<u>_</u>

	Power Supply: PoE
	Other Features / Smart Functions:
	Wide Dynamic Range (WDR)
	Motion Detection, Line Cross Detection,
	Intrusion Detection, Face Detection
	3D Digital Noise Reduction
	Must Support ONVIF
	Accessories: Wall Mount Bracket, Junction Box for Selected Camera
	Network Video Recorder
	IP Camera Inputs: Minimum 64 channels
	Interface: 2x HDMI, 1x VGA
	Recording Modes: Manual, Schedule, Motion detection & continuous
	Search Mode: Time/Date, alarm, motion detection & Exact Search
	Backup Modes: USB Device, network, Internal SATA burner & eSATA
	Network Interface 2 x RJ45 Ports (10/100/1000 Mbps)
1	Internal HDD: 64TB.
	Video Compression
	Other Features / Functions:
	Should support 3 rd party IP Camera models
	Auto Search IP Cameras
	PTZ Control and Functions
	Support ONVIF, PSIA and RTSP protocols
	Wide Angle Lens Dewarping
3	48 Port Layer 3 Managed PoE Switch with 2 SFP Port
	Preferred brands: CISCO, HP, HUAWEI, DELL, UBIQUITI
2	Network Keyboard Controller with Joystick
	Control Protocols: IP, RS-485, RS-232
	Control: 3D/4D Zoom Joystick for PTZ Control
	Compatibility: PTZ Dome Cameras and NVR selected for the above-
	mentioned items.
	L

Features / Functions:
Preset Position, Auto Scan, Auto Pan, Auto Tour and Pattern Control

Preferred Brands:

CCTV Camera & NVR : Hikvision, Dahua, Ubiquiti, Axis

Network Switch: CISCO, HP, HUAWEI, DELL, UBIQUITI