Technical Specification/Minimum Requirement for Double Cab Vehicle

SN	CRITERIA	DEPARMENTTAL REQUIRMENT	OFFERERD
1	Concret	Devible cab Bishup and delivits to the Little	SPECIFICATION
1	General	Double cab Pickup, model with two-wheel drive	Make:
		mode, suitable for driving both in ON-ROAD	
		condition giving smooth economic performance and	Model:
		in OFF-ROAD conditions capable of delivering strong	
		adequate traction and suitable needed for safe	Country of Origin:
		driving in rough, sandy or slippery road conditions.	
		Gross vehicle Weight of the vehicle not less than	
		2800 Kgs and shall have seating capacity for at least	
		5 passengers including driver.	
2	Engine / Fuel	Water cooled diesel engine, developing rated	Make:
		Power output not less than 120 Hp and Torque not	
		less than N-m at rated RPM. The Engine shall be fully	Model:
		equipped with all necessary items / accessories and	
		controlling devices	
3	Emission	The emission standard of the offered vehicle must be	
	Standard	in compliance applicable standard which is to be	
		certified by Ministry of Transport	
4	Gauges	Fitted with all the gauges, indicators, signals as	
		necessary for efficient operation, functional	
		monitoring, vehicle performance and maintenance	
		that includes Battery charge indicator, water	
		temperature, fuel, oil pressure, transmission gauge	
		etc. with all standard items of offered model vehicle	
5	Transmission	Auto shift, (auto gearing) at least five forward and	
		one reverse, all forward synchromesh	
6	Ground	Minimum 210 mm	
	clearance	Higher ground clearance preferred	
7	Suspension	Suitable for toughest terrain, smooth ride, stable	
		handling and comfortable driving conditions.	
		Front: Independent, Double wishbone with coil	
		spring and stabilizer/Torsion Bar	
		Rear: Leaf springs / shock absorbers	
8	Tyres	Standard Size	
9	Steering	Power assisted/power Steering	
10	Breaks	Front Disc type, rear drum type, hydraulic operated	
		on all wheels, and parking brake	
11	Fuel Tank	Not less than 65 Liters	
	Capacity		
12	Cab	4 doors, all metallic cab with insulated roof, right	
		hand drive, laminated glass windscreen, wipers, glass	
		windows on doors, through ventilation, comfortable	
		and adjustable seats for driver and passenger, two	
		sun visors, and two side view mirror, Rear body to	
		metallic, pickup type with drop type tail board	11 011

12	Classia d	6. 11. 1.1.1.1.1.	
13	Chassis and	Steel, heavy duty high rigidity frame structure	
11	Frame	suitable for rough road conditions with hoot at front	
14	Essential	Head light, tail and rear light, reversing light and	
	Accessories	turn signals	
		Cabin lights	
		Speedometer / odometer	
		Heavy duty front bumper	
		1 spare wheel with tyre and tube	
		Hydraulic jack with handle	
		Mud guard at front and rear	
		Floor mats	
		Steering Cover	
		Seat Cover	
		Electric control ORVMS	
		Alloy Wheels	
		Front seat for driver and co-passenger	
		Foot Steps	
		Air Conditioner with heater	
		• ABS	
		Power Windows	
		Central Door Locking system	
		Dual Airbag	
		Reverse Camera	
		Panorama view monitor	
		Speed Auto Door lock	
		• First aid kit	
		Rear parking sensor	
		• Fog light	
		• 7 inches Tough screen	
		Bluetooth connectivity with streaming Audio	
		Second – row under – seat storage	
		CD/MP3 Player, Preferably with Radio, MW & FM	
		Equipped with all accessories offered in standard	
		model but not limited to the above items	
		model but not innited to the above items	
15	Instructions	All sign and instructions in the vehicle shall be in	
		English	
16	Manual	One copy of the Operator's and Owner's Instructions	
		and Maintenance manual in English shall be supplied	
17	Tools	A set of tools, with a tool bag, as required for general	
4-		maintenance shall be supplied	
18	Color	Standard color	
19	Proven	The vehicle offered shall be a current model under	
	performance	standard production by the manufacturer for at	
		least one year	
		The bidder shall provide the manufacturer's data	
i de		of the performance of the unit to include the fuel	
80	30	consumption, performance curve of the engine	
3	100	and production capacity	

TE.

20	Warranty	The vehicle shall be warranted for at least 30,000 km or minimum of one year after acceptance	
21	Initial service	The supplier shall provide with the vehicle all the necessary filters and spare parts required for the first two services, after the vehicle has been commissioned and accepted	
22	Delivery	The Double – cab Pickup, RHD 1 unit, shall be delivered to KULHUDHUFFUSHI REGIONAL HOSPITAL	

Note:

- 1. QUOTE THE PRICE; INCLUDING SHIPPING AND TAXES IN BIDDING PRICES.
- 2. The major items are indicated by bold and highlighted letters/alphabets/figures in the above technical specifications. Non-Compliance of these major items will result in non-responsiveness of the bid offered.

