

Technical Specification – Server Rack and UPS

Server Rack

- 03 Nos x 42U Server Rack Enclosure 600mm x 1070mm w/ Sides Black
 - Standard enclosure for low to medium density server and networking applications.
 - Should include Baying hardware, Key(s), Keyed-alike doors and side panels, leveling feet, Mounting hardware, pre-installed casters, Side panels
 - Vendor-neutral mounting compatibility with all EIA-310 compliant 19" equipment.
 - Split rear doors, Perforated front and rear door, Quick release doors
 - Integrated electrical grounding
 - Basic Zero U rack PDU, 16A, 208/230V, (15) C13
 - Installation

UPS

- 01 Nos x 6000VA 230V UPS
 - Double-conversion on-line power protection with scalable runtime
 - Web/SNMP management card
 - Output: (8) IEC 60320 C13, (2) IEC 60320 C19
 - Input Connections: Hard wire 3-wire
 - Hot-swappable batteries
 - Automatic internal bypass
 - Form factor: rack/tower convertible
 - Installation and configuration
- 02 Nos x 3000VA 230V UPS
 - Double-conversion on-line power protection with scalable runtime
 - Web/SNMP management card
 - Output: (8) IEC 60320 C13, (2) IEC 60320 C19
 - Input Connections: Hard wire 3-wire
 - Hot-swappable batteries
 - Automatic internal bypass
 - Form factor: rack/tower convertible
 - Installation and configuration