



2 تحریر

درستی سے اپنے تحریر کو تصحیح کریں

- ۱. صحیح نمبر لکھیں اور تصحیح کریں:
- ۲. غلط نمبر:
- ۳. جوڑ کر لکھیں:
- ۴. ہٹا دیں:

۵. دیکھیں کہ اس خط میں کتنی غلطیاں ہیں اور ان کو تصحیح کریں اور اس کے ساتھ ساتھ اس خط کو بھی تصحیح کریں:

- 1.
- 2.
- 3.
- 4.
- 5.
- 6.
- 7.

۶. اس خط کو تصحیح کریں اور اس کے ساتھ ساتھ اس خط کو بھی تصحیح کریں:

.....
.....
.....

- ۷. صحیح نمبر لکھیں:
- ۸. صحیح نمبر لکھیں:

۹. تصحیح کریں اور اس کے ساتھ ساتھ اس خط کو بھی تصحیح کریں:

.....
.....
.....
.....



تقریر 3

SPECIFICATION FOR VIDEO CONFERENCING SOLUTION

CAMERA

- Smooth motorized pan, tilt and zoom controlled from remote or console
- Pan +/- 90°
- Tilt +35° / -45
- 10x lossless HD zoom
- Field of View
- Diagonal: 90°
- Horizontal: 82.1°
- Vertical: 52.2°
- Full HD 1080p 30fps
- H.264 UVC 1.5 with Scalable Video Coding (SVC)
- Autofocus
- 5 camera presets
- Far-end control (PTZ) of Conference Cam product (with supported services)
- Kensington security slot
- Video mute/unmute LED indicator
- Standard tripod thread

REMOTE CONTROL

- Camera, speakerphone, and call control
- 5 camera presets
- Docks on speakerphone
- IR 8.5 m range
- CR2032 battery (included)



SPEAKERPHONE

- Full-duplex performance
- Acoustic echo cancellation
- Noise reduction technology
- Ultra-wideband audio
- Pairs with mobile devices via Bluetooth and NFC
- LCD for caller ID, call duration and other functional response
- LEDs for speakerphone streaming, mute, hold, and Bluetooth
- Tactile buttons for call answer/end, volume and mute, Bluetooth, and camera controls
- 5 camera presets for pan, tilt, and zoom settings
- Kensington security slot

MICOROPHONE

- Pickup Range: 6 m
- Pickup range with expansion mics: 8.5 m
- Four omnidirectional, beamforming microphones
- Frequency response: 100Hz – 11KHz
- Sensitivity: -28 dB +/-3Db
- Distortion: <5% from 200Hz

HUB / CABLES / POWER

- Central Hub connects and powers all components
- Under-table mounting adhesive included
- One cable to camera: 5 m
- One cable to speakerphone: 5 m
- Extended cables available: 10 and 15 m
- One USB cable for connection to PC/Mac: 2 m
- AC Power adapter with regional plugs
- Power cable: 3 m



MOUNT

-Dual-purpose bracket works for both wall mounting and tabletop elevation

COMPATIBILITY AND CERTIFICATIONS

- Plug-and-play USB connectivity
- Certified for Skype for Business and ready for Teams
- Zoom Certified
- Fuze Certified
- Microsoft Cortana®
- Cisco Jabber®
- Compatible with BlueJeans, BroadSoft, GoToMeeting, Vidyo, and other video conferencing, recording, and broadcasting applications that support USB cameras

WARRANTY INFORMATION

- 2-Year Limited Hardware Warranty