



**UPS**  
**Qty: 25 (FIS)**

General	
User replaceable batteries	Yes
Automatic battery tests	Yes
Energy star qualified	Yes
Battery backup outlets	4
Surge protected outlets	4
Total outlets	8
Automatic volatfe regulator	Yes
Power chute personal edition software	Yes
Replaceable battery	Yes
Input	
Voltage	180-270V
Type of input protection required	gL fuse
Maximum input current	12.0A
	140 Vac < Vin < 276 Vac
	@50% load / 184 Vac <
	Vin < 276 Vac @ 100%
Voltage tolerance	LOAD
Frequency	50/60 Hz
Power factor	>0.99
Current distorsion	≤7%
Power cord	6ft (1.83 meters)
Output	
Output power capacity	420Watts / 700VA
Nominal output voltage	120V
	(3) Nema 5-15R (Battery backup)
Output connectors	(3) Nema 5-15R
	selector_surgetitle)

ދިވެހިރާއްޖޭގެ ޖުމްހޫރިއްޔާ ގުޅިގެން

80% ފަސޭހަވާ ދަނީ:

15% ފަސޭހަވާ ދަނީ:

5% ފަސޭހަވާ ދަނީ:

ސެލެކްޓްކުރެވޭ ޕްރޮޖެކްޓްތަކުގެ ތެރެއިން 3345173، 3345174 ޕްރޮޖެކްޓްތަކުގެ ތެރެއިން

ޕްރޮޖެކްޓްތަކުގެ ތެރެއިން 3345111 ޕްރޮޖެކްޓްތަކުގެ ތެރެއިން









