



ދިވެހިސަރުކާރުގެ ގެޒެޓް ގައި ބަޔާންކުރި ގޮތުގައި
ދަތުރު، ދިވެހިސަރުކާރުގެ ގެޒެޓް ގައި

ދިވެހިސަރުކާރުގެ ގެޒެޓް ގައި ބަޔާންކުރި ގޮތުގައި - ދަތުރު، ދިވެހިސަރުކާރުގެ ގެޒެޓް ގައި

ސަރުކާރުގެ ގެޒެޓް ގައި ބަޔާންކުރި ގޮތުގައި (IUL)30-C/30/2017/147 ދަތުރު، ދިވެހިސަރުކާރުގެ ގެޒެޓް ގައި

#	PRODUCT NAME	SPECIFICATION	QTY
1	Generator	Capacity:- 4-5 KVA Sound proof- silent type Fuel type: diesel Air cooled	1
2	Generator	Capacity:- 1-2.6 KVA Sound proof- silent type Fuel type: diesel or Petrol Air cooled	1
3	Water Pump	Flow rate :- 550 liters per minute at 22.5 meters of head. Inlet – 2” Outlet – 2” Fuel type: diesel Air cooled	1
4	Water Pump	Flow rate :- 1300 liters per minute at 25 meters of head. Inlet – 4” Outlet – 4” Fuel type: diesel 4 Stroke engine, Air cooled electric start	1
5	Pressure Pump	Flow rate: - 200 liters per minute at 30 meters of head. Inlet – 2” Outlet – 1.5” 2.4kw, 3ph, Voltage,220-250	6
6	Pressure Pump	Flow rate: - 460 liters per minute at 41 meters of head. Inlet – 2” Outlet – 1.5” 3.0kw, 3ph, Voltage 220-250	6
7	Submersible Pump	Flow rate: - 240 liters per minute at 12 meters of head. Outlet – 1.5”	6

		Voltage 220-250	
8	Submersible Pump	Flow rate: - 85 liters per minute at 8 meters of head. Outlet – 1" Voltage 220-250	10
9	Clear Spring Reinforced hose pipe	Diameter 2"	2 Roll
10	Clear Spring Reinforced hose pipe	Diameter 1.5"	2 Roll
11	Clear Reinforced hose pipe	Diameter 1"	10 Roll
12	Clear Reinforced hose pipe	Diameter 3/4"	10 Roll
13	Clear Reinforced hose pipe	Diameter 1/2"	10 Roll
14	Colored hose pipe	Diameter 1/2"	5 Roll

10 October 2017