

13	Light source	Lamp
14	watt lamp	240
15	Lamp life (hours)	4000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)
Optics		
16	shooting distance	0.25:1
17	Projection distance (m)	0.45m - 0.56m
18	zoom type	Fixed
19	Focal length (mm)	3.72mm/0.146"
20	native offset	118%
21	shooting distance	0.25:1
Connectivity		
22	connections	Inputs 1 x HDMI 1.4a / 3D + MHL, 1 x HDMI 1.4a / 3D, 1 x VGA (YPbPr/RGB), 1 x Composite Video, 1 x 3.5mm Audio, 2 x USB-A reader/wireless Outputs 1 x VGA, 1 x Audio 3.5mm Control 1xRS232, 1xRJ45
General		
23	PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
24	2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i /p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
25	3D compatibility	Side-by-Side: 1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
26	3D	Full 3D
27	Security	Security bar, Kensington Lock, Password protected interface
27	Functional condition	5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
29	Remote control	Remote control with laser and mouse function
30	Speakers	1
31	Watts per speaker	16

HDMI Cable Specification

1	Cable Type	Fiber Optic HDMI Cable
2	Connector Type	HDMI to HDMI cable with gold plated connector
3	Length	50 M (164 feet)
4	Color	Black
5	Compatible Devices	Projector, Laptop, Monitor, Television, PlayStation, DVD Player, Personal Computer, Xbox

