

JB Mixer 搅拌机系列



■ JB150

■ JB300

■ JB650

JBZK Vacuum Mixer 真空搅拌机系列



■ JBZK150


■ JBZK400

■ JBZL750

- 可选用电脑编程自动化控制,可贮存99个配方,可配数显温度控制仪。
- 采用SUS304不锈钢材质,符合HACCP卫生标准。
- 主轴采用双轴承结构,提高了搅拌效率及搅拌效果。
- 正、反转自由控制、自动出料。
- The whole machine adopts SUS304 that is compliance with HACCP standard.
- Optional Computerized Auto Control.99 recipes can be stored. Temperature display.
- Double shaft fan-shape propeller.Good mixing and agitating effect.
- Positive and inversive rotation control.Auto-dump function.



■ JB2000



在真空状态下,物料被负压后膨胀同时被浆叶进行径向翻滾、轴向回流,完成混合均匀的搅拌功能。浆叶有多种形式,真空翻轉搅拌机采用双轴椭圆螺旋布置的扇形浆叶,对物料进行径向搅拌,同时完成轴向回流,使物料得以充分混合均匀,达到理想的混合效果。采用优质不锈钢材料制造,可采用水流直接冲洗,方便卫生、符合卫生标准要求。出料的开关均采用油缸操作,只需拨动按钮即可实现翻轉全部动作,操作非常方便。本机采用减速机齿轮链条传动,使机器运动平稳可靠、噪音低,是同等产品的佼佼者。

Under the vacuum state, materials are mixed and blended by double shaft fan-shape propeller after materials have been expanded under the pressure.

The materials will be mixed sufficiently, several type of propellers.

The machine adopt double shaft ellipse and helix paddle, can mix the material in radial direction and perform axial back flow, so that can mix material completely and reach the perfect mixing effect.

Whole body of the machine made by SUS304 stainless steel, it is qualified the sanitary standard, can clean directly by using water.



■ JBZK1200

The switch of discharging adopts cylinder operation, just press the switch then can perform overturn function, and it is very convenient.

The drive system of this machine is designed by reducer gear-chain drive, can ensure the machine run smoothly with low noise. Which is the best among same level.

型号 Type	外形尺寸 (mm) External Dimension	电压 Voltage	总功率 (kw) Power	容积 (L) Volume	生产能力 (kg) Capacity	重量 (kg) Weight	桨叶形式 Propeller
JB50	740 × 810 × 775	3PH 380V 50HZ	0.74	50	20-30	180	①
JBZK50H	740 × 810 × 775	3PH 380V 50HZ	1.11	50	20-30	280	②
JB150 (单轴) (Single Shaft)	1200 × 682 × 1060	3PH 380V 50HZ	2.2	150	80-110	384	③
JB150H	1440 × 1100 × 1200	3PH 380V 50HZ	3	150	80-120	400	③
JB300	1500 × 800 × 1300	3PH 380V 50HZ	4.4	300	220-265	476	③
JB0700	1330×1190×1670	3PH 380V 50HZ	6	700	480-525	750	③
JB1200	1930 × 1490 × 1700	3PH 380V 50HZ	11	1200	820-900	1420	③
JB2000	3200 × 1900 × 2300(3900开盖)	3PH 380V 50HZ	22	2000	1200-1400	2830	③
JB 3000	3500 × 2200(2900扶梯) × 3400(4350开盖)	3PH 380V 50HZ	34	3000	< 1600kg/次	2830	③

型号 Type	外形尺寸 (mm) External Dimension	电压 Voltage	总功率 (kw) Power	容积 (L) Volume	生产能力 (kg) Capacity	重量 (kg) Weight	真空度 (MPa) Vacuum	桨叶形式 Propeller
JBZK50	740 × 810 × 775	3PH 380V 50HZ	1.11	50	20-30	208	-0.09	①
JBZK150 (单轴) Single Shaft	1200 × 700 × 1260 1400 × 1200 × 1345	3PH 380V 50HZ	2.75 3.75	150 150	80-110 65-105	350 500	-0.09 -0.09	① ①
JBZK300	1560 × 1470 × 1400	3PH 380V 50HZ	5.5	300	150-210	760	-0.09	③
JBZK400	1560 × 1470 × 1400		6	400	260-300	760	-0.09	③
JBZK650	1870 × 1600 × 1700		9.5	650	440-490	1070	-0.09	②③
JBZK1200	1985 × 2300 × 1920	3PH 380V 50HZ	13.2	1200	820-900	1870	-0.09	②③
JBZK2000	3200 × 2300 × 2200(3900开盖)		22	2000	1200-1400	2830	-0.09	②③
JBZK3000	3500 × 2300 × 2400(4350开盖)		30	3000	1500-2100	4200	-0.09	②③
JBZL150 (液氮) Refrigeration	1500×1050×1900	3PH 380V 50HZ	5.15	150	≤80	700	-0.09	③
JBZL750 (液氮)	1660×1550×2160		15	750	≤380	1600	-0.09	③
JBZL1200 (液氮)	2150 × 1900 × 2400		39.7	1200	≤600	2400	-0.09	③
JBZL2000 (液氮)	3200 × 2000 × 3000(3400开盖)		34	2000	≤1100	3600	-0.09	③
JBZL3000 (液氮)	3500 × 2200 × 3400(4350开盖)		41	3000	≤1600	4500	-0.09	③

备注: 生产能力根据产品密度不同会有差异
Notes: capacity is different based on density of product.