



THE PERFORMER
VALUE

MATERIAL HANDLING TIRES

THE PERFORMER

Optimized for Value

THE PERFORMER is simple and efficient, providing perfect performance at a competitive price.



ENERGY SAVING

Good energy saving and efficiency due to low rolling resistance.



OPERATING TIME

Good operating time in suitable applications.



LIFE TIME

Good tire life providing very good value.



CORNERING STABILITY

Good cornering stability enabling safety and comfort.



Low abrasion tread compound.

High lug depth and optimized aspect ratio.



TREAD COMPOUND

BASE COMPOUND

BEAD WIRES

THE PERFORMER

GRI
WE'LL GET YOU THERE

Tire Size	Rim Size	Clip on	Profile	Tire Dimensions		Tire Dimensions		Tire load capacity on forklifts at Max. Speed			
								12 Miles/h (Lbs)		20 Km/h (Kg)	
				Max width ±1% (mm)	OD ± 2% (mm)	Max width ±1% (inch)	OD ± 2% (Inch)	Load wheel	Steer wheel	Load wheel	Steer wheel
4.00-8	3.00 D-8		GS	104	406	4.09	15.98	2095	1610	950	730
5.00-8	3.00 D-8		GS	116	446	4.57	17.56	3120	2405	1415	1090
15x4 1/2-8 125/75-8	3.00 D-8	•	GS	103	377	4.06	14.84	2295	1765	1040	800
16x6-8 150/75-8	4.33 R-8	•	GS	139	407	5.47	16.02	3210	2535	1455	1150
18x7-8 180/70-8	4.33 R-8	•	GS	153	451	6.02	17.76	4730	3640	2145	1650
6.00-9	4.00 E-9	•	GS	139	520	5.51	20.47	4155	3195	1885	1450
21x8-9 200/75-9	6.00 E-9	•	GS	174	516	6.85	20.31	6075	4675	2755	2120
6.50-10	5.00 F-10	•	GS	153	565	6.02	22.24	5160	3970	2340	1800
200/50-10	6.50 F-10	•	GS	188	456	7.40	17.95	5445	4190	2470	1900
23x9-10 225/75-10	6.50 F-10	•	GS	188	582	7.52	22.80	7595	5840	3445	2650
7.00-12	5.00 S-12	•	GS	164	647	6.46	25.47	6435	4940	2920	2240
23x10-12	8.00 G-12	•	GS	234	580	9.21	22.83	8310	6390	3770	2900
27x10-12 250/75-12	8.00 G-12	•	GS	232	675	9.13	26.50	8600	6615	3900	3000
7.00-15	5.50-15	•	GS	175	705	7.01	27.76	7815	6005	3545	2725
7.00-15	6.00-15	•	GS	175	705	7.01	27.76	7815	6005	3545	2725
250-15 250/70-15	7.00-15	•	GS	211	712	8.43	28.03	10470	8045	4750	3650
250-15 250/70-15	7.50-15	•	GS	211	712	8.43	28.03	10470	8045	4750	3650
8.15-15 (28x9-15) 225/75-15	7.00-15	•	GS	202	681	8.23	26.81	8310	6390	3770	2900
8.25-15	5.50-15	•	GS	194	809	7.64	31.85	10470	8045	4750	3650
8.25-15	6.50-15	•	GS	193	809	7.60	31.85	10470	8045	4750	3650
300-15 315/70-15	8.00-15	•	GS	243	812	9.57	31.97	12895	9920	5850	4500
355/65-15	9.75-15	•	GS	291	826	11.46	32.52	17190	13230	7800	6000
9.00-20	6.50-10		GS	225	971	8.86	38.23	11770	9810	5340	4450
9.00-20	7.00-20		GS	225	971	8.86	38.23	11770	9810	5340	4450
10.00-20	7.00-20		GS	250	1006	9.84	39.61	13230	11025	6000	5000
10.00-20	7.50-20		GS	250	1006	9.84	39.61	13230	11025	6000	5000
10.00-20	8.00-20		GS	250	1006	9.84	39.61	13230	11025	6000	5000
11.00-20	7.50-20		GS	265	1088	10.43	42.83	14420	12015	6540	5450
11.00-20	8.00-20		GS	265	1088	10.43	42.83	14420	12015	6540	5450
11.00-20	8.50-20		GS	265	1088	10.43	42.83	14420	12015	6540	5450
12.00-20	8.00-20		GS	265	1088	10.43	42.83	16535	13780	7500	6250
12.00-20	8.50-20		GS	265	1088	10.43	42.83	16535	13780	7500	6250



GRI takes a long-term view, looking beyond the obvious horizon. The **GREEN X CIRCLE** is a global farmer ecosystem connecting natural rubber farmers with crop farmers worldwide focusing on sustainable farming practices to increase productivity that will benefit farming communities and inspire greatness for generations to come.



GRI produces high-grade specialty tires that are built sustainably using pure natural rubber in Sri Lanka. Founded in 2002, the company produces material handling solid tires, radial agriculture tires and construction tires. GRI has operations in 9 countries, and a business presence in more than 50 countries. In 2018, GRI opened an advanced manufacturing plant in Sri Lanka to produce radial agricultural tires. In 2020, GRI commenced construction of a large mixing facility for tire compounds and in 2021 began further expansion of its advanced specialty tire plant. GRI ensures its commitment to sustainability and environmental protection through all its strategies and processes. Environmentally sustainable growth is our strategic goal, both now and for generations to come.

info@gritires.com
www.gritires.com

www.facebook.com/GRIitires/
www.instagram.com/gritires/?hl=en

LIMITED WARRANTY

All tires manufactured by Global Rubber Industries (Pvt) Ltd are covered by limited warranty, which includes cover against material, workmanship and other manufacturing defects subject to the usage of the tires under specified conditions. If any tire covered by this warranty is deemed unserviceable due to aforementioned defects, we will either repair the tire or provide an allowance to purchase a new tire at the current price as a percentage of the worn off tread of the original tire at the time of making the claim.

The cost of transportation, service and paid sales tax will be borne by the owner of the claimed tire. The limited warranty is exclusively applicable to the tire owner who is using the product. No other warranty of liability, expressed or implied, is applicable to the limited warranty or to our products.