



James

BY SONANCE


VISUAL EXPERIENCE with QUADRATECH DATA SHEET




10.125" (257mm)
Cut-Out
Diameter
Front View



3.78" (96.1mm)
Mounting Depth
(Open Back)
Side View



3.92" (99.6mm)
Shallow Enclosure
Side View



5.92" (150.4mm)
Deep Enclosure
Side View

VXQ88R TECHNICAL SPECIFICATIONS

SKU	VXQ88R 66058 - Each
Tweeter	1" (25mm) four titanium domes, Ferrofluid-cooled, acoustic back chamber
Woofer	8" (203mm) Aluminum cone, Santoprene surround
Dispersion Technology	Quadratech Tweeter with Cymatic Diffuser
Frequency Response	30Hz - 20kHz +/-3dB
Impedance	8 ohms nominal; 6 ohms minimum
Power Handling (RMS)	5 watts minimum; 175 watts maximum
Sensitivity (2.83V/1m)	91dB SPL
Mounting Technology	1-stage, 4 x RotoLock® Clamps
Environmental	Conforms to Military Standard 810G for humidity, salt spray, temperature & UV, IP-67 waterproof rating
Environment Temp	-30°F - 194°F (-34°C - 90°C)
Round Micro Trim Grille (Dia)	11.54" (293.2mm)
Round Trimless Grille (Dia)	11.17" (283.8mm)
Square Micro Trim Grille (WxH)	11.54" x 11.54" (293.1mm x 293.1mm)
Square Trimless Grille (WxH)	11.18" x 11.18" (283.9mm x 283.9mm)
Speaker Mounting Depth (D)	3.78" (96.1mm)
Mounting Depth + Shallow Encl. (D)	3.92" (99.6mm)
Mounting Depth + Deep Encl. (D)	5.92" (150.4mm)
Cut-Out Dims (Dia)	10.125" (257mm)
Shipping Weight	20.0 lbs. (9.0kg)

VXQ 8" ROUND ACCESSORIES

VXQ8R-GRILLE-T 8" XPC Micro Trim Round Grille / Each	60479	VXQ8-SE-R 8" Round Shallow Enclosure / Each	60470
VXQ8R-GRILLE-NT 8" XPC Trimless Round Grille / Each	60480	VXQ8-DE-R 8" Round Deep Enclosure / Each	60471
VXQ8SQ-T 8" XPC Micro Trim Square Adapter / Each	60491	FLEXBRK-8-R 8" Round Flex Bracket / 5x Pair	92247
VXQ8SQ-NT 8" XPC Trimless Square Adapter / Each	60492		

LIMITED FIVE (5) YEAR WARRANTY Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the period stated above. Sonance will at its option and expense during the warranty period, either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. For more details please refer to the product manual.

©2024 Sonance. All rights reserved. Sonance is a registered trademarks of Dana Innovations. Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product specification information visit our website at www.sonance.com.